

Notification of a Body in the framework of a technical harmonization directive

From : Subdirección General de Calidad y Seguridad Industrial / Ministerio de Industria, Energía y Turismo
Paseo de la Castellana, 160
28071 Madrid
Spain

To : **European Commission**
Enterprise Directorate-General
-
B 1049 Brussels
Other Member States

Reference :

Legislation : 97/23/EC Pressure equipment

Body name, address, telephone, fax, email, website :

NORCA INGENIERIA DE CALIDAD, S.L.U.
c/ Peña Herbosa, 20
39003 Santander (Cantabria)
Spain
Phone : +34 942314521
Fax :
Email : norca@intertek.com
Website : www.norca.es // www.intertek-spain.es

Body :

NB 2313

Created : 26/07/2011 | **Last update :** 16/08/2011

Period of validity of the notification :

Valid until : 31/12/2015

The body is formally accredited against :

EN 45004 - EN ISO/IEC 17020

Name of National Accreditation Body (NAB) : ENAC - Entidad Nacional de Acreditación

The accreditation covers the product categories and conformity assessment procedures concerned by this notification : Yes

Tasks performed by the Body :

Created : 26/07/2011 | Last update : 16/08/2011

Product family, product /Intended use/Product range	Procedure/Modules	Annexes or articles of the directives
<p>Pressured tanks</p> <p>Pressure equipment</p> <p>Pressure-cookers</p> <p>Portable fire extinguishers</p> <p>Safety accessories</p> <p>Pressure accessories</p> <p>Portable fire extinguishers and bottles for breathing apparatus</p> <p>Pressure equipment and assemblies except for portable fire extinguishers and bottles for breathing apparatus</p> <p>Components for water and gas fire suppression and extinguishing systems</p> <p>Pressure equipment and assemblies of categories II, III, IV as parts of LPG and water installations</p> <p>Pressure equipment and assemblies of categories II, III, IV as parts of refrigeration installations</p> <p>Conformity assessment of safety valves fitted to fixed LPG (liquefied petroleum gas) storage vessels</p> <p>Conformity assessment of 'hermetically sealed' compressor units used in refrigeration systems</p> <p>Pressure equipment as referred to in 1.1, 1.3 and 1.4 of Article 3 and assemblies as referred to in 2.2 and 2.3 of Article 3, made from ferritic materials with wall temperatures of -40°C to 250°C, or from austenitic materials with wall temperatures of -200°C to 300°C, applying a calculation method in accordance with the first indent of 2.2.3(a) of Annex I, or a design method in accordance with 2.2.4 of Annex I in combination with the first indent of 2.2.3(a)</p> <p>Pressure equipment and assemblies as defined in Article 1 for use exclusively in fire-fighting plant, excluding fired or otherwise heated pressure equipment presenting a risk of overheating</p>	<p>Internal manufacturing checks with monitoring of the final assessment</p> <p>Conformity to type</p> <p>Product verification</p> <p>Approval of permanent joining procedures</p> <p>European approval of materials</p> <p>Approval of permanent joining personnel</p>	<p>Annex III - Module A1</p> <p>Annex III - Module C1</p> <p>Annex III - Module F</p> <p>Annex I, 3.1.2</p> <p>Article 11</p> <p>Annex I, 3.1.2</p>