



# **Synopsis of RFCS Projects 2015 – 2016**

**Full list of projects co-financed by the Research Fund  
for Coal and Steel of the European Union**



## Table of Contents 1

Projects listed by Project Number

Project Number	Technical Group	Project Acronym	Page				
709418 (2016)	TGS6	MUSTMEF	68	RFSR-CT-2015-00014	TGS6	INCROHSS	66
709424 (2016)	TGS1	DEPREX	33	RFSR-CT-2015-00015	TGS6	LIGHTOUGH	67
709434 (2016)	TGS8	INNOSEIS	91	RFSR-CT-2015-00016	TGS7	JOININGTWIP	77
709435 (2016)	TGS5	HIJETROD PILOT	60	RFSR-CT-2015-00017	TGS7	HOTFORM	78
709493 (2016)	TGC2	DIRPRIMCOAL	19	RFSR-CT-2015-00018	TGS7	ICUT	79
709504 (2016)	TGS4	ROLLOILFREE	49	RFSR-CT-2015-00019	TGS7	EFFIPRESS	80
709526 (2016)	TGS8	REFOS	92	RFSR-CT-2015-00020	TGS8	SLIMAPP	85
709553 (2016)	TGS9	ROBOHARSH	110	RFSR-CT-2015-00021	TGS8	SHOWTIME	86
709600 (2016)	TGS8	PUREST	93	RFSR-CT-2015-00022	TGS8	FREEDAM	87
709601 (2016)	TGS7	ULTRASLIM	81	RFSR-CT-2015-00023	TGS8	NEWREBAR	88
709607 (2016)	TGS6	TIANOBAIN	69	RFSR-CT-2015-00024	TGS8	JABACO	89
709620 (2016)	TGS2	PERMONLIST	40	RFSR-CT-2015-00025	TGS8	PROLIFE	90
709629 (2016)	TGC3	FLEXICAL	25	RFSR-CT-2015-00027	TGS9	PREVENTSECDUST	106
709669 (2016)	TGS9	CYBER-POS	111	RFSR-CT-2015-00028	TGS9	POWGETEG	107
709694 (2016)	TGS5	MACO PILOT	61	RFSR-CT-2015-00029	TGS9	GASNET	108
709711 (2016)	TGS6	TOOLKIT	70	RFSR-CT-2015-00030	TGS9	AUTOADAPT	109
709740 (2016)	TGS2	DISSTEC	41	RFSR-CT-2015-00031	TGS2	SIMULEAF	39
709741 (2016)	TGC2	PROMOTEE	20				
709755 (2016)	TGS6	OPTIQPAP	71				
709782 (2016)	TGS8	OUTBURST	94				
709803 (2016)	TGS6	NANOFORM	72				
709807 (2016)	TGS8	LASTEICON	95				
709816 (2016)	TGS1	STACKMONITOR	34				
709828 (2016)	TGS6	MILDROLLING	73				
709830 (2016)	TGS3	SHELL-THICK	45				
709855 (2016)	TGS6	HIGHQP	74				
709868 (2016)	TGC1	CERES	14				
709892 (2016)	TGS8	HOLLOSSTAB	96				
709920 (2016)	TGS4	REDUWEARGUID	54				
709923 (2016)	TGS2	OSCANEAF	42				
709936 (2016)	TGS8	OPTOSTEEL	97				
709954 (2016)	TGC3	DP700-PHASE 1	26				
709962 (2016)	TGS8	DURAMECH	98				
709976 (2016)	TGC3	NIBALO725	27				
710040 (2016)	TGS8	REDUCE	99				
710066 (2016)	TGS9	DROMOSPLAN	112				
710068 (2016)	TGS8	SBRIPLUS	100				
710078 (2016)	TGC2	INNOWATREAT	21				
RFCR-CT-2015-00001	TGC1	SLOPES	9				
RFCR-CT-2015-00002	TGC1	STAMS	10				
RFCR-CT-2015-00003	TGC1	BEWEXMIN	11				
RFCR-CT-2015-00004	TGC1	MERIDA	12				
RFCR-CT-2015-00005	TGC1	MAPROC	13				
RFCR-CT-2015-00006	TGC2	SUPERCOAL	17				
RFCR-CT-2015-00007	TGC2	BINGO	18				
RFSR-CT-2015-00026	TGS9	PLANTTEMP	105				
RFSR-CT-2015-00001	TGS1	OPTIBLAFINS	31				
RFSR-CT-2015-00002	TGS1	ALCIRC	32				
RFSR-CT-2015-00004	TGS2	DYNSTIR	37				
RFSR-CT-2015-00005	TGS2	LEANSTORY	38				
RFSR-CT-2015-00006	TGS4	MANCOOL	50				
RFSR-CT-2015-00007	TGS4	MICROCONTROL-PLUS	51				
RFSR-CT-2015-00008	TGS4	INFOMAP	52				
RFSR-CT-2015-00009	TGS4	LASER4ROLLS	53				
RFSR-CT-2015-00010	TGS5	IMMARS	57				
RFSR-CT-2015-00011	TGS5	MICROCORR	58				
RFSR-CT-2015-00012	TGS5	ORSC	59				
RFSR-CT-2015-00013	TGS6	PRETICONTROL	65				



## Table of Contents 2

Projects listed by Project Acronym

Project Acronym	Technical Group	Project Number	Page
ALCIRC	TGS1	RFSR-CT-2015-00002	32
AUTOADAPT	TGS9	RFSR-CT-2015-00030	109
BEWEXMIN	TGC1	RFCR-CT-2015-00003	11
BINGO	TGC2	RFCR-CT-2015-00007	18
CERES	TGC1	709868 (2016)	14
CYBER-POS	TGS9	709669 (2016)	111
DEPREX	TGS1	709424 (2016)	33
DIRPRIMCOAL	TGC2	709493 (2016)	19
DISSTEC	TGS2	709740 (2016)	41
DP700-PHASE 1	TGC3	709954 (2016)	26
DROMOSPLAN	TGS9	710066 (2016)	112
DURAMECH	TGS8	709962 (2016)	98
DYNSTIR	TGS2	RFSR-CT-2015-00004	37
EFFIPRESS	TGS7	RFSR-CT-2015-00019	80
FLEXICAL	TGC3	709629 (2016)	25
FREEDAM	TGS8	RFSR-CT-2015-00022	87
GASNET	TGS9	RFSR-CT-2015-00029	108
HIGHQP	TGS6	709855 (2016)	74
HIJETROD PILOT	TGS5	709435 (2016)	60
HOLLOSSTAB	TGS8	709892 (2016)	96
HOTFORM	TGS7	RFSR-CT-2015-00017	78
ICUT	TGS7	RFSR-CT-2015-00018	79
IMMARS	TGS5	RFSR-CT-2015-00010	57
INCROHSS	TGS6	RFSR-CT-2015-00014	66
INFOMAP	TGS4	RFSR-CT-2015-00008	52
INNOSEIS	TGS8	709434 (2016)	91
INNOWATREAT	TGC2	710078 (2016)	21
JABACO	TGS8	RFSR-CT-2015-00024	89
JOININGTWP	TGS7	RFSR-CT-2015-00016	77
LASER4ROLLS	TGS4	RFSR-CT-2015-00009	53
LASTEICON	TGS8	709807 (2016)	95
LEANSTORY	TGS2	RFSR-CT-2015-00005	38
LIGHTOUGH	TGS6	RFSR-CT-2015-00015	67
MACO PILOT	TGS5	709694 (2016)	61
MANCOOL	TGS4	RFSR-CT-2015-00006	50
MAPROC	TGC1	RFCR-CT-2015-00005	13
MERIDA	TGC1	RFCR-CT-2015-00004	12
MICROCONTROL-PLUS	TGS4	RFSR-CT-2015-00007	51
MICROCORR	TGS5	RFSR-CT-2015-00011	58
MILDROLLING	TGS6	709828 (2016)	73
MUSTMEF	TGS6	709418 (2016)	68
NANOFORM	TGS6	709803 (2016)	72
NEWREBAR	TGS8	RFSR-CT-2015-00023	88
NIBALO725	TGC3	709976 (2016)	27
OPTIBLAFINS	TGS1	RFSR-CT-2015-00001	31
OPTIQPAP	TGS6	709755 (2016)	71
OPTOSTEEL	TGS8	709936 (2016)	97
ORSC	TGS5	RFSR-CT-2015-00012	59
OSCANEF	TGS2	709923 (2016)	42
OUTBURST	TGS8	709782 (2016)	94
PERMONLIST	TGS2	709620 (2016)	40
PLANTTEMP	TGS9	RFSR-CT-2015-00026	105
POWGETEG	TGS9	RFSR-CT-2015-00028	107
PRETICONTROL	TGS6	RFSR-CT-2015-00013	65
PREVENTSECDUST	TGS9	RFSR-CT-2015-00027	106
PROLIFE	TGS8	RFSR-CT-2015-00025	90
PROMOTEE	TGC2	709741 (2016)	20
PUREST	TGS8	709600 (2016)	93
REDUCE	TGS8	710040 (2016)	99
REDUWEARGUID	TGS4	709920 (2016)	54
REFOS	TGS8	709526 (2016)	92
ROBOHARSH	TGS9	709553 (2016)	110
ROLLOILFREE	TGS4	709504 (2016)	49
SBRIPLUS	TGS8	710068 (2016)	100
SHELL-THICK	TGS3	709830 (2016)	45
SHOWTIME	TGS8	RFSR-CT-2015-00021	86
SIMULEAF	TGS2	RFSR-CT-2015-00031	39
SLIMAPP	TGS8	RFSR-CT-2015-00020	85
SLOPES	TGC1	RFCR-CT-2015-00001	9
STACKMONITOR	TGS1	709816 (2016)	34
STAMS	TGC1	RFCR-CT-2015-00002	10
SUPERCOAL	TGC2	RFCR-CT-2015-00006	17
TIANOBAIN	TGS6	709607 (2016)	69
TOOLKIT	TGS6	709711 (2016)	70
ULTRASLIM	TGS7	709601 (2016)	81



## Technical Group Coal 1

# Coal mining operation, mine infrastructure and management, unconventional use of coal deposits

### The scope TGC1 includes:

- Modern techniques for surveying deposits
- Integrated mine planning
- Highly efficient, largely automated excavation and mining technologies corresponding to the geological characteristics of EU hard coal deposits
- Appropriate support technologies
- Transport systems
- Power supply services, communication and information, transmission, monitoring and process control system
- Health and safety in mines, gas control, ventilation and air conditioning, occupational health safety
- Reduction of greenhouse emissions from coal deposits
- Return to the mine of mining waste, fly ash, desulphurisation, other forms of waste
- Refurbishment of waste heaps and the industrial use of residues from coal production and consumption
- Protection of water tables and the purification of mine drainage water
- Protection of surface installation against the effects of subsidence in the short and long term CO<sub>2</sub> geological storage
- Upgrading coal deposits; coal bed methane, enhanced coal bed methane, underground gasification, others







**TGC1 : Coal mining operation, mine infrastructure and management,  
unconventional use of coal deposits**

<b>RFCR-CT-2015-00001</b>	<b>SLOPES</b>			
	<i>Smarter Lignite Open Pit Engineering Solutions</i>			
Info	Type of Project	Research	Duration (months)	36
	Total Budget	3.309.995 €	Start Date	01/07/2015
	EU Contribution	1.985.998 €	End date	30/06/2018

Abstract

The SLOPES project brings together experts from across Europe to advance the current technology and methodologies applied to monitoring and risk analysis of slopes within open pit lignite mines. Modern techniques which aim to overcome the challenges of monitoring within open pit mines will be deployed and tested within real mines and results will be compared against physical model tests as well as rigorous numerical modelling. A reliability-based method for the evaluation of risks will be developed based on monitoring and modelling results which will provide significant benefits to design optimisation and decision support within real open-pit lignite mines.

Coordinator

**THE UNIVERSITY OF NOTTINGHAM**

*Country Scientific person in charge*

UK Dr. Alec MARSHALL

Partners

**CENTRE FOR RESEARCH AND TECHNOLOGY HELLAS**

EL Dr. Nikolaos KOUKOUZAS

**GEOCONTROL S.A.**

ES Mr Agustín MUÑOZ NIHARRA

**INSTITUT NATIONAL DE L'ENVIRONNEMENT INDUSTRIEL ET DES RISQUES**

FR Ms Auxane CHERKAOUI

**POLTEGOR INSTYTUT - INSTYTUT GORNICTWA ODKRYWKOWEGO**

PL Ms Barbara ROGOSZ

**SUBTERRA INGENIERIA S.L.**

ES Dr. José Miguel GALERA

**UNIVERSITY OF EXETER**

UK Prof. John COGGAN

**VYZKUMNY USTAV PRO HNEDE UHLI A.S.**

CZ Dr. Petr SVOBODA



**TGC1 : Coal mining operation, mine infrastructure and management,  
unconventional use of coal deposits**

<b>RFCR-CT-2015-00002</b>	<b>STAMS</b>			
	<i>Long-term Stability Assessment and Monitoring of flooded Shafts</i>			
Info	Type of Project	Research	Duration (months)	36
	Total Budget	3.153.076 €	Start Date	01/07/2015
	EU Contribution	1.891.845 €	End date	30/06/2018

Abstract

The main objective is to implement solutions to monitor and assess the stability of flooded shafts, for long periods of time. The objective will be achieved by subjecting a shaft (a) to periodic measurements, and (b) to continuous monitoring. This requires developing new technologies and achieving the following goals:

- Develop and test a Multi-functional Monitoring Module for periodic measurements;
- Develop and test an Ultrasonic Inspection Module, featuring the novel combination of ultrasonic profiling and ultrasonic imaging, to inspect shafts visually and measure possible deformations;
- Develop and test water dynamics and gas devices to continuously measure, analyse and assess the stability with provision to deploy sensors post-closure, that will withstand shaft filling operations;
- Develop and test a software control and analysis system to measure, in-situ and in real-time, significant differences that may indicate instability or significant changes in a flooded shaft;
- Develop a modelling approach to assess the long term stability of shafts during and after flooding by coupling the hydro-mechanical behaviour with the chemical reactions which occur between the aqueous solution and the shaft lining components.

For periodic measurements, inspection tools will be implemented with multiple instruments to perform measurements of water aggressiveness, gas production and to carry out macroscopic inspection. A software control system will be developed to analyse, in-situ, if there are significant changes in the conditions of the shafts acquiring information from the inspection modules and from the continuous measurement devices. For continuous measurements the objective is to install newly developed devices to monitor the water level recovery dynamics. Additionally this device could also be used as reference points to make comparisons between periodic images. The numerical simulation will be used to help the design and the interpretation of the in-situ measurement.

Coordinator	Country	Scientific person in charge
<b>INSTITUT NATIONAL DE L'ENVIRONNEMENT INDUSTRIEL ET DES RISQUES</b>	FR	Dr. Marwan AL HEIB
Partners		
<b>ASOCIACION PARA LA INVEST. Y EL DESAR. INDUSTRIAL DE LOS RECURSOS NAT.</b>	ES	Mr Carlos REOL
<b>ASS. POUR LA RECHERCHE ET LE DEV. DES METHODES ET PROC. IND., ARMINES</b>	FR	Prof. Faouzi HADJ-HASSEN
<b>THE COAL AUTHORITY</b>	UK	Dr. Steven KERSHAW
<b>DMT GMBH &amp; CO KG</b>	DE	Mr. Klaus SIEVER
<b>GLOWNY INSTYTUT GORNICTWA</b>	PL	Dr. Stanislaw PRUSEK
<b>HULLERAS DEL NORTE, S.A.</b>	ES	Mr. Fran MIRANDA
<b>KOMPANIA WEGLOWA S.A.</b>	PL	Mr. Lucjan GAJDA
<b>SPOLKA RESTRUKTURYZACJI KOPALN SA* SRK SA</b>	PL	Mr Pawel RYDLEWSKI
<b>UNIVERSIDAD CARLOS III DE MADRID</b>	ES	Prof. Carlos BALAGUER
<b>UNIVERSITY OF EXETER</b>	UK	Prof. John COGGAN



**TGC1 : Coal mining operation, mine infrastructure and management, unconventional use of coal deposits**

<b>RFCR-CT-2015-00003</b>	<b>BEWEXMIN</b>			
	<i>Bucket wheel excavators operating under difficult mining conditions including unmineable inclusions and geological structures with excessive mining resistance.</i>			
Info	Type of Project	Research	Duration (months)	36
	Total Budget	2.817.117 €	Start Date	01/09/2015
	EU Contribution	1.690.271 €	End date	31/08/2018

Abstract

In newly-opened as well as in existing lignite mines are increasingly difficult mining conditions. Mainly due to the presence of growing number of undiggable inclusions and partings of excessive mining resistance in overburden. During exploitation of such centers there are large dynamic and impulse loads. Already working excavators and often newly designed are not fully adapted to such conditions. This results in frequent breakdowns, resulting in the exclusion of the machine from normal operation. The aim of the project is to develop solutions to reduce failure rates of bucket wheel excavators working in those conditions. This will be achieved either by reducing the sensitivity of excavators on pulse load or by efforts to reduce the size of dynamic loads.

The project includes three packages. The first package WP1 includes:

- The experimental determination of the dynamic surplus from mass forces and the linkage of these surpluses with physico-mechanical characteristics of exploited soils;
- Method for determining of alternative computational strength of pulse loads;
- Determination of the requirements for flawless excavator work in specific conditions.

In the second - WP2 will be developed way to create a system to monitor stress excavator's structures leading to continuous assessment of the degree of construction effort, signaling of the damage possibility, and information on the residual fatigue strength.

The activities included in the third - WP3 is to strive to eliminate or just reduce the size of pulsed loads caused by encountering on undiggable obstacle (stone) by early detection of stones in the slope and adequate control of the excavator. Information collected by the system will also facilitate the correct interpretation of the signals sent by the stress monitoring system.

All three WPs are interrelated and create a complete set of activities aiming at the same goal, which is to reduce failure rates of bucket wheel excavators in difficult mining conditions.

Coordinator	Country	Scientific person in charge
<b>POLTEGOR INSTYTUT - INSTYTUT GORNICTWA ODKRYWKOWEGO</b>	PL	Ms Barbara ROGOSZ
Partners		
<b>SOCIETATEA COMPLEXUL ENERGETIC OLTENIA SA</b>	RO	Dr. IONUT COSMIN PREDOIU
<b>INSTYTUT TECHNIKI GORNICZEJ KOMAG</b>	PL	Dr. Jaroslaw TOKARCZYK
<b>NATIONAL TECHNICAL UNIVERSITY OF ATHENS</b>	EL	Dr. Theodoros MICHALAKOPOULOS
<b>PGE GORNICTWO I ENERGETYKA KONWENCJONALNA SA</b>	PL	Mr. Zbigniew MIZERSKI
<b>PUBLIC POWER CORPORATION S.A.</b>	EL	Dr. Christos ROUMPOS
<b>THE RESEARCH COMMITTEE OF THE TECHNICAL UNIVERSITY OF CRETE</b>	EL	Dr. Michael GALETAKIS
<b>UNIVERSITATEA DIN PETROSANI</b>	RO	Prof. Maria LAZAR
<b>VYZKUMNY USTAV PRO HNEDE UHLI A.S.</b>	CZ	Dr. Petr SVOBODA



**TGC1 : Coal mining operation, mine infrastructure and management,  
unconventional use of coal deposits**

<b>RFCR-CT-2015-00004</b>	<b>MERIDA</b>			
	<i>Management of Environmental Risks During and After mine closure</i>			
Info	Type of Project	Research	Duration (months)	48
	Total Budget	3.793.767 €	Start Date	15/12/2015
	EU Contribution	2.276.259 €	End date	14/12/2019

Abstract

The management of environmental risks during and after mine closure is a multi-hazard and multi-risk process that requires integration of interrelated environmental processes and combining their effects when considering hazard identification and risk characterisation. Failure to manage environmental impacts and risks in an acceptable manner throughout the mine closure and post-closure will result in the mining industry finding it increasingly difficult to obtain community and government support for existing and future projects. The objective of the current proposal (MERIDA) is to design and provide technical guidance on the implementation of necessary investigations that should be undertaken in order to develop a mine closure plan. The aim is to minimise the environmental impacts and risks during the mine closure and post-closure periods in accordance with the general principle that the mine must take responsibility and minimise all risks that can be foreseen. In practical terms, MERIDA will provide a planning tool that allows the design of a logical, step-wise approach to mine closure that can be progressively refined during the post-closure period and allows to address all relevant environmental risks.

The objectives of MERIDA are:

- To provide specific guidance on the issues that need to be considered when assessing the environmental impacts from coal mines at closure and post-closure stages;
- To identify the physical and chemical processes that affect environmental risks during mine closure and post-closure and establish monitoring and modelling methods that should be implemented in order to make reliable environmental impact predictions;
- To establish an integrated risk assessment methodology;
- To provide a practical methodology (written up as a technical guidance) that can be used for the evaluation of risk remediation measures in terms of their performance in risk reduction, practical implementation and cost.

Coordinator	Country	Scientific person in charge
<b>GLOWNY INSTYTUT GORNICTWA</b>	PL	Dr. Alicja KRZEMIEN
Partners		
<b>DMT GMBH &amp; CO KG</b>	DE	Dipl.-Ing. Karsten ZIMMERMANN
<b>HULLERAS DEL NORTE, S.A.</b>	ES	Mr. Fran MIRANDA
<b>INSTYTUT MECHANIKI GOROTWORU - POLSKIEJ AKADEMII NAUK</b>	PL	Prof. Jerzy KRAWCZYK
<b>IMPERIAL COLLEGE OF SCIENCE, TECHNOLOGY AND MEDICINE</b>	UK	Dr. Anna KORRE
<b>INSTITUT NATIONAL DE L'ENVIRONNEMENT INDUSTRIEL ET DES RISQUES</b>	FR	Mr Arnaud CHARMOILLE
<b>KOMPANIA WEGLOWA S.A.</b>	PL	Mr. Stanisław ADAMEK
<b>UNIVERSITY OF EXETER</b>	UK	Dr. Patrick FOSTER
<b>UNIVERSIDAD DE OVIEDO</b>	ES	Prof. Ana SUÁREZ SÁNCHEZ
<b>VYSOKA SKOLA BANSKA - TECHNICKA UNIVERZITA OSTRAVA</b>	CZ	Prof. Jaroslav DVORACEK



**TGC1 : Coal mining operation, mine infrastructure and management, unconventional use of coal deposits**

<b>RFCR-CT-2015-00005</b>	<b>MAPROC</b>			
	<i>Monitoring, Assessment, Prevention and Mitigation of Rock Burst and Gas Outburst Hazards in Coal Mines</i>			
Info	Type of Project	Research	Duration (months)	42
	Total Budget	4.122.079 €	Start Date	01/07/2015
	EU Contribution	2.473.246 €	End date	31/12/2018

Abstract

The main objectives of MapROC are to:

- Develop and field test rock burst and gas outburst prevention techniques based on the use of large diameter boreholes with alternative stress and gas pressure relief techniques such as blasting, slotting and/or high pressure water injection;
- Formulate a methodology to couple the near-real time processing of field monitored microseismic data with Artificial Neural Networks and Fractal Dimension analysis to develop a short-term prediction method for rock bursts and gas outbursts;
- Demonstrate the use of this prediction method as a tool for early risk assessment, prevention, and mitigation of rock bursts and gas outbursts;
- Numerically model the field application of the borehole stress/gas pressure relief methods as well as modelling stress control and protective mining options;
- Develop and validate a generic risk assessment methodology for the prevention and mitigation of rock bursts and gas outbursts; and
- Widely disseminate the research findings within the industrial and academic communities.

Coordinator

**IMPERIAL COLLEGE OF SCIENCE, TECHNOLOGY AND MEDICINE**

*Country*

UK

*Scientific person in charge*

Prof. Sevket DURUCAN

Partners

**ASOCIACION PARA LA INVEST. Y EL DESAR. INDUSTRIAL DE LOS RECURSOS NAT.**

ES

Dr. José Luis FUENTES-CANTILLANA

**PREMOGOVNIK VELENJE, D.D.**

SI

Dr. Simon ZAVSEK

**GLOWNY INSTYTUT GORNICTWA**

PL

Dr. Adam LURKA

**JASTRZEBSKA SPOLKA WEGLOWA S.A.**

PL

Mr Piotr BOJARSKI

**RHEINISCH-WESTFÄLISCHE TECHNISCHE HOCHSCHULE AACHEN**

DE

Dr. Bernhard KROOSS



**TGC1 : Coal mining operation, mine infrastructure and management,  
unconventional use of coal deposits**

<b>709868 (2016)</b>	<b>CERES</b>			
	<i>Co-processing of coal mine and electronic wastes: Novel resources for a sustainable future</i>			
Info	Type of Project	Research	Duration (months)	36
	Total Budget	3.335.839 €	Start Date	01/07/2016
	EU Contribution	2.001.503 €	End date	30/06/2019

Abstract

CEReS aims to introduce a series of technological improvements to reduce the risks associated with managing existing and future coal production wastes. Virtually all European coal miners have to manage AMD production when processing coal with relatively high sulfur content; to be able to maintain economically viable production they must adopt sustainable solutions for their wastes. CEReS will develop a generic technological approach for AMD generating wastes.

The co-processing approach proposed by CEReS employs AMD-generating coal production wastes as a cheap source of leaching solution (lixiviant) to recover metals from e-wastes. The novel flow-sheet will (i) remove the AMD-generating potential of coal wastes, ensuring their long term environmental stability while expanding avenues for their safe reuse; and (ii) enable selective recovery of base metals from waste PCBs, while concentrating precious and critical as well as rare earths into enriched substrates. Compared to best available technologies CEReS has numerous economic and environmental benefits by bringing together two waste streams from opposite ends of the supply chain; harvesting each as a novel resource for a single, coherent ‘grave-to-cradle’ process.

CEReS will use Poland as a case study region and will select and characterise suitable acidogenic coal wastes and obtain PCBs from regional e-waste processors. A cross-mapping exercise will identify the extent to which CEReS can be applied across the entire EU. A bioleaching circuit will be developed and optimised for acid and ferric iron lixiviant production and reuse options for leached residues elaborated. A PCB pyrolytic pre-processing step will be optimised, producing a metal-rich char. A char leaching reactor system will be developed to leach the metals using the biolixiviant from the coal wastes. These processes will be proven at lab (mini-pilot) scale and integrated through modelling and simulation to demonstrate the viability of the CEReS concept.

Coordinator

**THE UNIVERSITY OF EXETER**

*Country Scientific person in charge*

UK Dr. Chris BRYAN

Partners

**COMET TRAITEMENTS SA**

BE Dr. Pierre-François BAREEL

**UNIVERSITE DE LIEGE**

BE Prof. Stoyan GAYDARDZHIEV

**BUREAU DE RECHERCHES GEOLOGIQUES ET MINIERES**

FR Dr. Anne-Gwénaëlle GUEZENNEC

**CASPEO SARL**

FR Ms Marie-Véronique DURANCE

**TAURON WYDOBYCIE SPOLKA AKCYJNA**

PL Mr. Andrzej FRAS

**GLOWNY INSTYTUT GORNICWA**

PL Mrs Joanna CALUS MOSZKO

## Technical Group Coal 2

# Coal preparation, conversion and upgrading

### The scope TGC2 includes:

- Coal beneficiation
- Cokemaking
- Coal-derived carbon materials
- Coal gasification (hydrogen, syngas, synthetic natural gas etc.), including chemical and process aspects of underground coal gasification
- Coal liquefaction
- Environmental issues associated with coal upgrading processes







**TGC2 : Coal preparation, conversion and upgrading**

<b>RFCR-CT-2015-00006</b>	<b>SUPERCOAL</b>			
	<i>Coal-liquid based upgraded carbon materials for energy storage</i>			
Info	Type of Project	Research	Duration (months)	36
	Total Budget	2.075.609 €	Start Date	01/07/2015
	EU Contribution	1.245.365 €	End date	30/06/2018

Abstract

This project is aimed at the development of coal liquid-based carbon materials with superior properties for their use as active electrode materials in electrochemical energy storage systems as supercapacitors (SCs) and hybrid systems (battery-capacitor), a topic that is given top priority in the RFCS programme (upgrading of coal-derived liquids). In the present proposal, coal-derived liquids, such as coal tars and anthracene oil, are proposed as starting materials for the production of polymerized-isotropic/mesophase pitches, cokes and graphites to be used in the preparation of carbon materials with a tailored structure and, consequently, specifically targeted properties. Moreover, some of these materials will be subjected to different activation methods to develop the porous structure required for some of the proposed applications (electrodes in supercapacitors). The as obtained activated carbons (ACs) will be studied alone or combined with graphene (G), a high-tech material also produced and investigated as electrode material by itself. The development of this project will address the growing need of the electrical energy industry to have more efficient storage devices. One special feature is to choose proper treatment methods of transforming the irregular structure of the starting carbonaceous matter into the organised structure of carbon materials. The possibility of synthesizing carbon materials maximizing their porosity, tailoring their morphology, controlling their surface chemistry and retaining high electrical conductivity will allow the production of electrodes with improved performance and, subsequently, energy storage systems with higher power and energy densities. Thus, and from feedstocks with a low added-value, a new generation of supercapacitors and hybrid systems will be developed, which will help to a better and cleaner utilization of the energy resources.

Coordinator	Country	Scientific person in charge
<b>AGENCIA ESTATAL CONSEJO SUPERIOR DE INVESTIGACIONES CIENTIFICAS</b>	ES	Prof. Rosa MENENDEZ LOPEZ
Partners		
<b>CLAUDIU TOPROM SRL</b>	RO	Dr. Sorin AXINTE
<b>INDUSTRIAL QUIMICA DEL NALON S.A.</b>	ES	Dr. Juan José FERNANDEZ-RODRIGUEZ
<b>UNIVERSITY OF EAST ANGLIA</b>	UK	Dr. Sonia MELENDI
<b>POLITECHNIKA WROCLAWSKA - WROCLAW UNIVERSITY OF TECHNOLOGY</b>	PL	Prof. Grazyna GRYGLEWICZ
<b>UNIVERSITATEA POLITEHNICA DIN BUCURESTI</b>	RO	Dr. Georgeta PREDEANU



**TGC2 : Coal preparation, conversion and upgrading**

<b>RFCR-CT-2015-00007</b>	<b>BINGO</b>		
	<i>Bulk density and Internal Gas pressure in coke Ovens</i>		
Info	Type of Project	Research	Duration (months) 42
	Total Budget	1.897.471 €	Start Date 01/07/2015
	EU Contribution	1.138.483 €	End date 31/12/2018

Abstract

Wall Pressure is one of the major causes of coke oven degradation but it is impossible to measure it directly. Internal Gas Pressure is easier accessible; so the present project aims at increasing coke plant service life by controlling Internal Gas Pressure in industrial ovens. This project proposes to investigate parameters influencing Internal Gas Pressure measurements in stamp and gravity charging and to find correlations between Internal Gas Pressure measured at pilot and industrial scales. This study will allow to define guidelines for European coke plants to better monitor Internal Gas Pressure and to define limit values for safe operation.

Coordinator

**ARCELORMITTAL MAIZIERES RESEARCH S.A.**

*Country Scientific person in charge*

FR Mr Matthieu LANDREAU

Partners

**AKTIEN-GESELLSCHAFT DER DILLINGER HÜTTENWERKE AG**

DE Dr.-Ing. Rongshan LIN

**ARCELORMITTAL ATLANTIQUE ET LORRAINE SAS\*AAL**

FR Mrs Juliette DELINCHANT

**DMT GMBH & CO KG**

DE Dr. Drazen GAJIC

**THYSSENKRUPP STEEL EUROPE AG**

DE Mr. Viktor STISKALA

**VOESTALPINE STAHL GMBH**

AT Dipl.-Ing. Karl PILZ



**TGC2 : Coal preparation, conversion and upgrading**

<b>709493 (2016)</b>	<b>DIRPRIMCOAL</b>			
	<i>Direct Primary Coal Liquefaction via an Innovative Co-processing Approach with Waste and Petroleum Feedstocks</i>			
Info	Type of Project	Research	Duration (months)	36
	Total Budget	3.435.164 €	Start Date	01/07/2016
	EU Contribution	2.061.098 €	End date	30/06/2019

Abstract

The main goal of the proposed research is to improve the viability and environmental performance of direct coal liquefaction (DCL) by providing a framework where it can develop in the EU without the need for extremely large-scale plant and with a focus on low-rank and perhydrous coals that provide the highest conversions at lowest cost. The research will establish a distributed approach to DCL that will enable it to be introduced as a technology suitable for co-processing a variety of wastes, including plastics, tyres and bio-wastes which can thermally decompose into effective solvents.

The two primary conversion routes will be investigated to optimise the use of wastes and co-feeds are:

- The use of solvents with some H-donor properties without hydrogen pressure; and
- The use of waste and non-donor solvents with added hydrogen pressure with means for in-situ generation being investigated.

The primary liquefaction products will then be assessed for co-processing with petroleum feedstocks in existing refinery facilities with a test programme involving both catalytic cracking and hydrocracking with hydro-isomerisation of the naphtha produced from both processes. The research will identify and implement the improvements that need to be made to existing catalysts to optimally co-processing heavy coal liquids and petroleum fractions. This flexible approach will enable plants to operate on relatively small scales (ca. < 200 tonne p.d.) to provide intermediate heavy oil products suitable for further processing in existing oil refinery operations, as well as minimising CO2 emissions from co-processing a range of bio-wastes. The results of the research programme will provide the basis for designing two specific DCL modules as the basis for pilot-scale operation, based on the use of solvents with hydrogen-donor capabilities and non-donor solvents with added hydrogen pressure.

Coordinator	Country	Scientific person in charge
<b>THE UNIVERSITY OF NOTTINGHAM</b>	UK	Prof. Colin SNAPE
Partners		
<b>VYZKUMNY USTAV PRO HNEDE UHLI AS</b>	CZ	Dr. Petr SVOBODA
<b>UNIPETROL VYZKUMNE VZDELAVACI CENTRUM AS</b>	CZ	Mr. Radek CERNY
<b>ETHNIKO KENTRO EREVNAS KAI TECHNOLOGIKIS ANAPTYXIS</b>	EL	Dr. Angelos LAPPAS
<b>MOTOR OIL (HELLAS) DIILISTIRIA KORINTHOU AE</b>	EL	Mrs Maria EMMANOUILIDOU
<b>SOLUCIONES CATALITICAS IBERCAT SL</b>	ES	Dr. Francisco VILA ORTIS
<b>CENTRO DE INVESTIGACIONES ENERGETICAS, MEDIOAMBIENTALES Y TECNOLOGICAS-CIEMAT</b>	ES	Dr. Jose Maria SANCHEZ
<b>LABORATORIO NACIONAL DE ENERGIA E GEOLOGIA I.P.</b>	PT	Dr. Filomena PINTO
<b>ESTRA ENERGY TECHNOLOGY STRATEGIES LTD</b>	UK	Dr. Flavio FRANCO
<b>UNIVERSITY OF ULSTER</b>	UK	Dr. Ye HUANG



**TGC2 : Coal preparation, conversion and upgrading**

<b>709741 (2016)</b>	<b>PROMOTEE</b>			
	<i>Functional porous carbon materials derived from coal tar for energy and environmental applications</i>			
Info	Type of Project	Research	Duration (months)	42
	Total Budget	2.208.607 €	Start Date	01/10/2016
	EU Contribution	1.325.164 €	End date	31/03/2020

Abstract

In order to increase the viability and competitiveness of European coal tar distillation plants, it is essential that optimum use of coal-derived liquids is made. Attaining this goal implies finding ways for the revalorization of liquids that are currently of low value and are not used in high-end applications (e.g., creosotes, phenolic oils and rejects obtained from the purification of high value coal tar fractions).

To address this issue, PROMOTEE has been created as a complex European project aiming at the development of novel porous carbon materials for energy and environmental applications using low value coal-derived liquids as the carbon precursors. The following specific objectives are sought after:

- To maximize the use of coal-derived liquids as novel carbon material precursors with a view to their revalorization;
- To synthesize ordered mesoporous carbons via hard-templating from creosotes and rejects;
- To produce new carbon gels via sol-gel routes from phenolic oils;
- To understand the effect of coal tar-derived liquids on the characteristics of the carbon materials;
- To evaluate the performance of these new carbon materials in energy and environmental applications;
- To assess the feasibility of industrial applications of the porous carbons and compare them with commercial carbons.

PROMOTEE incorporates industrial participation from both ends of the value chain (coal tar distillers and porous carbon manufacturers) to ensure that a significant impact of the project results on relevant stakeholders is attained.

Coordinator	<i>Country</i>	<i>Scientific person in charge</i>
<b>AGENCIA ESTATAL CONSEJO SUPERIOR DE INVESTIGACIONES CIENTIFICAS</b>	ES	Dr. Juan Ignacio PAREDES
Partners		
<b>UNIVERSITE DE LIEGE</b>	BE	Dr. Nathalie JOB
<b>SILCARBON AKTIVKOHLE GMBH</b>	DE	Dr. Robert SMIT
<b>BILBAINA DE ALQUITRANES SOCIEDAD ANONIMA</b>	ES	Dr. Enrique ESPARZA
<b>CENTRE NATIONAL DE LA RECHERCHE SCIENTIFIQUE CNRS</b>	FR	Dr. Vanessa FIERRO
<b>HERIOT-WATT UNIVERSITY</b>	UK	Prof. Mercedes MAROTO-VALER



**TGC2 : Coal preparation, conversion and upgrading**

<b>710078 (2016)</b>	<b>INNOWATREAT</b>			
	<i>The innovative system for coke oven wastewater treatment and water recovery with the use of clean technologies</i>			
Info	Type of Project	Research	Duration (months)	36
	Total Budget	2.166.729 €	Start Date	01/07/2016
	EU Contribution	1.300.037 €	End date	30/06/2019

Abstract

Cokemaking industry generates huge amounts of wastewater contaminated with a range of contaminants. Those streams contain substances, which are of classified as priority substance and priority hazardous substances due to European Water Framework Directive. Hence, their proper treatment and management is crucial for protection of aquatic systems, to which they are usually discharged. The main aim of the INNOWATREAT project is the development of the complex system for coke oven wastewater characteristics, treatment and utilization. The project programme includes testing of analytical procedures, adaptation and development of a range of wastewater treatment methods and investigations on water recovery by means of clean technologies. Moreover, computational approach of the elaborated technological solutions as well as economic and environmental feasibility studies are involved to the project objectives. Project consortium comprises of partners, who possess wide experience and knowledge on the field of cokemaking, coke oven wastewater characteristics and wastewater treatment and utilization methods. The main principals of the project are elaborated on the basis of multiple consulting with cokemakers and coke oven wastewater treatment plants operators in order to approach the issue with the highest attention and further implementation to the industrial systems. Directive. Hence, their proper treatment and management is crucial for protection of aquatic systems, to which they are usually discharged. The main aim of the INNOWATREAT project is the development of the complex system for coke oven wastewater characteristics, treatment and utilization. The project programme includes testing of analytical procedures, adaptation and development of a range of wastewater treatment methods and investigations on water recovery by means of clean technologies. Moreover, computational approach of the elaborated technological solutions as well as economic and environmental feasibility studies are involved to the project objectives. Project consortium comprises of partners, who possess wide experience and knowledge on the field of cokemaking, coke oven wastewater characteristics and wastewater treatment and utilization methods. The main principals of the project are elaborated on the basis of multiple consulting with cokemakers and coke oven wastewater treatment plants operators in order to approach the issue with the highest attention and further implementation to the industrial systems.

Coordinator	Country	Scientific person in charge
<b>INSTYTUT CHEMICZNEJ PRZEROBKI WĘGLA</b>	PL	Dr. Anna KWIECIŃSKA
Partners		
<b>CESKE VYSOKE UCENI TECHNICKE V PRAZE</b>	CZ	Prof. Pavel DITL
<b>AKVOLUTION GMBH</b>	DE	Dr. Matan BEERY
<b>POLITECHNIKA WROCLAWSKA</b>	PL	Prof. Andrzej NOWORYTA
<b>POLITECHNIKA KRAKOWSKA</b>	PL	Prof. Michał DYLAĞ



## Technical Group Coal 3

# Coal combustion, clean and efficient coal technologies, CO<sub>2</sub> capture

### The scope TGC3 includes:

- Coal beneficiation
- Cokemaking
- Coal-derived carbon materials
- Coal gasification (hydrogen, syngas, synthetic natural gas etc.), including chemical and process aspects of underground coal gasification
- Coal liquefaction
- Environmental issues associated with coal upgrading processes







**TGC3 : Coal combustion, clean and efficient coal technologies, CO2 capture**

<b>709629 (2016)</b>	<b>FLEXICAL</b>			
	<i>Development of flexible coal power plants with CO2 capture by Calcium Looping</i>			
Info	Type of Project	Research	Duration (months)	36
	Total Budget	2.452.366 €	Start Date	01/07/2016
	EU Contribution	1.471.420 €	End date	30/06/2019

Abstract

Coal power plants undergo flexible operation with load changes and partial load operation due to the increasing amount of renewable energy. The main objective of this proposal is to evaluate and enhance the flexibility of power plants with CO2 capture by post combustion Calcium Looping. Two novel process options (a highly load flexible plant concept and a system using an energy storage using CaO/CaCO3) are experimentally investigated at pilot scale to evaluate operational limits. Data on load changes and energy storage are used to validate dynamic system and reactor models in order to scale up efficient and flexible Calcium Looping systems.

Coordinator	Country	Scientific person in charge
<b>AGENCIA ESTATAL CONSEJO SUPERIOR DE INVESTIGACIONES CIENTIFICAS</b>	ES	Dr. Borja ARIAS
Partners		
<b>UNIVERSITAET STUTTGART</b>	DE	Mr. Heiko DIETER
<b>HULLERAS DEL NORTE SA</b>	ES	Mr. Luis DIAZ
<b>POLITECNICO DI MILANO</b>	IT	Dr. Matteo ROMANO
<b>EDF POLSKA SPOLKA AKCYJNA</b>	PL	Mr. Piotr CZUPRYNSKI



**TGC3 : Coal combustion, clean and efficient coal technologies, CO2 capture**

**709954 (2016) DP700-PHASE 1**  
*Preparation for Commercial Demonstration Plant for 700oC Operation*

Info	Type of Project	Accompanying Measure	Duration (months)	18
	Total Budget	2.269.930 €	Start Date	01/07/2016
	EU Contribution	1.361.958 €	End date	31/12/2017

**Abstract**

PF-fired hyper super critical (HSC), also known as advanced ultra super critical (A-USC), power plant is able to reach 50-55% net (LHV) efficiency thereby decreasing the specific power plant CO2 emissions; however HSC plant development entails large technical and commercial risk. This project aims to bring together EU knowledge and experience on high temperature boiler materials and components suitable for HSC operation, thereby reducing these risks.

This consolidation of knowledge will lead into the design, build and operation of a full scale 1000MW demonstration plant, under a follow on project, allowing EU companies to have a head start in these new markets.

Phase 1 is the knowledge capture phase with Phase 2 being the design build and operation of a full scale 1000MW demonstration plant. Phase 2 will be subject of a follow on project from this Phase 1 project.

Coordinator	Country	Scientific person in charge
<b>DOOSAN BABCOCK LIMITED</b>	UK	Dr. Peter BARNARD
<b>Partners</b>		
<b>TECHNISCHE UNIVERSITAET GRAZ</b>	AT	Prof. Bernhard SONDEREGGER
<b>TECHNISCHE UNIVERSITAT DARMSTADT</b>	DE	Dr. Alfred SCHOLZ
<b>TECHNISCHE UNIVERSITAET CHEMNITZ</b>	DE	Prof. Peter MAYR
<b>TEKNOLOGIAN TUTKIMUSKESKUS VTT OY</b>	FI	Dr. Maria OKSA
<b>CENTRO SVILUPPO MATERIALI SPA</b>	IT	Mr. Sandro NOTARGIACOMO
<b>DEKRA CERTIFICATION BV</b>	NL	Mr. Arthur STAM
<b>CRANFIELD UNIVERSITY</b>	UK	Prof. John OAKEY



**TGC3 : Coal combustion, clean and efficient coal technologies, CO2 capture**

<b>709976 (2016)</b>	<b>NIBALO725</b>			
	<i>Ni-based alloys for Operation of 725 °C Power Plants</i>			
Info	Type of Project	Research	Duration (months)	48
	Total Budget	2.893.589 €	Start Date	01/09/2016
	EU Contribution	1.736.153 €	End date	31/08/2020

Abstract

In order to further increase the efficiency of coal fired power plants and reduce emissions higher steam temperatures and materials with improved mechanical properties under high temperatures are required.

Aim of the project is to implement Ni-based alloys in coal fired power plants in order to obtain maximum steam temperatures of > 700 °C in the steam cycle. A numerical assessment of stresses and material investigations of small and large scale specimen will be performed. A field test in a 725 °C test rig (GKM Project HWT III) will demonstrate the feasibility of the implementation of these materials.

Coordinator

**UNIVERSITAET STUTTGART**

*Country Scientific person in charge*

DE Dr. Alexander HOBT

Partners

**GE BOILER DEUTSCHLAND GMBH**

DE Mr. Frank KLUGER

**GROSSKRAFTWERK MANNHEIM AG**

DE Mr. Klaus METZGER

**ETHNIKO KENTRO EREVNAS KAI TECHNOLOGIKIS ANAPTYXIS**

EL Dr. Nikos NIKOLOPOULOS

**CENTRO SVILUPPO MATERIALI SPA**

IT Ms Arianna GOTTI

**SPECIAL METALS WIGGIN LIMITED**

UK Dr. Steve MCCOY



# Technical Group Steel 1

## Ore agglomeration and Ironmaking

### **The scope TGS1 includes:**

- Ore agglomeration, sintering and pelletising processes
- New and improved iron-ore reduction processes (including DRI & C-free reduction)
- Ironmaking processes and operations including slag treatment
- Standardisation of testing and evaluation methods
- Maintenance and reliability of production lines
- Reduction of emissions, energy consumption and improvement of the environmental impact
- Instrumentation, modelling and control of processes





**TGS1 : Ore agglomeration and Ironmaking**

<b>RFSR-CT-2015-00001</b>	<b>OPTIBLAFINS</b>		
	<i>Optimizing Blast Furnace Hearth Inner State</i>		
Info	Type of Project	Research	Duration (months) 42
	Total Budget	3.599.376 €	Start Date 01/07/2015
	EU Contribution	2.159.625 €	End date 31/12/2018

Abstract

This proposal reflects to different dead man states in a blast furnace hearth in relation to coke particles forming the dead man, hearth liquid flow and respective heat loads. Describing the dead man as a conglomeration of individual particles and correlating global process parameters with local wear factors will form highly innovative activities of the project. State of the art computer modelling technique combining DEM-CFD approaches will be used to understand the actual liquid and solid flow within the hearth. Such modelling approach will be used for the first time in a project realised within the RFCS frame work. In addition, advanced monitoring techniques will be tested with the aim to gain an improved understanding of localised wear events. This will provide a better ground for decision-making concerning stabilizing the hearth condition, improving hearth drainage and prolonging hearth life.

Coordinator

**TATA STEEL NEDERLAND TECHNOLOGY B.V.**

Country

NL

Scientific person in charge

Ir. G. LOUWERSE

Partners

**ABO AKADEMI UNIVERSITY**

FI

Prof. Henrik SAXEN

**AKTIEN-GESELLSCHAFT DER DILLINGER HÜTTENWERKE AG**

DE

Dr.-Ing. Rongshan LIN

**ARCELORMITTAL MAIZIERES RESEARCH S.A.**

FR

Dr. Thibault QUATRAVEUX

**ARCELORMITTAL EISENHÜTTENSTADT GMBH**

DE

Dr. Jörg MERNITZ

**CENTRE DE RECHERCHES METALLURGIQUES ASBL**

BE

Mr Claudio OJEDA

**UNIVERSITÄT LINZ\*JOHANNES KEPLER UNIVERSITÄT, LINZ**

AT

Dr. Gijbert WIERINK

**LUOSSAVAARA-KIIRUNAVAARA AB**

SE

Mr Nicklas EKLUND

**SWEREA MEFOS AB**

SE

Dr. Lena SUNDQVIST ÖQVIST

**RUHR-UNIVERSITÄT BOCHUM**

DE

Dr. Siegmund WIRTZ

**VDEH-BETRIEBSFORSCHUNGSINSTITUT GMBH**

DE

Dr.-Ing. Yalcin KAYMAK

**VOESTALPINE STAHL GMBH**

AT

Dipl.-Ing. Christoph FEILMAYR



**TGS1 : Ore agglomeration and Ironmaking**

<b>RFSR-CT-2015-00002</b>	<b>ALCIRC</b>			
	<i>Assessing and control of alkaline circulation in BF operation</i>			
Info	Type of Project	Research	Duration (months)	42
	Total Budget	2.302.713 €	Start Date	01/07/2015
	EU Contribution	1.381.628 €	End date	31/12/2018

Abstract

The overall research project objective is improved blast furnace (BF) process stability and energy efficiency with increasing flexibility in raw material selection, taking into account deteriorating raw material qualities in terms of alkali content. This is achieved by developing and establishing new methods for online alkali control in the BF, based on a novel online top gas evaluation tool for determination of the alkali accumulation in the operational blast furnace. This tool consists of the top gas measurement equipment (FTIR or MS) and the evaluation routine for determination of the alkali accumulation / cycle. The new online tool will be applied for monitoring of the alkali cycle amount at selected representative BF's with elevated alkali input and with differences in the source of alkali components. The selected BF's differ in operational modes. Monitoring of the alkali cycle amount enables the premature detection of operational states with elevated alkali load. In this way, countermeasures for alkali control may be triggered at an early stage in order to prevent operational disturbances at the BF. For BF alkali control some promising novel measures are developed within the research project, like coke pre-treatment/coating with alkali absorbing minerals as well as a more optimised adjustment of BF slag composition. Finally, concepts will be worked out for improved BF alkali control by combined application of the online top gas evaluation tool with selected methods for inhibition of the alkali circulation. The concepts will consider the special restraints at the different operational BF's. Finally the concepts will be validated by operational trials at the different BF's in comparison with normal operational data.

Coordinator

**VDEH-BETRIEBSFORSCHUNGSINSTITUT GMBH**

*Country Scientific person in charge*

DE Dipl.-Ing. Gerald STUBBE

Partners

**ISD DUNAFERR DUNAI VASMU ZRT.**

HU Mr Róbert MÓGER

**LUOSSAVAARA-KIIRUNAVAARA AB**

SE Ms Anna DAHLSTEDT

**LULEÅ UNIVERSITY OF TECHNOLOGY**

SE Prof. Bo BJÖRKMAN

**SWEREA MEFOS AB**

SE Dr. Lena SUNDQVIST ÖQVIST

**SSAB EMEA AB**

SE Mr David LINDSTRÖM

**VOESTALPINE STAHL DONAWITZ GMBH & CO KG**

AT Dipl.-Ing. Roland MAYERHOFER





**TGS1 : Ore agglomeration and Ironmaking**

<b>709424 (2016)</b>	<b>DEPREX</b>			
	<i>Early detection and prevention of tuyere damaging conditions for extension of tuyere life time at blast furnaces</i>			
Info	Type of Project	Research	Duration (months)	42
	Total Budget	2.080.691 €	Start Date	01/07/2016
	EU Contribution	1.248.414 €	End date	31/12/2019

**Abstract**

The damage of a blast furnace tuyere is an incident, which happens in average 30 up to 120 times a year at normal blast furnace operation. Each single tuyere damage causes a stoppage of the whole blast furnace of about two hours, in some case up to eight hours. Although, the hot blast is stopped and no hot metal is produced, coke is consumed and additional coke has to be charged. Energy is spent without any benefit. In order to reduce the unplanned BF stoppages due to tuyere damages the objectives of the proposed RFCS project are:

- to generate advanced knowledge about tuyere damage mechanisms by analysis of tuyere material properties during tuyere life time (chronology of degradation);
- to develop advanced operational tuyere monitoring systems for monitoring of BF tuyeres during operation as industrial standard application for all tuyeres;
- to develop a BF tuyere damage risk assessment system for early detection of BF tuyere damaging conditions;
- to define practical countermeasures for BF operators to go against tuyere damaging conditions and to extend BF tuyere life time.

The decrease of the number of unplanned blast furnace stoppages due to tuyere damages enables a significant reduction of energy consumption and costs in blast furnace operation. Furthermore, it decreases the risk for the occupational health due to e. g. contact of BF staff with toxic CO gas and hot metal during tuyere exchange. Therefore, each single tuyere damage, which can be prevented, helps to increase safety of BF staff. Consequently, the proposed project contributes to the RFCS programme objectives (Council Decision 2008/376/EC):

1. New and improved steelmaking and finishing techniques
  - process instrumentation, control and automation
  - maintenance and reliability of production lines
2. Conservation of resources and improvement of working conditions
  - occupational health and safety

Coordinator	Country	Scientific person in charge
<b>VDEH-BETRIEBSFORSCHUNGSINSTITUT GMBH</b>	DE	Dr. Jörg ADAM
<b>Partners</b>		
<b>VOESTALPINE STAHL GMBH</b>	AT	Dr. Christoph THALER
<b>THYSSENKRUPP STEEL EUROPE AG</b>	DE	Mr. Andrej JOHNNEN
<b>ISD DUNAFERR DUNAI VASZMŰ ZARTKÖRŰEN MŰKÖDŐ RESZVÉNYTÁRSASÁG</b>	HU	Dr. Robert MOGER
<b>FUROL TANÁCSADÓ ES SZOLGÁLTATÓ KORLATOLT FELELŐSÉGU TÁRSASÁG</b>	HU	Dr. Oszkar GREGA

**TGS1 : Ore agglomeration and Ironmaking**

709816 (2016)	STACKMONITOR			
	<i>Online Blast Furnace Stack Status Monitoring</i>			
Info	Type of Project	Research	Duration (months)	42
	Total Budget	1.813.217 €	Start Date	01/07/2016
	EU Contribution	1.087.930 €	End date	31/12/2019
Abstract	<p>The decreasing and fluctuating quality of raw materials and the aim to maximise PCI and decrease coke rates force European blast furnaces to operate closer to operational limits. At same time productivity and efficiency must be raised to survive in global competition. High stack permeability and stable gas distribution become most important.</p> <p>However, the analysis and control of the stack processes is difficult: Hundreds of measurement values are available nowadays, but they are distributed around the blast furnace and just show indirect “fingerprints” from outside instead of the real internal process information needed (e.g. position of process zones).</p> <p>New measurement techniques deliver very fast, full 2D information of the top (acoustical gas temperature, burden profile radar), but they are not sufficiently validated and not investigated by research. Instead, the operators are overcharged with even more separate measurement data. No overall process information is available to decide about control actions.</p> <p>The main idea of StackMonitor is to establish a new hybrid approach of data processing which couples statistical and kinetic process models with several online measurements. This new approach will provide industrial benefit even beyond iron making, since several industrial processes suffer from the mismatch between the vast amount of measurement data and its poor exploitation.</p> <p>To achieve this aim, StackMonitor establishes the innovative coupled CFD-DEM simulation to support online process monitoring and control, validated with comprehensive high temperature lab trials. Thus, for the first time the interrelations between solids and gas in the upper stack can realistically be described: The percolation, mixing and degradation of material during descent and the corresponding layer permeability.</p> <p>Online tools for process monitoring, analysis and control are developed and validated in collaboration with three industry partners covering different operational conditions.</p>			
Coordinator	<b>VDEH-BETRIEBSFORSCHUNGSINSTITUT GMBH</b>	Country	DE	Scientific person in charge Dr. Hauke BARTUSCH
Partners	<b>AKTIEN-GESELLSCHAFT DER DILLINGER HÜTTENWERKE</b>	DE		Dr. Rongshan LIN
	<b>SALZGITTER FLACHSTAHL GMBH</b>	DE		Dr. Tatjana MIRKOVIC
	<b>ABO AKADEMI</b>	FI		Prof. Henrik SAXEN
	<b>OULUN YLIOPISTO</b>	FI		Prof. Timo FABRITIUS

# Technical Group Steel 2

## Steelmaking processes

### **The scope TGS2 includes:**

- Electric arc furnace processes
- Physico-chemical metallurgy of liquid steel and slag
- Recycling of steel scrap
- Secondary metallurgy techniques
- Standardisation of testing and evaluation methods
- Maintenance and reliability of production lines
- Reduction of emissions, energy consumption and improvement of the environmental impact
- Instrumentation, modelling and control of processes



**TGS2 : Steelmaking processes**

<b>RFSR-CT-2015-00004</b>	<b>DYNSTIR</b>
	<i>Dynamic stirring for improvement of energy efficiency in secondary steelmaking</i>
Info	Type of Project      Research      Duration (months)      36
	Total Budget      1.927.815 €      Start Date      01/07/2015
	EU Contribution      1.156.689 €      End date      30/06/2018

## Abstract

The project objective is to improve ladle stirring by developing dynamic stirring policies in secondary steelmaking at different treatment stations (CASOB treatment, vacuum treatment and final treatment (rinsing)). In heat-individual dynamic stirring, the stirring process will be tailored to the individual need of each treated steel melt, based on metallurgical fundamentals, with the aim to improve the energy efficiency of the ladle stirring processes while maintaining the cleanness of the final product. Imaging and vibration measurement systems will be used to monitor the actual stirring, compare it to the ideal treatment according to the stirring policies and advise correct stirring accordingly. Extensive sampling and analysis will verify the improvements. Energy efficiency will be improved by shorter treatment time, reduced amount of stirring gas used and diminished temperature loss of the steel melt.

## Coordinator

**VDEH-BETRIEBSFORSCHUNGSINSTITUT GMBH**

## Country

DE

## Scientific person in charge

Dr.-Ing. Birgit PALM

## Partners

**CENTRO SVILUPPO MATERIALI SPA**

IT

Dr.ssa Patrizia MICELI

**GEORGMARIENHÜTTE GMBH**

DE

Mr Bernd DETTMER

**KUNGLIGA TEKNISKA HÖGSKOLAN - THE ROYAL INSTITUTE OF TECHNOLOGY**

SE

Prof. Du SICHEN

**UDDEHOLMS AB**

SE

Dr. Mselly NZOTTA

**TGS2 : Steelmaking processes**

<b>RFSR-CT-2015-00005</b>	<b>LEANSTORY</b>			
	<i>Improvement of steel cleanness by reducing refractory contamination in secondary steelmaking</i>			
Info	Type of Project	Research	Duration (months)	42
	Total Budget	1.735.185 €	Start Date	01/07/2015
	EU Contribution	1.041.112 €	End date	31/12/2018

## Abstract

MgO based refractory of new generation is developed by the joint competence of steelmaker, refractory producer and university scientists. Both new carbon free binder system and modification of the current binder systems are studied. The new refractory (either bricks or castable) is characterized and tested firstly in laboratory and then in full scale ladles. The development is directly towards the need of steelmaking. The new refractory is expected to result in great improvement of steel cleanness and prolonged lifetime of ladle lining. The sustainability and recyclability of the refractory should be another important factor in the development.

## Coordinator

**KUNGLIGA TEKNISKA HÖGSKOLAN - THE ROYAL INSTITUTE OF TECHNOLOGY**

*Country Scientific person in charge*

SE Prof. Du SICHEN

## Partners

**SIDENOR INVESTIGACION Y DESARROLLO EUROPA S.A.**

ES Mr Asier ARTEAGA

**REFRACTORY SOLUTIONS INSERTEC SL**

ES Mr. Roberto CABALLERO

**OVAKO SWEDEN AB**

SE MSc Jan-Erik ANDERSSON

**POLITECNICO DI BARI**

IT Prof. Giovanni MUMMOLO

**UNIVERSIDAD POLITECNICA DE MADRID**

ES Prof. Joaquín ORDIERES MERE



**TGS2 : Steelmaking processes**

<b>RFSR-CT-2015-00031</b>	<b>SIMULEAF</b>			
	<i>Improvement of electrical arc furnace operations with support of advanced multiphysics modeling SIMULations of the EAF process</i>			
Info	Type of Project	Research	Duration (months)	36
	Total Budget	1.534.605 €	Start Date	01/09/2015
	EU Contribution	920.763 €	End date	31/08/2018

Abstract

The proposal, supported by two research centres (CSM and BFI), three industrial partners (GERDAU, GMH and ORI Martin) and a supplier of electromagnetic stirring devices (ABB AB) are aimed at:

- developing a numerical simulation tool for the EAF process, coupling fluid flow, magneto-hydrodynamics, energy and mass transfer as well as selected thermodynamic calculations;
- using this tool for elaboration of process measures with respect to energy savings, reduction of CO2 emissions, and improved metallic yield.

Validating and integrating sub-models (micro-models) into a macro-model used as advanced simulation tool will allow to:

- improve EAF process knowledge, as some data can only be obtained using mathematical modelling techniques due to practical limitations of taking measurements on the plant;
- reduce risks, as modelling can enable decisions on production plant modifications without carrying out on-site experiments, which are expensive and leading to a loss of production;
- reduce development costs, as modelling offers a wider range of design options to be evaluated before testing on the plant.

The project is composed by the following working topics:

- selection of available micro-models (detailed description of local phenomena, e.g., stirring, decarburisation by lance, postcombustion);
- development of missing micro-models (e.g. thermodynamics, ..);
- integration into a macro-model (able to describe unsteady transport phenomena by coupled multi-physics approach);
- performance of complete EAF furnace simulations with the tool;
- validation of the modelling results with process data collected at several EAF plants;
- performance of parameter studies to optimise the process layout and the operational practices;
- dissemination of the results.

The techniques used will be based on: modelling: Computational Fluid Dynamics numerical models and physical modelling tools will be used and design of stirring sources - plant tests.

Coordinator	Country	Scientific person in charge
<b>CENTRO SVILUPPO MATERIALI SPA</b>	IT	Dr. Valerio BATTAGLIA
Partners		
<b>ABB AB</b>	SE	Mr Jan Erik ERIKSSON
<b>SIDENOR INVESTIGACION Y DESARROLLO EUROPA S.A.</b>	ES	Mr José Manuel LLANOS RUIZ
<b>GEORGMARIENHÜTTE GMBH</b>	DE	Mr Bernd DETTMER
<b>O.R.I. MARTIN - ACCIAIERIA E FERRIERA DI BRESCIA SPA</b>	IT	Ing. Uggero DE MIRANDA
<b>VDEH-BETRIEBSFORSCHUNGSINSTITUT GMBH</b>	DE	Dipl.-Ing. Kersten MARX



**TGS2 : Steelmaking processes**

<b>709620 (2016)</b>	<b>PERMONLIST</b>			
	<i>Continuous Performance Monitoring and Calibration of Model and Control Functions for Liquid Steelmaking Processes</i>			
Info	Type of Project	Research	Duration (months)	36
	Total Budget	1.688.369 €	Start Date	01/07/2016
	EU Contribution	1.013.022 €	End date	30/06/2019

Abstract

The main objective of the research project is to improve, for the different stages of the liquid steelmaking process route, the continuous monitoring of the process performance as well as to ensure the permanent reliability of used dynamic process models and control rules. For this purpose, methods and tools will be developed involving the application of innovative and comprehensive performance indexes and strategies for automatic calibration of model and control parameters.

By these developments the following benefits shall be achieved for the liquid steelmaking processes:

- Improved on-line monitoring of the process performances, to be used by engineers and operators to decide about necessary countermeasures. Moreover, the increased knowledge about the process behaviour can be used to improve the operating practices;
- Long-term reliable operation of dynamic process models and rule based set-point calculations used for off-line process optimisation as well as on-line monitoring and process control, by continuous monitoring of model and control performance with automatic adaptation of related parameters (self- learning system). Results from process performance monitoring provide necessary input to the automatic calibration methods to assess the current reliability and relevance of measured data;
- Improved reliability and stability of the liquid steelmaking processes by enhanced performance of model- and rule-based control of analysis and temperature of the steel melt with reduced scatter and deviations from the desired target values;
- Minimisation of energy and resources consumption as well as treatment duration by enhanced reliability of Level-2 automation and process control functions.

The developed tools will be coupled to an integrated approach and tested exemplarily for the most important liquid steelmaking facilities of the electric steelmaking route, i.e. for EAF, LF, VD and AS plants.

Coordinator	<i>Country</i>	<i>Scientific person in charge</i>
<b>VDEH-BETRIEBSFORSCHUNGSINSTITUT GMBH</b>	DE	Dr. Martin SCHLAUTMANN
Partners		
<b>CENTRE DE RECHERCHES METALLURGIQUES ASBL</b>	BE	Mr. Olivier ANSSEAU
<b>PEINER TRAGER GMBH</b>	DE	Mr. Vasilij ZAGREBIN
<b>CENTRO SVILUPPO MATERIALI SPA</b>	IT	Dr. Piero FRITTELLA
<b>FERALPI SIDERURGICA S.P.A.</b>	IT	Mr. Stefano FILIPPINI





**TGS2 : Steelmaking processes**

<b>709740 (2016)</b>	<b>DISSTEC</b>			
	<i>Valorisation and dissemination of technologies for measurement, modelling, and control in secondary metallurgy</i>			
Info	Type of Project	Accompanying Measure	Duration (months)	18
	Total Budget	365.684 €	Start Date	01/07/2016
	EU Contribution	219.410 €	End date	31/12/2017

Abstract

The objective of this dissemination project is to revise the most important European projects related to Secondary Metallurgy technologies carried out in the last years. The basic idea is that an action of dissemination and valorisation of the most important results, based on an integrated critical analysis, is useful to valorise, disseminate and promote the exploitation of the results. Also this action is a necessary step for preparing and communicating a roadmap for future research activities and priorities. These general objectives can be broken down as follows:

- To promote the dissemination of the knowledge gained and the technological solutions introduced in relevant projects on Secondary Metallurgy;
- To identify present merits and limitations of the various technological solutions, as well as the spread of their implementation in the European steel plants;
- To identify most promising and most useful emerging development lines and to encourage the use of best results and innovative solutions, taking into account possible technological barriers;
- To identify future developments, to produce a clear and realistic picture of the future trends to be expected in Secondary Metallurgy technology;
- To supply guidelines for the next developments of Secondary Metallurgy technologies, to give indications on priorities for research subjects and activities;
- To suggest a clear road map for the technological development in this field.

The dissemination activities will comprise the following actions:

- Set-up of a web site to allow the access to the results of the project analysis, the presentations of seminars and workshops and the road map for future developments;
- Seminars on dedicated topics;
- Webinars with demonstration of successful applications;
- Workshops to provide the possibility for information exchange and open discussion, especially regarding the identification of future developments and definition of a road map.

Coordinator

**VDEH-BETRIEBSFORSCHUNGSINSTITUT GMBH**

*Country*

DE

*Scientific person in charge*

Dr. Bernd KLEIMT

Partners

**CENTRE DE RECHERCHES METALLURGIQUES ASBL**

BE

Dr. Jean-Christophe PIERRET

**CENTRO SVILUPPO MATERIALI SPA**

IT

Dr. Piero FRITTELLA

**SWEREA MEFOS AB**

SE

Dr. Jonas ALEXIS

**MATERIALS PROCESSING INSTITUTE**

UK

Dr. Stuart MILLMAN



**TGS2 : Steelmaking processes**

<b>709923 (2016)</b>	<b>OSCANEAF</b>			
	<i>On-line slag composition analysis for electric arc furnaces</i>			
Info	Type of Project	Research	Duration (months)	36
	Total Budget	1.201.903 €	Start Date	01/07/2016
	EU Contribution	721.142 €	End date	30/06/2019

Abstract

Electric steelmaking has fast gained ground in developed countries due to reduced CO<sub>2</sub> emissions compared to blast furnace steelmaking and better production flexibility. Due to increased scrap usage, the quality of the scrap is getting worse and worse. This is reflected in the increase of non-metallic material in the scrap. Fluctuations in EAF scrap charge composition causes significant fluctuations in the EAF slag composition, since the non-metallic material in the scrap accumulates in the slag.

Fluctuation of slag composition causes many challenges in EAF steelmaking. In stainless steelmaking one of the most important goals in EAF is to keep the chromium content of the slag low, since it causes costs due to increased alloying additions and problems in recycling of slag. In carbon steelmaking it is important to ensure foaming slag conditions, which increases energy efficiency of the EAF. Due to the slag composition fluctuations the slag foaming is sometimes hindered when the slag composition drifts to the composition area with low foamability.

There are currently very few methods available for analysing slag composition in EAF. One of the most popular methods to gain information of slag composition is taking slag samples and analysing them in laboratory. Currently there is no method available to analyse slag composition in industrial EAFs on-line.

The objective of the proposal is the development of a continuous measurement system for EAF slag component analysis based on optical emission spectroscopy. The aim for stainless steel grades is the analysis of Cr<sub>2</sub>O<sub>3</sub> and MnO content, while for carbon steel grades the aim is to analyse CaO, SiO<sub>2</sub>, Al<sub>2</sub>O<sub>3</sub> and MgO content of the slag. The proposed technology will follow these criteria:

- Remote and continuous measurement system for slag component analysis;
- Low maintenance system design;
- Optimized operating practices based on continuous slag composition data increasing resource and energy efficiency.

Coordinator	<i>Country</i>	<i>Scientific person in charge</i>
<b>RHEINISCH-WESTFAELISCHE TECHNISCHE HOCHSCHULE AACHEN</b>	DE	Prof. Herbert PFEIFER
Partners		
<b>DEUTSCHE EDELSTAHLWERKE GMBH</b>	DE	Mr. Jens-Sebastian KLUNG
<b>OUTOKUMPU STAINLESS OY</b>	FI	Mr. Esa PUUKKO
<b>LUXMET OY</b>	FI	Mr. Mikko JOKINEN
<b>OULUN YLIOPISTO</b>	FI	Prof. Timo FABRITIUS
<b>KUNGLIGA TEKNISKA HOEGSKOLAN</b>	SE	Prof. Pär JÖNSSON

# Technical Group Steel 3

## Casting

### **The scope TGS3 includes:**

- Continuous casting and near net shape casting techniques with or without direct rolling for flat and long products
- Chemistry and physics of solidification
- Ingot casting
- Maintenance and reliability of production lines
- Reduction of emissions, energy consumption and improvement of the environmental impact
- 
- Standardisation of testing and evaluation methods
- Instrumentation, modelling and control of processes
-





**TGS3 : Casting**

<b>709830 (2016)</b>	<b>SHELL-THICK</b>			
	<i>Improvement of the continuous casting through a new system for the real-time measurement of SHELL THICKness in several locations of the casting strand</i>			
Info	Type of Project	Research	Duration (months)	36
	Total Budget	1.453.483 €	Start Date	01/07/2016
	EU Contribution	872.090 €	End date	30/06/2019

Abstract

SHELL-THICK project aims at developing an innovative induction tomography system for metal solidification process. It provides a real-time and reliable measurement of the shell thickness in three billet cross-sections in the final region of the strand and the value of the metallurgical length for a better control of the process. Based on this information, the project will also implement a tool for the on-line and non-destructive detection of different surface defects and potential fails in the process. This will introduce a step change in solidification process with significant benefits in terms of quality, safety, productivity, costs and ultimately of competitiveness.

Coordinator

**FUNDACION TECNALIA RESEARCH & INNOVATION**

*Country*    *Scientific person in charge*

ES            Mr. Jose Ignacio BARBERO

Partners

**ERGOLINES LAB SRL**

IT            Dr. Isabella MAZZA

**FERRIERE NORD SPA**

IT            Dr. Loris BIANCO

**UNIVERSITY OF BATH**

UK            Dr. Manuchehr SOLEIMANI



# Technical Group Steel 4

## Hot and cold rolling processes

### **The scope TGS4 includes:**

- Reheating furnaces
- Hot and cold rolling
- Thermal treatments
- Standardisation of testing and evaluation methods
- Maintenance and reliability of production lines
- Reduction of emissions, energy consumption and improvement of the environmental impact
- Instrumentation, modelling and control of processes







**TGS4 : Hot and cold rolling processes**

<b>709504 (2016)</b>	<b>ROLLOILFREE</b>			
	<i>Steel cold rolling with aqueous oilfree lubricant</i>			
Info	Type of Project	Research	Duration (months)	42
	Total Budget	2.479.534 €	Start Date	01/07/2016
	EU Contribution	1.487.720 €	End date	31/12/2019

Abstract

Lubricants applied in cold rolling processes aims to generate high surface aspects, cooling and cleaning as well as optimisation of the tribological system. This project is focused on the targeted development of aqueous oil free lubricants (OFLs) as substitute for the conventional oil based lubricants. As result of the former RFCS-projects Optilub and Lubwork polyalkyleneglycols (PAGs) have already shown comparable or even better rolling properties than conventional lubricants. The targeted development of OFL (PAGs, Polymers) for selected cold rolling processes is central aspect of the planned work programme. One route is set for PAG based lubricants focussing the positive outcome of the former RFCS-project, the other routes are open for other promising formulation based on other type of polymers. As this constitutes a step change in the rolling process, first of all a risk assessment e.g. compatibility of the new lubricant with the existing aggregates and process fluids is required as a work basis. Then the systematic development of oil free lubricants (OFL), their implementation, monitoring and handling measures will be covered by the project. Moreover, the impact of the new lubricant on subsequent processes will be studied in detail. The influence on cleaning, pickling, annealing and finishing will be examined too. Additionally control, care, environmental and ecological aspects will be covered as well. Based on these results OFLs composition will be continuously optimized. An equal substitute, with comparable rolling, cleaning and protective properties as conventional lubricants for both, steel cold rolling and hot aluminium rolling, will generate a massive decrease of running care, costs for replenish and disposal, over 40% cost reduction and 50% lubricant savings are possible.

Coordinator	Country	Scientific person in charge
<b>VDEH-BETRIEBSFORSCHUNGSINSTITUT GMBH</b>	DE	Mr. Tilo REICHARDT
Partners		
<b>ARCELORMITTAL EISENHÜTTENTSTADT GMBH</b>	DE	Dr. Andreas POLLACK
<b>CARL BECHEM GMBH</b>	DE	Dr. Heinz DWULETZKI
<b>HYDRO ALUMINIUM ROLLED PRODUCTS GMBH</b>	DE	Dr. Kai KARHAUSEN
<b>THYSSENKRUPP STEEL EUROPE AG</b>	DE	Dr. Martin RAULF
<b>LUXCONTROL SA</b>	LU	Dr. Mohammed CHTAIB
<b>SWEREA MEFOS AB</b>	SE	Mr. Andreas JOHNSON



**TGS4 : Hot and cold rolling processes**

<b>RFSR-CT-2015-00006</b>	<b>MANCOOL</b>			
	<i>Effective Management of Coolant in Cold Rolling</i>			
Info	Type of Project	Research	Duration (months)	42
	Total Budget	1.129.209 €	Start Date	01/07/2015
	EU Contribution	677.526 €	End date	31/12/2018

Abstract

The objective of this research project is to increase the process and product window in cold rolling mills by enhancing the coolant functionality. In a previous RFCS-project “INCOOL” enormous steps have been made already. Based on the findings in it is expected that a further optimisation is possible and more benefits can be obtained. New innovative ideas that will be investigated in this project should further increase the cold mill capabilities. Expected benefits are increased reduction per stand, increased rolling speed and less temperature related material rejections. Specific objectives of this project are:

- Development of a strip cool unit with width control and testing of this unit in an industrial Cold Rolling Mill;
- Development of a method to re-use the thermal energy that is stored in the emulsion bath. A small scale test installation will be built to verify the concept. If successful, the option that saves most energy will be tested in a packaging cold mill in Tata Steel Ijmuiden;
- Thorough experimental work in order to improve the currently used roll coolant settings (flow, nozzle type, distance/angle of header with respect to the roll). In contrast to previous experimental work, emphasis will be on testing with (various types of) emulsions and particular interest will be given to the influence of oil layer on cooling efficiency;
- Investigation and implementation of innovative approaches with respect to cooling, such as adding additives to the bath and optimising the lubricant to enable efficient cooling;
- Increasing the fundamental knowledge with respect to the formation of heat scratches. More specific a model will be developed that predicts the maximum reduction per stand without creating heat scratches (depending on roll/strip/emulsion temperature and material grade).

Coordinator

**TATA STEEL NEDERLAND TECHNOLOGY B.V.**

*Country Scientific person in charge*

NL Ir. Leon JACOBS

Partners

**BRNO UNIVERSITY OF TECHNOLOGY - VYSOKE UCENI TECHNICKE V BRNE**

CZ Dr. Miroslav RAUDENSKY

**CENTRE DE RECHERCHES METALLURGIQUES ASBL**

BE Mr Bart VERVAET

**TGS4 : Hot and cold rolling processes**

<b>RFSR-CT-2015-00007</b>	<b>MICROCONTROL-PLUS</b>			
	<i>Combined Online Microstructure Sensor and Model for a Better Control of Hot Rolling Conditions and Final Products Properties (phase 2)</i>			
Info	Type of Project	Research	Duration (months)	48
	Total Budget	1.817.557 €	Start Date	01/08/2015
	EU Contribution	1.090.535 €	End date	31/07/2019
Abstract	<p>Improving of the hot rolling process and achieving better consistency of end-user properties is a big challenge. The online real-time evaluation of microstructure changes becomes key element to address this challenge, particularly for the new generation of steels. For example, to comply with the everlasting need for CO2 emission reduction, advanced high strength steels for automotive applications are lighter and stronger. At the same time, their microstructures show higher sensitivity to process variations, especially of hot rolling conditions. In continuation with the MicroControl (RFS-CR- 2009-10010) project, a new tool combining a microstructural hot rolling model and a Laser Ultrasonic Sensor (LUS) is proposed to predict/control steel properties all along the coil, while maximizing mill productivity. To reach this goal, the all-fibered LUS (prototype successfully tested in previous project) will be improved to a robust, portable, full-industrial version for multi-points measurements at several locations in the hot rolling mill. In parallel, laboratory tests will help develop new signal processing techniques to monitor microstructural changes i.e.:</p> <ul style="list-style-type: none"><li>• austenite or ferrite average grain size;</li><li>• grain size gradients along thickness;</li><li>• multiple phase transformation during cooling;</li><li>• final ferrite grain size before coiling.</li></ul> <p>Finally, a new analysis and control tool will be developed combining a microstructural model using a multi-objectives optimization and calibrated with signals obtained from the LUS sensor. This tool will be tested in two industrial situations: 1. predict hot rolling process parameters to achieve final mechanical properties and evaluate microstructure evolution. 2. measure and control austenite microstructure during finishing to improve toughness of line-pipes grades. This online tool will significantly improve the hot rolling process and move a step closer to a fully automatic feed-back control of microstructure and product properties.</p>			
Coordinator	<b>ARCELORMITTAL MAIZIERES RESEARCH S.A.</b>	Country	FR	Scientific person in charge Dr. Louis SATYANARAYAN
Partners	<b>IMAGINE OPTIC SA</b>		FR	Mr Nicolas LEFAUDEUX
	<b>SWEREA KIMAB AB</b>		SE	Mrs Eva LINDH ULMGREN
	<b>SWEREA MEFOS AB</b>		SE	Mr. Bijish BABU



**TGS4 : Hot and cold rolling processes**

<b>RFSR-CT-2015-00008</b>	<b>INFOMAP</b>			
	<i>Integration of complex measurement information of thick products to optimise the through process geometry of hot rolled material for direct application</i>			
Info	Type of Project	Research	Duration (months)	42
	Total Budget	2.385.416 €	Start Date	01/07/2015
	EU Contribution	1.431.250 €	End date	31/12/2018

**Abstract** Measurement systems covering flatness and dimensional accuracy on plate/strip products are widely available. Output is usually in the form of contour plots or 'maps', providing visual feedback to mill operators who must interpret the information subjectively, and also to technical staff for investigative purposes. Objective interpretation of these maps is not straightforward, and comparison of output from devices of different type or manufacturer often presents further difficulties. The proposed project seeks to address this, developing a tool for objective interpretation of maps from different devices along the process route, generating concise data suitable for use within automatic control/advisory systems.

Coordinator	Country	Scientific person in charge
<b>ARCELORMITTAL ESPAÑA SA</b>	ES	Mr. Gabriel BONET
<b>Partners</b>		
<b>CENTRE DE RECHERCHES METALLURGIQUES ASBL</b>	BE	Mr Hugo UIJTDEBROEKS
<b>INDUSTEEL BELGIUM</b>	BE	Mr. Benjamin LECRENIER
<b>SWEREA MEFOS AB</b>	SE	M Sc Jan LEVEN
<b>SCUOLA SUPERIORE DI STUDI UNIVERSITARI E DI PERFEZIONAMENTO SANT'ANNA</b>	IT	Dr. Valentina COLLA
<b>VDEH-BETRIEBSFORSCHUNGSINSTITUT GMBH</b>	DE	Mr Roger LATHE



**TGS4 : Hot and cold rolling processes**

<b>RFSR-CT-2015-00009</b>	<b>LASER4ROLLS</b>			
	<i>Development of compound work rolls for hot mill finishing stands by Laser-cladding</i>			
Info	Type of Project	Research	Duration (months)	48
	Total Budget	1.920.389 €	Start Date	01/07/2015
	EU Contribution	1.152.233 €	End date	30/06/2019

Abstract

The objective is developing a new compound work roll system for the HSM finishing stands by exploiting the advantages of the laser-cladding to overlay a reusable steel arbour with a thick layer (20 mm) of enhanced tool steel materials. Key points will be defining the system requirements, lasercladding trials, modelling and materials evaluation. Modelling of the laser-cladding process, of abrasive wear and of thermal treatment combined with NDT measurements for a sound layer and bonding zone will lead to recommendations for this new processing route and a demonstrator (diameter 600mm, length 1m , layer 20 mm) will assess the feasibility.

Coordinator

**CENTRE DE RECHERCHES METALLURGIQUES ASBL**

*Country Scientific person in charge*

BE Ir Gisèle WALMAG

Partners

**LISMAR ENGINEERING B.V.**

NL Mr. Jack TENSEN

**FONDERIES J. MARICHAL, KETIN & CIE**

BE Eng. Mario SINNAEVE

**TATA STEEL NEDERLAND TECHNOLOGY B.V.**

NL Dr. Petrus Henk BOLT

**UNIVERSITEIT TWENTE**

NL Dr. Gert-Willem ROMER



**TGS4 : Hot and cold rolling processes**

<b>709920 (2016)</b>	<b>REDUWEARGUID</b>			
	<i>Reduction of wear on guiding components in hot strip mill</i>			
Info	Type of Project	Research	Duration (months)	42
	Total Budget	2.086.788 €	Start Date	01/07/2016
	EU Contribution	1.252.073 €	End date	31/12/2019

Abstract

The hot strip mill for flat products is still key part in the steel strip production. During the last decades, the plants were optimised and became more and more effective. Intensive work was done especially on the key process steps like mill stands, cooling sections, etc. Nevertheless some parts of the plant were not that much focused, like the guiding components. The project ReduWearGuid is aimed at reducing the wear on guiding components used in hot rolling mill (pinch roll, side guides, conveyor rolls) by the application of new type of lubricants, wear protective coatings or wear resistant materials for the guiding components. The main requirements for these guiding components are high resistance against abrasive and adhesive wear, thermal impact and corrosion. The increase of wear on the guiding components is a real problem because it induces:

- Plant downtimes for maintenance / repair / exchange of guiding components;
- Unnecessary downtimes due to unharmonised lifetime of the guiding components;
- Material defects caused by damage or by sticking of material;
- Lower product dimensional tolerance (damage on strip edge, etc.).

In order to develop individual solutions to reduce local mechanical and thermal wear, a multi-disciplinary approach will be used based on state-of-the-art characterisation, laboratory testing, modelling and production trials. The main objectives are the increased life time of guiding components, the reduction of production costs and downtimes and the reduction of surface defects on the strip.

Coordinator	<i>Country</i>	<i>Scientific person in charge</i>
<b>VDEH-BETRIEBSFORSCHUNGSINSTITUT GMBH</b>	DE	Dr. Delphine RECHE
Partners		
<b>FRAUNHOFER GESELLSCHAFT ZUR FOERDERUNG DER ANGEWANDTEN FORSCHUNG E.V.</b>	DE	Dr. Andreas KAILER
<b>THYSSENKRUPP STEEL EUROPE AG</b>	DE	Dr. Ingolf JÄCKEL
<b>FCT INGENIEURKERAMIK GMBH</b>	DE	Dr. Ulrich DEGENHARDT
<b>SCUOLA SUPERIORE DI STUDI UNIVERSITARI E DI PERFEZIONAMENTO SANT'ANNA</b>	IT	Dr. Valentina COLLA

# Technical Group Steel 5

## Finishing and coating

### The scope TGS5 includes:

- Heat treatment technology
- Chemical treatments, finishing and coating techniques including new technologies
- Coating development, including new coatings
- Surface characteristics
- Corrosion properties
- Standardisation of testing and evaluation methods
- Maintenance and reliability of production lines
- Reduction of emissions, energy consumption and improvement of the environmental impact
- Instrumentation, modelling and control of processes







<b>RFSR-CT-2015-00010</b>	<b>IMMARS</b>			
	<i>Integrated Material Modelling for Abrasion Resistant Steels</i>			
Info	Type of Project	Research	Duration (months)	36
	Total Budget	1.556.191 €	Start Date	01/07/2015
	EU Contribution	933.714 €	End date	30/06/2018

**Abstract**

The abrasion resistance of a material is not solely determined by the ratio of its hardness as compared to the hardness of the abrasive medium. It is also affected by other factors like:

- The surface state (topography, composition and microstructure);
- The level of residual stresses at the surface.

At the same time, systematic screening have indicated that the material's microstructure as well as its mechanical response to impact (strain hardening and damage accumulation) have a pronounced effect on the abrasion resistance. This effect is not captured in the conventional design criteria, where only the material hardness is taken into account. The IMMARS project objective is to develop an enhanced numerical model to link the surface state (i.e. topography, composition and structure), the level of residual stresses at the surface and the microstructure to the abrasion resistance, by:

- Lab-scale (open three body impact abrasion) and full-scale (cultivator tine rig) testing to measure abrasion resistance for different microstructural and
- operational conditions;
- Develop a micromechanically sound microscopic model that allows taking into account the microstructural features;
- Develop a mechanism informed macroscopic model specifically accounting for the deformation and damage/failure mechanism of the abrasion
- process;
- Develop a scaling method to link microstructural features with macroscopic abrasion damage;
- Validate the predictive capability of the micro- and macroscale models by simulation of the lab-scale coupon tests and full-scale cultivator tine tests;
- Applying the multiscale modelling approach to perform design optimization of microstructures with tailored property profiles.

Coordinator	Country	Scientific person in charge
<b>RHEINISCH-WESTFÄLISCHE TECHNISCHE HOCHSCHULE AACHEN</b>	DE	Dr.-Ing. Sebastian MÜNSTERMANN
Partners		
<b>ONDERZOEKSCENTRUM VOOR AANWENDING VAN STAAL N.V.</b>	BE	Dr. Filip VAN DEN ABEELE
<b>TECHNISCHE UNIVERSITÄT BRAUNSCHWEIG</b>	DE	Prof. Ludger FRERICHS
<b>UNIVERSITEIT GENT</b>	BE	Dr. Jacob SUKUMARAN
<b>TEKNOLOGIAN TUTKIMUSKESKUS VTT OY</b>	FI	Dr. Anssi LAUKKANEN



**TGS5 : Finishing and coating**

<b>RFSR-CT-2015-00011</b>	<b>MICROCORR</b>			
	<i>Improving steel product durability through alloy coating microstructure</i>			
Info	Type of Project	Research	Duration (months)	42
	Total Budget	1.789.066 €	Start Date	01/09/2015
	EU Contribution	1.073.439 €	End date	28/02/2019

Abstract

The project is devoted to the relationship between the metallic coating microstructure and corrosion resistance. Interactions between alloys coating components will be investigated in series of experiments using a number of innovative, mostly in-situ, electrochemical, corrosion and surface analytical techniques. A numerical model describing the effect of coating microstructure on the evolution of coated steel structures with time emphasizing Zn-Al and Zn-Al-Mg systems will be developed and validated by accelerated and field corrosion tests. It will allow coating developers to reduce the time to market for new generations of metallic coatings with superior long-term corrosion stability and lower coating thickness. The new products will be more cost-effective due to reduced use of raw materials providing thus competitive advantage to European steel industry and end-users.

Coordinator

**INSTITUT DE LA CORROSION SASU**

Country

FR

Scientific person in charge

Dr. Dominique THIERRY

Partners

**ARCELORMITTAL MAIZIERES RESEARCH S.A.**

FR

Dr. Christian ALLELY

**CENTRE NATIONAL DE LA RECHERCHE SCIENTIFIQUE**

FR

Prof. Kevin OGLE

**MAX-PLANCK-INSTITUT FÜR EISENFORSCHUNG GMBH**

DE

Dr. Michael ROHWERDER

**TATA STEEL NEDERLAND TECHNOLOGY B.V.**

NL

Dr. Nitte VAN LANDSCHOOT

**SWANSEA UNIVERSITY\*PRIFYSGOL ABERTAWE**

UK

Prof. James SULLIVAN

**VOESTALPINE STAHL GMBH**

AT

Dr. Gerald LUCKENEDER



**TGS5 : Finishing and coating**

<b>RFSR-CT-2015-00012</b>	<b>ORSC</b>			
	<i>Optimal Residual Stress Control</i>			
Info	Type of Project	Research	Duration (months)	42
	Total Budget	2.702.556 €	Start Date	01/07/2015
	EU Contribution	1.621.533 €	End date	31/12/2018

Abstract

Client demands for European steel sheet producers are facing a trend in product development where higher quality standards in terms of tighter material property tolerances are demanded. Producers today encounter great problems coupled to residual stresses where an increased number of customer complaints are experienced. Traditional control approaches are not sufficient anymore whereas this project will develop a new “residual-stressbased” control concept, validated at participating industrial partner plants, applicable by combining inline measurements and accurate modelling approaches. Thereby, material property-related homogenization will be facilitated resulting in noticeable increased product quality for European steel producers to successfully meet the market expectations.

Coordinator

**SWEREA MEFOS AB**

*Country*    *Scientific person in charge*

SE            Lic. Eng. Mats KARLBERG

Partners

**FRAUNHOFER GESELLSCHAFT ZUR FOERDERUNG DER ANGEWANDTEN FORSCHUNG E.V.**

DE            Dr. Bernd WOLTER

**HUGO VOGELANG GMBH & CO. KG**

DE            Dr. Andreas HESSLER

**INSTYTUT METALURGII ZELAZA IM. STANISLAWA STASZICA**

PL            Prof. Roman KUZIAK

**BÖHLER-UDDEHOLM PRECISION STRIP AB**

SE            Mr. Henrik SAMUELSSON

**VDEH-BETRIEBSFORSCHUNGSINSTITUT GMBH**

DE            Mr. Joachim DENKER



**TGS5 : Finishing and coating**

<b>709435 (2016)</b>	<b>HIJETROD PILOT</b>			
	<i>Resource-efficient hydromechanical descaling system for wire coils</i>			
Info	Type of Project	Pilot&Demonstration	Duration (months)	42
	Total Budget	974.853 €	Start Date	01/07/2016
	EU Contribution	487.426 €	End date	31/12/2019

Abstract

During rolling and annealing of steel, metal oxides (scale) are formed on the steel surface. The demand for further processing of steel is a scale-free surface. The achievement of a completely scale-free surface is expensive, especially for wire rod. In the forerunner project RFSR-CT-2010-00014 (HiJetRod) the great advantages of environmentally friendly high pressure water jet treatment were shown. Manually operated onsite tests have been performed with wire coils of three industrial partners. The descaling results are very good and the downstream pickling treatment of the treated coils can be reduced – the tests have shown a potential of 10% to 15% productivity increase of the pickling line.

For widespread application of the new descaling process, energy and water consumption of high pressure water jet treatment have to be reduced. For this purpose, new concepts for descaling (self-induced pulsating nozzles, acid resistant equipment, innovative shape of the coil rotation equipment) as well as spent water treatment and recycling will be investigated on a laboratory and pilot scale. For detailed evaluation of the reduction of pickling effort with the new descaling process in terms of consumables (energy, pickling acid and water), a life cycle assessment is included in the project.

The industrial integration of the developed process in a pickling line by this pilot and demonstration project is completely new and innovative. It is a logical and important step to reduce the high effort required for wire coil pickling and to replace resource-intensive pre-treatment. Besides the application for so-called swab-removable scale – scale loosened in a previous pickling step – other applications for the removal of organic/inorganic deposits will be tested. Authoritative data regarding the operational and investment costs for the installation of the high pressure water jet treatment will be determined to give a basis for investment decisions of potential users.

Coordinator	<i>Country</i>	<i>Scientific person in charge</i>
<b>VDEH-BETRIEBSFORSCHUNGSINSTITUT GMBH</b>	DE	Dr. Barbara WENDLER
Partners		
<b>VYSOKE UCENI TECHNICKE V BRNE</b>	CZ	Prof. Miroslav RAUDENSKY
<b>DEUTSCHE EDELSTAHLWERKE GMBH</b>	DE	Mr. Sebastian BANGE



**TGS5 : Finishing and coating**

<b>709694 (2016)</b>	<b>MACO PILOT</b>			
	<i>Optimisation of the mixed acid online monitoring and control in stainless steel pickling plants</i>			
Info	Type of Project	Pilot&Demonstration	Duration (months)	42
	Total Budget	1.920.363 €	Start Date	01/07/2016
	EU Contribution	960.182 €	End date	31/12/2019

Abstract

The European steel sector is under strong economic pressure due to the difficult global market conditions. This demands high flexible and favourable production while maintaining high product quality standards. The customized production of small lots of a wide range of special stainless steel grades distinguishes the European competitive advantage. Especially the pickling step is of high importance for stainless steel production as the product surface quality is a very essential attribute for the customers. In conjunction with the demanded high process flexibility the fast adjustment of defined concentrations in industrial mixed-acid pickling baths is of great importance for achieving consistently high product qualities and plant productivity. Available mixed acid concentration analysis techniques aren't capable to achieve these requirements. Thus, there is a great demand for advanced mixed acid online concentration supervision and pickling plant process control techniques. Within the RFCS project FLEXPROMUS an innovative method for continuous HF-HNO<sub>3</sub>-mixed-acid online analysis was successfully developed. First tests at two stainless steel strip pickling lines showed very promising results. However, further measuring technique optimisations are necessary to reach TRL 7. This pilot project addresses the optimisation of the innovative online concentration measuring technique concerning set-up, long-term reliability and operative range. Besides laboratory investigations and pickling process operation model developments, pilot scale tests shall be carried out at a stainless steel strip pickling line including acid regeneration, and for the first time at a wire rod plant. Finally, modernisation concepts for existing mixed acid pickling plants are to be developed. The overall goal of this pilot research project is the further optimisation of the mixed acid concentration monitoring and control in order to improve the pickling plant process operation and working conditions.

Coordinator	<i>Country</i>	<i>Scientific person in charge</i>
<b>VDEH-BETRIEBSFORSCHUNGSINSTITUT GMBH</b>	DE	Dr. Matthias WERNER

Partners		
<b>OUTOKUMPU NIROSTA GMBH</b>	DE	Mr. Karl-Heinz KIRCHHOFF
<b>DEUTSCHE EDELSTAHLWERKE GMBH</b>	DE	Mr. Sebastian BANGE
<b>UNIVERSIDAD DE OVIEDO</b>	ES	Dr. Iván MACHÓN GONZÁLES
<b>ACERINOX EUROPA SA</b>	ES	Mrs Esther QUIRÓS PINO
<b>SWEREA KIMAB AB</b>	SE	Dr. Karin JACOBSON



## Technical Group Steel 6

# Physical metallurgy and design of new generic steel grades

### The scope TGS6 includes:

- Precipitation, re-crystallisation, microstructure & texture and ageing
- Predictive simulation models on microstructures & mechanical properties
- Development of steel with improved properties at low and high temperatures such as strength and toughness, fatigue, wear, creep and resistance against fracture
- Magnetic properties
- New steel grades for demanding applications
- Standardisation of testing and evaluation methods





**TGS6 : Physical metallurgy and design of new generic steel grades**

<b>RFSR-CT-2015-00013</b>	<b>PRETICONTROL</b>			
	<i>Control of precipitation sequences during hot rolling to improve product uniformity of titanium containing high strength steels</i>			
Info	Type of Project	Research	Duration (months)	42
	Total Budget	2.113.428 €	Start Date	01/07/2015
	EU Contribution	1.268.057 €	End date	31/12/2018

## Abstract

The project aims to understand how precipitation of Ti, in conjunction with Nb and V, influences microstructure and property development during processing of high titanium (max. 0.15wt%) containing high strength steels (>700MPa) and hence make recommendations for compositions which are relatively insensitive to varying processing conditions. It will be achieved by characterization of precipitation sequences during the main stages of the hot rolling process. Influence of microalloying elements on austenite recrystallization behaviour and bainite phase transformation will be investigated by thermo-mechanical techniques coupled to high resolution characterization methods. Models will be developed and applied to optimise hot strip rolling strategy.

## Coordinator

**CENTRE DE RECHERCHES METALLURGIQUES ASBL**

## Country

BE

## Scientific person in charge

Mr Benjamin POHU

## Partners

**ASOCIACION CENTRO DE ESTUDIOS E INVESTIGACIONES TECNICAS**

ES

Dra Beatriz LOPEZ SORIA

**ONDERZOEKSCENTRUM VOOR AANWENDING VAN STAAL N.V.**

BE

Dr. Lieven BRACKE

**TATA STEEL UK LIMITED**

UK

Dr. Sally PARKER

**THYSSENKRUPP STEEL EUROPE AG**

DE

Dipl -Ing Georg PAUL

**THE UNIVERSITY OF GLASGOW**

UK

Dr. Ian MACLAREN



<b>RFSR-CT-2015-00014</b>	<b>INCROHSS</b>
	<i>Impact of two-phase region rolling on the microstructure and properties distribution in heavy gauge structural steel plate</i>
Info	Type of Project      Research      Duration (months)      42
	Total Budget      1.529.323 €      Start Date      01/07/2015
	EU Contribution      917.594 €      End date      31/12/2018

## Abstract

Heavy gauge line pipe and structural steel plate materials are often rolled in the two-phase region for strength reasons. However, strength and toughness show opposite trends and the exact effect of each rolling process parameter remains unclear. A stable process window can only be achieved by a more profound understanding of the microstructure development during the intercritical rolling and its relations with the final microstructure and properties. By means of recently developed microstructure investigation techniques and modelling, the relation between the temperature gradient, bcc-fcc balance at high temperature, strain partitioning between phases and subsequent transformation will be studied in detail to allow for wider process windows. Especially as there is a current trend in increasing the product thickness it is important to zoom in on the microstructure evolution and how it influences the processing window and the distribution of the final mechanical properties in these products. This project for first time will use a clear strategy to assess the potential opportunities and risks for the implementation or the consequences of intercritical rolling in an actual industrial product. By combining a systematic approach to map the behavior of each phase separately and looking at the global mechanical properties on the other hand a correlation will be developed to allow improved processing conditions for this type of products. In addition the current know-how and capabilities for microstructure investigation will allow developing an actual micro-mechanical model based on actual observations.

## Coordinator

**CENTRE DE RECHERCHES METALLURGIQUES ASBL***Country      Scientific person in charge*

BE      Mr Matteo CARUSO

## Partners

**ASOCIACION CENTRO DE ESTUDIOS E INVESTIGACIONES TECNICAS**

ES      Dr. Pello URANGA

**ONDERZOEKSCENTRUM VOOR AANWENDING VAN STAAL N.V.**

BE      Mrs Ulrike LORENZ

**TECHNISCHE UNIVERSITEIT DELFT**

NL      Dr. Ir. Jilt SIETSMA



**TGS6 : Physical metallurgy and design of new generic steel grades**

<b>RFSR-CT-2015-00015</b>	<b>LIGHTOUGH</b>			
	<i>Screening of tough lightweight Fe-Mn-Al-C steels using high throughput methodologies</i>			
Info	Type of Project	Research	Duration (months)	42
	Total Budget	1.086.144 €	Start Date	01/07/2015
	EU Contribution	651.686 €	End date	31/12/2018
Abstract	<p>Fe-Mn-Al-C steels show superior tensile properties at low density, which triggered further studies on other engineering properties but also on fundamental aspects. Stabilised by Mn and C, the dominant microstructure most compositions is austenitic, although formation of brittle phases needs to be avoided by a proper balance of Mn and C. Adding Al reduces the density and leads to the precipitation of nano-sized kappa carbides, which, if properly controlled by the right tempering conditions, effectively strengthen the material. Further, Al readily promotes the formation of ferrite, opening possibilities for application tailored microstructure variations, but also greatly increasing the alloy complexity. The ongoing steel design and development process is therefore often time consuming and of limited efficiency. This proposal deals therefore with the screening of toughness, density and strength of Fe-Mn-Al-C alloys, in quenched and quenched and tempered condition. Alloy compositions with interesting properties and their respective thermo-mechanical processing parameters will be systematically identified and refined following an iterative combinatorial approach. In parallel innovative methodologies will be fine-tuned and applied for thermodynamic modelling as well as for efficient high throughput sample generation, processing and testing. The targeted outcome is twofold:</p> <ul style="list-style-type: none"> <li>• Property and microstructure “maps” as a function of chemical composition and processing parameters provide the basis for future product development;</li> <li>• Innovative high-throughput methodologies enable to accelerate future steel alloy design.</li> </ul>			
Coordinator	<b>MAX-PLANCK-INSTITUT FÜR EISENFORSCHUNG GMBH</b>	Country	DE	Scientific person in charge Dr. Hauke SPRINGER
Partners	<b>KUNGLIGA TEKNISKA HÖGSKOLAN - THE ROYAL INSTITUTE OF TECHNOLOGY</b>	SE		Prof Malin SELLEBY
	<b>ONDERZOEKSCENTRUM VOOR AANWENDING VAN STAAL N.V.</b>	BE		Dr. Nele VAN STEENBERGE
	<b>STRATEGISCH INITIATIEF MATERIALEN VZW*SIM SIM-FLANDERS</b>	BE		Dr. Guido HUYBERECHTS



**TGS6 : Physical metallurgy and design of new generic steel grades**

**709418 (2016)** | **MUSTMEF**  
*Multi Scale Simulation Techniques for Metal Forming*

Info	Type of Project	Research	Duration (months)	48
	Total Budget	2.206.836 €	Start Date	01/07/2016
	EU Contribution	1.324.102 €	End date	30/06/2020

**Abstract**

This project aims at a breakthrough in modeling of AHSS. These steels are increasingly being used within the automotive industry but have a challenging forming behavior. This project aims at a breakthrough in modeling of AHSS. These steels are increasingly being used within the automotive industry but have a challenging forming behavior.

An extremely fast crystal plasticity code will be used to derive macroscopically observable anisotropic plastic properties from complex 3D artificial multi-phase microstructures. This will be directly coupled to efficient Multi-Scale code, leading to numerically very efficient state-of-the-art models for forming processes of dual-phase steels. The resultant multi-scale material model will be demonstrated for realistic microstructures in an industrial FE-Code to predict product properties after forming of a large automotive part.

Coordinator	Country	Scientific person in charge
<b>TATA STEEL NEDERLAND TECHNOLOGY BV</b>	NL	Dr. Piet KOK
<b>KATHOLIEKE UNIVERSITEIT LEUVEN</b>	BE	Prof. Albert VANBAEL
<b>MAX PLANCK INSTITUT FUR EISENFORSCHUNG GMBH</b>	DE	Dr. Franz ROTERS
<b>INPRO INNOVATIONSGESELLSCHAFT FUER FORTGESCHRITTENE PRODUKTIONSSYSTEME IN DER FAHRZEUGINDUSTRIE MBH</b>	DE	Dr. Kim KOSE
<b>THYSSENKRUPP STEEL EUROPE AG</b>	DE	Mr. Georg PAUL
<b>TECHNISCHE UNIVERSITEIT DELFT</b>	NL	Prof. Jilt SIETSMA

**TGS6 : Physical metallurgy and design of new generic steel grades**

709607 (2016)	TIANOBAIN			
	<i>Towards industrial applicability of (medium C) nanostructured bainitic steels</i>			
Info	Type of Project	Research	Duration (months)	42
	Total Budget	1.577.170 €	Start Date	01/10/2016
	EU Contribution	946.302 €	End date	31/03/2020
Abstract	<p>Excellent combinations of strength and toughness can be obtained from high-carbon nanobainite, but this requires high levels of alloying and long heat treatments. This project will develop very fine bainitic – austenitic steels more cost effectively from leaner medium carbon alloys using shorter processing times via thermomechanical ausforming. Tensile strengths above 1600MPa are aimed at to give hot rolled steels with enhanced wear resistance combined with good toughness. Suitable compositions and processing parameters will be developed using modelling and physical simulation. Trial products will be produced and tested using laboratory rolled materials, and recommendations for full-scale production parameters will be made.</p>			
Coordinator		<i>Country</i>	<i>Scientific person in charge</i>	
<b>AGENCIA ESTATAL CONSEJO SUPERIOR DE INVESTIGACIONES CIENTIFICAS</b>		ES	Dr. Carlos GARCIA-MATEO	
Partners				
<b>ONDERZOEKSCENTRUM VOOR AANWENDING VAN STAAL NV</b>		BE	Dr. Lode DUPREZ	
<b>THYSSENKRUPP STEEL EUROPE AG</b>		DE	Mr. Georg PAUL	
<b>OULUN YLIOPISTO</b>		FI	Dr. Mahesh SOMANI	



**TGS6 : Physical metallurgy and design of new generic steel grades**

<b>709711 (2016)</b>	<b>TOOLKIT</b>			
	<i>Toolkit for the design of damage tolerant microstructures</i>			
Info	Type of Project	Research	Duration (months)	36
	Total Budget	1.586.913 €	Start Date	01/07/2016
	EU Contribution	952.148 €	End date	30/06/2019

Abstract

Two measures can be applied to improve the sustainability of components subjected to mechanical loads. On the one hand, materials should be used that offer the optimum balance of mechanical properties. On the other hand, a full exploitation of the offered mechanical properties should be made possible. This project addresses the first measure. It aims to provide a simulation toolkit for the computer-assisted design of damage tolerant microstructures. In detail, the project presents an approach that is made up by three steps:

- Identification of mechanical property requirements through numerical simulations of full component behaviour. Therefore, parametric studies shall reveal the required hardening and fracture parameters that will help achieving a significantly improved structural performance;
- Finding microstructural configurations providing the required properties. This task is based on parametric studies on statistically representative artificial microstructure models;
- Identification of suitable processing parameters to adjust these tailored microstructures.

The project is based on the understanding that the conventional measures for mechanical property optimization have been widely exploited for many steel grades, so that tailoring the microstructure morphology is the most promising measure for future steel developments. The focus of the project lies in the development of the general method. Its applicability will only be demonstrated for two different examples. The project will bring added value in the following terms:

- Fostering sustainable component design options;
- Providing the method of tailoring steels for specific applications;
- Finding new mechanisms of material performance improvement;
- Improving the ICME approaches;
- Strengthening the position of steel products.

Coordinator	Country	Scientific person in charge
<b>RHEINISCH-WESTFAELISCHE TECHNISCHE HOCHSCHULE AACHEN</b>	DE	Dr.-Ing. Sebastian MÜNSTERMANN
Partners		
<b>ONDERZOEKSCENTRUM VOOR AANWENDING VAN STAAL NV</b>	BE	Dr. Filip VAN DEN ABEELE
<b>THYSSENKRUPP STEEL EUROPE AG</b>	DE	Mr Georg PAUL
<b>PANEPISTIMIO THESSALIAS</b>	EL	Prof. Nikolaos ARAVAS
<b>UNIVERSITEIT GENT</b>	BE	Prof. Patricia VERLEYSEN
<b>SOLINOURGEIA KORINTHOU ANONYMI ETAIREIA VIOMICHANIAS SOLINON KAI EKMETALLEFSIS AKINITON</b>	EL	Dr. Athanasios TAZEDAKIS



**TGS6 : Physical metallurgy and design of new generic steel grades**

<b>709755 (2016)</b>	<b>OPTIQPAP</b>			
	<i>Optimization of QP steels designed for industrial applications</i>			
Info	Type of Project	Research	Duration (months)	42
	Total Budget	2.699.139 €	Start Date	01/07/2016
	EU Contribution	1.619.483 €	End date	31/12/2019

Abstract

Despite significant research on microstructure, strength, ductility and strain hardening of advanced high strength steels (AHSS) processed via quenching and partitioning (Q&P) in the current literature, their application related performance has not yet been studied. The present OptiQPAP proposal focuses on intelligent microstructural design in the high strength Q&P steels for simultaneous improvement of various performance and mechanical properties, which are required for their commercialization. Special attention is paid to fatigue and fracture behaviour, wear resistance, weldability, ductile-brittle transition temperature, high strain rate behavior and energy absorption, along with the formability and bendability of Q&P steels.

Coordinator	<i>Country</i>	<i>Scientific person in charge</i>
<b>FUNDACION IMDEA MATERIALES</b>	ES	Dr. Ilchat SABIROV
Partners		
<b>UNIVERSITEIT GENT</b>	BE	Prof. Roumen PETROV
<b>THYSSENKRUPP STEEL EUROPE AG</b>	DE	Dr. Richard G. THIESSEN
<b>FUNDACIO CTM CENTRE TECNOLOGIC</b>	ES	Dr. Jose Maria CABRERA
<b>CENTRO SVILUPPO MATERIALI SPA</b>	IT	Dr. Andrea DI SCHINO
<b>TATA STEEL NEDERLAND TECHNOLOGY BV</b>	NL	Dr. Piet KOK
<b>TECHNISCHE UNIVERSITEIT DELFT</b>	NL	Prof. Jilt SIETSMA



**TGS6 : Physical metallurgy and design of new generic steel grades**

<b>709803 (2016)</b>	<b>NANOFORM</b>			
	<i>Improved formability in 3rd generation AHS steels by nanosize precipitation and microstructure control during and after hot rolling</i>			
Info	Type of Project	Research	Duration (months)	42
	Total Budget	1.956.922 €	Start Date	01/07/2016
	EU Contribution	1.174.153 €	End date	31/12/2019

Abstract

The goal of this project is to develop new Complex Phase Low Carbon Microalloyed Steels, by optimization of chemistry and thermomechanical processing, i.e. hot rolling and cooling, to simultaneously obtain refined microstructures and arrays of precipitate nanoparticles. The previously unexplored synergies between the elements Nb, Mo, V and Ti on precipitation before, during and after phase transformation from austenite during hot rolling and cooling will be also addressed. The project will result in new product concepts optimized with respect to processing parameter windows to give robust mechanical properties, i.e. static and fatigue strength, bendability, hole expandability and toughness.

Coordinator

**FUNDACIO CTM CENTRE TECNOLOGIC**

*Country*

ES

*Scientific person in charge*

Ms Silvia MOLAS

Partners

**SALZGITTER MANNESMANN FORSCHUNG GMBH**

DE

Dr. Marion BECHTOLD

**AGENCIA ESTATAL CONSEJO SUPERIOR DE INVESTIGACIONES CIENTIFICAS**

ES

Dr. Carlos CAPDEVILA

**INSTITUT NATIONAL DES SCIENCES APPLIQUEES DE LYON**

FR

Dr. Sophie CAZOTTES

**CENTRE NATIONAL DE LA RECHERCHE SCIENTIFIQUE CNRS**

FR

Frédéric DANOIX

**THYSSENKRUPP STEEL EUROPE AG**

DE

Dr. Kirill KHLOPKOV





**TGS6 : Physical metallurgy and design of new generic steel grades**

<b>709828 (2016)</b>	<b>MILDROLLING</b>		
	<i>Ultrafine grained steel long products by Multi-Pass Warm Caliber Rolling Technology</i>		
Info	Type of Project	Research	Duration (months) 42
	Total Budget	1.747.851 €	Start Date 01/07/2016
	EU Contribution	1.048.711 €	End date 31/12/2019

Abstract

The aim of this project is to produce submicron ultrafine grain (UFG) long steel products (ferrite-cementite microstructure) with high strength and adequate ductility for automotive and mechanical applications that can be further processed by cold forming or direct machining. The idea consists in producing UFG bars by multi-pass warm caliber rolling in the temperature range 500-700°C, exploiting as refining mechanism the dynamic recrystallization or recovery of ferrite induced by accumulation of strain during multipass deformation. The focus will be on medium and high carbon steels. The medium carbon steels are currently used in the manufacturing of automotive component and in this case the development of ultrafine microstructure can lead to improvement in strength and toughness and, accordingly, to a subsequent improvement of dynamic properties, as fatigue resistance and a higher reliability of safety components with direct impact on vehicle safety. About high carbon steels, a problem of using them for engineering applications is the fact that toughness deteriorates due to the high carbon content. Grain refinement is a method of improving toughness and strength simultaneously and could allow the use of high carbon steels for mechanical applications where high toughness levels are required. While previous research, both at European and worldwide levels, has been focused on validation of UFG technologies at laboratory scale, MILDROLLING project approach is extending validation to semi industrial scale in order to determine its industrial feasibility, to state mechanical properties of UFG steels for further processing and to establish the influence of those processes on grain size stability, aiming for a practical application and quick transferability to European car – making industry of UFG long steel products.

industry of UFG long steel products.

Coordinator	Country	Scientific person in charge
<b>CENTRO SVILUPPO MATERIALI SPA</b>	IT	Mrs Ilaria SALVATORI
Partners		
<b>RHEINISCH-WESTFAELISCHE TECHNISCHE HOCHSCHULE AACHEN</b>	DE	Mrs Alina MELZNER
<b>TECHNISCHE UNIVERSITAET BERGAKADEMIE FREIBERG</b>	DE	Prof. Rudolf KAWALLA
<b>ASOCIACION CENTRO TECNOLOGICO CEIT-IK4</b>	ES	Dr. Javier ALDZABAL
<b>GERDAU INVESTIGACION Y DESARROLLO EUROPA SA</b>	ES	Ms Zurine IDOYAGA
<b>ACCIAIERIE E FERRIERE DI PIOMBINO SPA</b>	IT	Dr. Alessandra MERIGO

**TGS6 : Physical metallurgy and design of new generic steel grades**

<b>709855 (2016)</b>	<b>HIGHQP</b>			
	<i>Controlling austenite stability by substitutional alloying elements in QP route</i>			
Info	Type of Project	Research	Duration (months)	42
	Total Budget	1.797.726 €	Start Date	01/07/2016
	EU Contribution	1.078.636 €	End date	31/12/2019

## Abstract

This proposal presents a new high temperature Quenching & Partitioning (Q&P) treatment where the stabilization of austenite is achieved not only by C diffusion but also by the diffusion of substitutional alloying elements. This innovative idea opens an unprecedented approach to produce martensite – austenite microstructures, which is expected to lead to a new 3rd generation advanced high strength steel family with enhanced formability. Investigations will combine advanced experimental techniques and the formulation of new models. It will lead to understand the partitioning behavior of substitutional elements in Q&P route and to determine the TRIP effect that an austenite stabilized by substitutionals can originate.

## Coordinator

**FUNDACION TECNALIA RESEARCH & INNOVATION***Country*    *Scientific person in charge*

ES    Dr. Maribel ARRIBAS

## Partners

**ARCELORMITTAL MAIZIERES RESEARCH SA**

FR    Dr. Artem ARLAZAROV

**CENTRO RICERCHE FIAT SCPA**

IT    Dr. Giuseppe DANDELO

**TECHNISCHE UNIVERSITEIT DELFT**

NL    Dr. Maria SANTOFIMIA

**SWEREA KIMAB AB**

SE    Mr. David MARTIN

## Technical Group Steel 7

# Steel products and applications for automobiles, packaging and home appliances

### The scope TGS7 includes:

- Technologies relating to the forming, cutting, welding and joining of steel and other materials
- Design of assembled structures to facilitate the easy recovery of steel scrap and its re-conversion into usable steels and techniques for recycling
- Steel-containing composites and sandwich structures
- Prolonging service life of steel products
- Standardisation of testing and evaluation methods





**TGS7 : Steel products and applications for automobiles, packaging and home appliances**

<b>RFSR-CT-2015-00016</b>	<b>JOININGTWIP</b>			
	<i>JoiningTWIP - TWIP-Steels for multi material design in automotive industry using low-heat joining technologies</i>			
Info	Type of Project	Research	Duration (months)	36
	Total Budget	2.134.379 €	Start Date	01/07/2015
	EU Contribution	1.280.628 €	End date	30/06/2018

Abstract

JoiningTWIP will support the introduction of TWIP-steels in applications of vehicle manufacturers by providing reliable joining technologies for multimaterial design of TWIP-steels with conventional steels and lightweight materials. The results of JoiningTWIP will shift the state of art concerning lightweight-related joining technologies significantly. Already established mechanical and low-heat joining technologies will be enhanced regarding their applicability in joining similar and dissimilar joints of TWIP-steels with conventional ultra high strength steels and traditional lightweight materials. The joining technologies examined in this project will be clinching, tack-setting, flow-drill screwing, rivet-element welding and friction element welding. The joints made with these specially adapted joining technologies will be tested comprehensively. The testing programme consists of metallographic analysis, determination of mechanical properties (static and crash loads, fatigue) and corrosion tests and even prototype tests under realistic conditions. This will allow end-users to consider TWIP-steels in further designs and constructions by providing them the needed mechanical and technological properties in joining this new steel-grade in multi-material design. Always in focus of the project is the applicability of the results for end-users. Therefore, the results will be directly comparable to already existing results of solutions made from conventional steels and will show the superior properties of multi-material designs made with TWIP-steels.

Coordinator	Country	Scientific person in charge
<b>SALZGITTER MANNESMANN FORSCHUNG GMBH</b>	DE	Dr. Tobias BOEDDEKER
Partners		
<b>COMTES FHT A.S.</b>	CZ	Mr Filip TIKAL
<b>CENTRO RICERCA FIAT SCPA</b>	IT	Dr. Daniele PULLINI
<b>EJOT GMBH &amp; CO. KG</b>	DE	Mr. Dirk RUNKEL
<b>THYSSENKRUPP STEEL EUROPE AG</b>	DE	Dr. Azeddine CHERGUI
<b>GOTTFRIED WILHELM LEIBNIZ UNIVERSITÄT HANNOVER</b>	DE	Dr. Thomas HASSEL
<b>UNIVERSITÄT PADERBORN</b>	DE	Mr. Marcus MATZKE

**TGS7 : Steel products and applications for automobiles, packaging and home appliances**

<b>RFSR-CT-2015-00017</b>	<b>HOTFORM</b>			
	<i>New multiphase AHSS steel grades for hot forming, with improved formability and reduced springback</i>			
Info	Type of Project	Research	Duration (months)	42
	Total Budget	1.756.120 €	Start Date	01/07/2015
	EU Contribution	1.053.672 €	End date	31/12/2018

## Abstract

In automotive lightweight design, AHSS components are one of the preferred alternatives, since they allow downsizing vehicle structures in a cost effective manner. Different AHSS grades are used according to the component required functionality, structural, stiffness, crash behaviour,... Cold forming of AHSS grades, in the range of 1.000MPa, implies high resulting springback and press force, limited formability, reduced post-forming ductility and low stretch flangeability, several operations needed for manufacturing complex geometry parts and large scrap is produced after trimming the addendum and blank-holder areas. HOTFORM proposes a new route for manufacturing multiphase AHSS grades (DP type and CP type), where the annealing stage, from the steel processing, is performed at the press shop, heating the blank sheet in a furnace and then hot forming the part, with cooled dies. This will be achieved by optimized steel alloying design and dilatometry testing and characterization, aiming at ensuring the stability of the required phase transformation kinetics over the combined thermal and deformation gradients, produced during hot forming. The benefits of hot forming will be: improved formability, no springback, reduced press forming forces, reduced raw material usage and produced scrap, only one forming operation for complex geometries,..The total energy usage will be optimized, as the energy used for annealing stage, from the steel processing, will be converted in the heating before the hot stamping. Reduced press forces and number of operations will account for production energy savings. Zn coated materials will be used, and the hot forming process will be designed to ensure the quality of the hot stamped parts (neither liquid metal embrittlement nor micr-cracks). Experimental tests will validate the new steels. An additional pursued benefit will be the possibility of integrating flanging operations during the hot stamping. This will be evaluated with CAE simulations.

## Coordinator

**FUNDACION TECNALIA RESEARCH & INNOVATION***Country Scientific person in charge*

ES Ing. Iñigo ARANGUREN MENDIETA

## Partners

**CENTRO RICERCHE FIAT SCPA**

IT Dr. Daniele PULLINI

**TATA STEEL NEDERLAND TECHNOLOGY B.V.**

NL Dr.ir. C.T.W. LAHAYE

**VOLKSWAGEN AG**

DE Dr. Christina SUNDERKOETTER



**TGS7 : Steel products and applications for automobiles, packaging and home appliances**

<b>RFSR-CT-2015-00018</b>	<b>ICUT</b>			
	<i>Integrative cutting solutions to produce high performance automotive components with high-Mn steel sheet</i>			
Info	Type of Project	Research	Duration (months)	42
	Total Budget	2.170.945 €	Start Date	01/07/2015
	EU Contribution	1.302.568 €	End date	31/12/2018

Abstract

The high mechanical strength of AHSS makes them especially susceptible to premature failure if defects are introduced in structural parts as a result of non-optimised cutting processes. The exceptional combination of strength and ductility of high Mn steel (HMnS) poses them as exceptional candidates for parts that needs high fatigue resistance and may contain defects from processing steps. Currently, there is a major lack of knowledge about the effects of the cutting processes on the mechanical properties and formability of HMnS. It hampers their extensive industrial application because nonoptimized cutting could lead to dramatic reduction of part performance. A detailed investigation regarding the quality of the cut edge, which determines fatigue and delayed fracture resistance, is required to face the industrial implementation of HMnS in structural vehicle parts. Moreover, the costs associated with cutting high strength sheets, as well as the environmental impact of the use of HMnS steels, have to be considered before industrial implementation. Press cutting is the most efficient cutting process but tool durability has a big impact on process efficiency and has to be assessed to develop competitive industrial process. A rational evaluation will be performed based on LCA of the of the substitution of currently used steels in the car body by TWIP steels. Thus, the objective of iCut is to provide the clues to overcome the detrimental effects of the imperfections introduced in cut edge during cutting processes on the fatigue, H-embrittlement sensitivity and formability of sheared areas of HMnS sheets aimed at obtaining the cutting parameters and cutting technology that allow producing high performance HMnS parts. Different cutting technologies will be studied, looking at process competitiveness and LCA evaluation. For press cutting, which is currently considered the most competitive cutting technology, tool durability and to the effect of tool wear on the evolution.

Coordinator	<i>Country</i>	<i>Scientific person in charge</i>
<b>FUNDACIO CTM CENTRE TECNOLOGIC- CTM</b>	ES	Mrs Jessica CALVO

Partners		
<b>CENTRO RICERCHÉ FIAT SCPA</b>	IT	Dr. Daniele PULLINI
<b>INDUSTRIELLT UTVECKLINGSCENTRUM I OLOFSTRÖM AB</b>	SE	Mr. Mikael KJELLBERG
<b>ROVALMA SA</b>	ES	Dr. Anwar HAMASAIID
<b>RHEINISCH-WESTFÄLISCHE TECHNISCHE HOCHSCHULE AACHEN</b>	DE	Prof. Dr.-Ing. Wolfgang BLECK
<b>SALZGITTER MANNESMANN FORSCHUNG GMBH</b>	DE	Dr. Stefan MÜTZE



**TGS7 : Steel products and applications for automobiles, packaging and home appliances**

<b>RFSR-CT-2015-00019</b>	<b>EFFIPRESS</b>			
	<i>Development of energy-efficient press hardening processes based on innovative sheet and tool steel alloys and thermo-mechanical process routes</i>			
Info	Type of Project	Research	Duration (months)	36
	Total Budget	2.210.210 €	Start Date	01/07/2015
	EU Contribution	1.326.127 €	End date	30/06/2018

Abstract

Increased emphasis on the lifecycle resource efficiency of automobiles is pushing the boundaries of contemporary steel grades. The implementation of the new SSAB steel grade enables the production of lightweight components with improved resource efficiency during the manufacturing and service cycles. The know-how on steel hot forming process necessary to exploit its potential market competitiveness edge, however, does not exist today. The objective of this project is to characterise and develop press hardening processes for this new DOCOL® 2000Bor steel alloy and featuring a tensile strength of 2000 MPa. In addition, investigations of the assisting heating and cooling processes and sheet forming are aimed at ensuring the comprehensive industrial applicability of the project. The cost-to-benefit advantages of this new steel grade can be demonstrated by the development and evaluation of automotive component prototypes. As reference for this evaluation, the commercially established DOCOL® 1800Bor steel alloy will be considered. For the development of the die tools, the new grade HTCS® 230 tool steel alloy will be optimized in order to be used for production dies considering the potential advantages that can be achieved with help of its enhanced thermal and mechanical properties along with reduced die construction cost. The project encompasses sheet and tube-based component processing workflows that finalise in dedicated prototypes of passive safety-critical parts. Material property and forming limit characterization of this steel sheets and tubes is followed by the experimental study of sheetforming and tube hydroforming processes with an emphasis on formability, tool loads and spring-back behaviour. Within the tube workflow the welding and heat treatment for improved properties and precision are assessed. The sheet and tube workflows are supported by forming FE simulations, and experimental tribological characterisation for the selection of appropriate coatings.

Coordinator	Country	Scientific person in charge
<b>TECHNISCHE UNIVERSITÄT CHEMNITZ</b>	DE	Mr Enrique MEZA GARCIA
Partners		
<b>GRUPO ANTOLIN-INGENIERIA S.A.</b>	ES	Mr. Diego VAL
<b>FUNDACIO CTM CENTRE TECNOLOGIC- CTM</b>	ES	Prof. José Maria CABRERA MARRERO
<b>FRAUNHOFER GESELLSCHAFT ZUR FOERDERUNG DER ANGEWANDTEN FORSCHUNG E.V.</b>	DE	Ms Anja RAUTENSTRAUCH
<b>ROVALMA SA</b>	ES	Dr. Anwar HAMASAIID
<b>SALZGITTER HYDROFORMING GMBH &amp; CO KG</b>	DE	Dipl.-Ing. Peter FREYTAG
<b>SSAB EMEA AB</b>	SE	Mr Thomas MÜLLER
<b>ZAPADOCESKA UNIVERZITA V PLZNI-UNIVERSITY OF WEST BOHEMIA</b>	CZ	Prof. Dr.-Ing. Bohuslav MASEK





**TGS7 : Steel products and applications for automobiles, packaging and home appliances**

<b>709601 (2016)</b>	<b>ULTRASLIM</b>			
	<i>ULTRA-fine austenitic stainless Steel as a Lightweight automotive Material</i>			
Info	Type of Project	Research	Duration (months)	42
	Total Budget	1.258.243 €	Start Date	01/07/2016
	EU Contribution	754.946 €	End date	31/12/2019

Abstract

The 300-series austenitic stainless steels (ASS) are an excellent choice for the automotive sector, but its use is limited by the price fluctuation due to the nickel content. Current low Ni grades of 200-series do not fully match the outstanding balanced properties 300-series steels, thus they are not considered a sound option for this sector. ULTRASLIM aims at developing ultrafine ASS – with low Ni content, high strength/ductility and good formability/weldability for the automotive industry. The new steels will be based on modifications of actual 201 ASS with an appropriate martensite thermomechanical treatment for ultrafine (< 1µm) austenitic microstructure production.

Coordinator

**CENTRO RICERCHE FIAT SCPA**

*Country Scientific person in charge*

IT Dr. Giuseppe DANIELO

Partners

**ACERINOX EUROPA SA**

ES Mrs Julia CONTRERAS F

**FUNDACION TECNALIA RESEARCH & INNOVATION**

ES Ms Teresa GUTIERREZ

**TWI LIMITED**

UK Mr. Sullivan SMITH



## Technical Group Steel 8

# Steel products and applications for building, construction and industry

### The scope TGS8 includes:

- Structural safety and design methods, in particular with regard to resistance to fire and earthquakes
- Technologies relating to the forming, cutting, welding and joining of steel and other materials
- Design of assembled structures to facilitate the easy recovery of steel scrap and its re-conversion into usable steels and techniques for recycling
- Prolonging service life of steel products
- Standardisation of testing and evaluation methods



**TGS8 : Steel products and applications for building, construction and industry**

<b>RFSR-CT-2015-00020</b>	<b>SLIMAPP</b>			
	<i>Slim-Floor Beams - Preparation of Application rules in view of improved safety, functionality and LCA</i>			
Info	Type of Project	Research	Duration (months)	36
	Total Budget	1.269.763 €	Start Date	01/07/2015
	EU Contribution	761.858 €	End date	30/06/2018

## Abstract

The aim is to increase the competitiveness of steel in buildings by developing the application of slim floor beams through improved rules for safety, functionality and LCA. Within a holistic approach considering all aspects of optimal technical and sustainable design, special focus is given to the composite action by reinforcing bars as efficient shear connectors. For normal design, new rules will fill the gap where slim floor solutions are currently not covered in Eurocode 4. Based on this new ULS and SLS design methodology, "pilot" projects will allow optimization of different composite slim floor solutions taking account of lifecycle assessment.

## Coordinator

**UNIVERSITAET STUTTGART***Country Scientific person in charge*

DE Prof.Dr.-Ing. Ulrike KUHLMANN

## Partners

**ARCELORMITTAL BELVAL & DIFFERDANGE S.A.**

LU Prof. Dr. Olivier VASSART

**LINDAB SA**

LU Mr Ernest HENDRICKX

**THE STEEL CONSTRUCTION INSTITUTE LBG**

UK Dr. R. Mark LAWSON

**UNIVERSITY OF BRADFORD**

UK Prof. Dennis LAM

**UNIVERSITA DEGLI STUDI DI TRENTO**

IT Prof. Riccardo ZANDONINI



**TGS8 : Steel products and applications for building, construction and industry**

<b>RFSR-CT-2015-00021</b>	<b>SHOWTIME</b>			
	<i>Steel Hybrid Onshore Wind Towers Installed with Minimal Effort</i>			
Info	Type of Project	Research	Duration (months)	36
	Total Budget	1.849.586 €	Start Date	01/07/2015
	EU Contribution	1.109.751 €	End date	30/06/2018

Abstract

More powerful wind turbines need higher towers (over 120 m) and therefore require new solutions which are economically justified and

environmentally friendly. The project goal is to find an economical solution based on a hybrid tower, comprising a steel lattice lower part and a steel tubular upper part. The solution is targeted at tall onshore applications which are more effective in energy generation in situations where wind shear profile is clearly benefiting higher turbines, for example near forests. The work will focus on:

- The erection process, in which the lattice portion of the tower is used as support for the installation of the upper tubular part of the tower and the turbine;
- The use of new type of steel for maintenance-free bolts and high strength steel grades for critical parts of the tower (the transition between the lattice and tubular parts);
- The optimization of design and construction of a low maintenance truss structure for the design life.

The work packages and the partnership are formed in order to address following issues:

- Optimal proportions and geometry of lattice and tubular parts of the hybrid structure, considering transport and crane size constraints; Conceptual design of several case studies will be performed;
- Competitiveness of solution in terms of structural performance and life cycle assessment; fabrication, construction and inservice maintenance must be minimized; alternative steel-intensive piled foundations will be considered;
- Practicality of erection process (using lower lattice part as support for sliding procedure); numerical simulations will be carried out and a small scale prototype will be constructed;
- Use of high strength steel grades for the lattice part and transition segment; several experimental tests are proposed in order to assess compressive strength of truss bars, stiffness of joints, feasibility of erection, resistance of transition segment and metallurgical characterization of bolts' steel.

Coordinator

**UNIVERSIDADE DE COIMBRA**

Country Scientific person in charge

PT Prof. Carlos REBELO

Partners

**FRIEDBERG PRODUKTIONSGESELLSCHAFT MBH**

DE Mrs Beatrix BRAND

**SIDENOR INVESTIGACION Y DESARROLLO EUROPA S.A.**

ES Dr. Diego HERRERO VILLALIBRE

**LULEÅ UNIVERSITY OF TECHNOLOGY**

SE Prof. Dr. Milan VELJKOVIC

**MARTIFER ENERGIA - EQUIPAMENTOS PARA ENERGIA, SA**

PT Mr Antonio Manuel MATOS SILVA

**RHEINISCH-WESTFÄLISCHE TECHNISCHE HOCHSCHULE AACHEN**

DE Prof. Dr.-Ing. Markus FELDMANN

**THE STEEL CONSTRUCTION INSTITUTE LBG**

UK Dr. Bassam BURGAN

**THE UNIVERSITY OF BIRMINGHAM**

UK Prof. Dr.-Ing. Charalampos BANIOPOULOS

**TGS8 : Steel products and applications for building, construction and industry**

<b>RFSR-CT-2015-00022</b>	<b>FREEDAM</b>			
	<i>FREE from DAMAge Steel Connections</i>			
Info	Type of Project	Research	Duration (months)	36
	Total Budget	1.449.860 €	Start Date	01/07/2015
	EU Contribution	869.915 €	End date	30/06/2018

## Abstract

The proposed research is aimed at the development of a new design strategy whose goal is the design of connections able to withstand without any damage the rotation demands due to seismic events, namely "Free From Damage Connections". Such innovative beam-to-column connections are equipped with friction dampers which are located at the bottom flange level of the connected beam to dissipate the earthquake input energy. The friction resistance is calibrated by acting on the number and diameter of bolts and their tightening torque governing the preloading. The flexural resistance results from the product between the damper friction resistance and the lever arm. The connections are conceived to exhibit wide and stable hysteresis loops without any damage to the connection steel plate elements. Therefore, the basic idea of the work is inspired to the strategy of supplementary energy dissipation, but it is based on the use of damping devices under a new perspective. In fact, while passive control strategies have been commonly based on the integration of the energy dissipation capacity of the primary structure by means of a supplementary dissipation coming from damping devices, conversely, the FREEDAM design strategy is based on the use of friction dampers conceived in such a way to substitute the traditional dissipative zones of MRFs, i.e. the beam ends. The development of FREEDAM connections has to be considered, on one hand, a first important goal because of the benefits coming from the cancellation of the connection repair costs in the aftermath of a seismic event and, on the other hand, a step towards the ambitious goal of free from damage buildings which will require, additionally, the identification of connection details, between non-structural components and primary structure, able to prevent also the damage to non-structural components (cladding panels, ceilings, plantfacilities, etc.) and systems to allow the structural recentering after severe seismic events.

## Coordinator

**UNIVERSITA DEGLI STUDI DI SALERNO***Country Scientific person in charge*

IT Prof. Vincenzo PILUSO

## Partners

**FIP INDUSTRIALE SPA**

IT Dr. Maria Gabriella CASTELLANO

**O FELIZ - METALOMECÂNICA, S.A.**

PT Dr. José Manuel SILVA

**UNIVERSITE DE LIEGE**

BE Prof. Jean-Pierre JASPART

**UNIVERSITA DEGLI STUDI DI NAPOLI FEDERICO II**

IT Prof. Dr. Raffaele LANDOLFO

**UNIVERSIDADE DE COIMBRA**

PT Prof. Dr. Luis SIMOES DA SILVA



**TGS8 : Steel products and applications for building, construction and industry**

<b>RFSR-CT-2015-00023</b>	<b>NEWREBAR</b>			
	<i>NEW dual-phase steel REinforcing BARs for enhancing capacity and durability of antiseismic moment resisting frames</i>			
Info	Type of Project	Research	Duration (months)	48
	Total Budget	1.911.052 €	Start Date	01/07/2015
	EU Contribution	1.146.631 €	End date	30/06/2019

**Abstract** One of the main requirements of the seismic-resistant reinforced concrete structures is a high global ductility, i.e. the ability to absorb energy during earthquakes. Another fundamental requirements of modern buildings is durability, in order to maintain an adequate safety level over time, minimizing the maintenance costs. This project aims to develop a new class of reinforcing bars using DP steels, which should guarantee better mechanical properties and improved corrosion resistance. DP steels have not yet used as reinforcing steel and they can represent a breakthrough for the European construction sector, allowing the realization of safer and more durable structures.

<b>Coordinator</b>	<i>Country</i>	<i>Scientific person in charge</i>
<b>UNIVERSITÀ DI PISA</b>	IT	Prof Walter SALVATORE

<b>Partners</b>		
<b>COMPAÑIA ESPAÑOLA DE LAMINACIÓN S.L.</b>	ES	Mr. Anders CARDONA
<b>FERRIERE NORD S.P.A.</b>	IT	Dr. Loris BIANCO
<b>INSTITUT FÜR STAHLBETONBEWEHRUNG EV</b>	DE	Dr.-Ing. Jörg MOERSCH
<b>INSTITUTO DE SOLDADURA E QUALIDADE</b>	PT	Mrs Maria Margarida PINTO
<b>RIVA ACCIAIO SPA</b>	IT	Eng Stefano BARAGIOLA
<b>SCUOLA SUPERIORE DI STUDI UNIVERSITARI E DI PERFEZIONAMENTO SANT'ANNA</b>	IT	Dr. Valentina COLLA
<b>UNIVERZA V LJUBLJANI</b>	SI	Prof. Matjaž DOLŠEK
<b>UNIVERSITY OF PATRAS* PANEPISTIMIO PATRON</b>	EL	Prof Charis APOSTOLOPOULOS





**TGS8 : Steel products and applications for building, construction and industry**

<b>RFSR-CT-2015-00024</b>	<b>JABACO</b>			
	<i>Development of Modular Steel Jacket for Offshore Windfarms</i>			
Info	Type of Project	Research	Duration (months)	42
	Total Budget	2.381.993 €	Start Date	01/07/2015
	EU Contribution	1.429.196 €	End date	31/12/2018

Abstract

Aim of JABACO is to develop a Modular Jacket concept composed by components of pre-qualified quality, for cost reduction of offshore wind farms. The concept is based on an integrated design considering water depths 30-80m, turbine sizes 5-10 MW, in the North Sea and the Mediterranean. Design of basic six cases, tests and numerical simulations of structural components conducted together with a sensitivity analysis. Deliverable is the "JABACO manual", containing procedure /recommendations for modular jacket design and the six case studies optimized, which will define a pathway to lowering cost of energy for upcoming offshore wind farms in European waters.

Coordinator

**CENTRO SVILUPPO MATERIALI SPA**

*Country Scientific person in charge*

IT Dr. Elisabetta MECOZZI

Partners

**INGENIERIA Y DISEÑO EUROPEO, SA**

ES Dr. Pablo COCA

**NATIONAL TECHNICAL UNIVERSITY OF ATHENS**

EL Prof. Spyros MAVRAKOS

**ONDERZOEKSCENTRUM VOOR AANWENDING VAN STAAL N.V.**

BE Dr. Philippe THIBAUX

**RAMBOLL MANAGEMENT CONSULTING GMBH**

DE Dr. Tim FISCHER

**PANEPISTIMIO THESSALIAS\*UNIVERSITY OF THESSALY**

EL Dr. Spyros A. KARAMANOS



**TGS8 : Steel products and applications for building, construction and industry**

<b>RFSR-CT-2015-00025</b>	<b>PROLIFE</b>		
	<i>Prolonging life time of old steel and steel-concrete bridges</i>		
Info	Type of Project	Research	Duration (months) 36
	Total Budget	1.514.602 €	Start Date 01/07/2015
	EU Contribution	908.761 €	End date 30/06/2018

Abstract

European bridges need refurbishment and strengthening to meet new demands of higher loads and new codes. Three distinctive ideas with potential of saving costs for the European community, reducing the environmental impact for the same result and minimizing the traffic disturbance:

- New composite action or strengthening of existing shear connectors by post installed shear dowels;
- Box action by horizontal trusses between the bottom flanges of I-girder bridges, transferring the very fatigue-sensitive I-girders into box girders;
- Effective strengthening of old truss bridges.

The multi-criteria decision scheme will be delivered reviewed by the expert group proposed by transport authorities.

Coordinator

**LULEÅ UNIVERSITY OF TECHNOLOGY**

Country

SE

Scientific person in charge

Prof. Peter COLLIN

Partners

**ALESSIO PIPINATO & PARTNERS ARCHITECTURAL ENGINEERING**

IT

Mr Alessio PIPINATO

**ARCELORMITTAL BELVAL & DIFFERDANGE S.A.**

LU

Prof. Dr. Olivier VASSART

**MOVARES NEDERLAND B.V.**

NL

Mr. Bert HESSELINK

**RAMBÖLL SVERIGE AB**

SE

Prof. Peter COLLIN

**SCHIMETTA CONSULT ZIVIL TECHNIKER GMBH**

AT

Dr. Roman GEIER

**UNIVERSIDADE DE COIMBRA**

PT

Prof. Dr. Luis SIMOES DA SILVA



**TGS8 : Steel products and applications for building, construction and industry**

<b>709434 (2016)</b>	<b>INNOSEIS</b>			
	<i>Valorization of innovative anti-seismic devices</i>			
Info	Type of Project	Accompanying Measure	Duration (months)	18
	Total Budget	995.660 €	Start Date	01/07/2016
	EU Contribution	597.392 €	End date	31/12/2017

Abstract

Valorization actions for 12 innovative anti-seismic devices will be undertaken. The devices were recently developed in the frame of RFCS, EU and national research projects by the partners involved in the project. Information documents for all devices will be produced for dissemination to all partners of the construction sector such as Architects, structural Engineers, construction companies, steel producers and all potential decision makers of the construction sector. These documents will be bundled in a volume for dissemination. The volume will be translated in several European languages. Criteria will be set on which it may be decided which of the devices are subject to CE marking in accordance with EN 15129 and which may be considered as innovative systems that require a code approval in EN 1998-1. For the latter pre-normative design recommendations will be drafted that will allow them to receive the status of code-approved systems. A reliability based methodological procedure to define values of behavior factors (q-factors) for building structures will be established. This procedure will be applied in turn to determine q-factors for structural systems with the anticipated devices. Case studies with application examples in which the devices are employed will be worked out. The case studies refer to new single story steel buildings, new multi-story steel-concrete composite buildings and to interventions for seismic upgrading of existing buildings. Seminars and Workshops will be organized in large parts of Europe. In addition, Seminars will be organized in non-European Mediterranean high seismicity countries to promote technologies and codes developed in Europe. A web site with free access to the users will be created and promoted to practice. Printed and electronic material will be produced and disseminated to all involved in the construction sector.

Coordinator	Country	Scientific person in charge
<b>NATIONAL TECHNICAL UNIVERSITY OF ATHENS - NTUA</b>	EL	Prof. Ioannis VAYAS
Partners		
<b>CONVENTION EUROPEENNE DE LA CONSTRUCTION METALLIQUE ASBL</b>	BE	Mrs Veronique DEHAN
<b>UNIVERSITEIT HASSELT</b>	BE	Prof. Herve DEGEE
<b>UNIVERSITET PO ARCHITEKTURA STROITELSTVO I GEODEZIJA</b>	BG	Prof. Nick RANGELOV
<b>MAURER SOHNE ENGINEERING GMBH &amp; CO KG</b>	DE	Dr. Christiane BUTZ
<b>RHEINISCH-WESTFAELISCHE TECHNISCHE HOCHSCHULE AACHEN</b>	DE	Prof. Benno HOFFMEISTER
<b>POLITECNICO DI MILANO</b>	IT	Prof. Carlo CASTIGLIONI
<b>UNIVERSITA DEGLI STUDI DI NAPOLI FEDERICO II.</b>	IT	Prof. Raffaele LANDOLFO
<b>UNIVERSITA DI PISA</b>	IT	Prof. Walter SALVATORE
<b>ISTITUTO SUPERIOR TECNICO</b>	PT	Prof. Luis CALADO
<b>UNIVERSITATEA POLITEHNICA TIMISOARA</b>	RO	Prof. Dan DUBINA



**TGS8 : Steel products and applications for building, construction and industry**

<b>709526 (2016)</b>	<b>REFOS</b>			
	<i>Life-Cycle Assessment of a Renewable Energy Multi-Purpose Floating Offshore System</i>			
Info	Type of Project	Research	Duration (months)	42
	Total Budget	1.826.177 €	Start Date	01/07/2016
	EU Contribution	1.095.706 €	End date	31/12/2019

Abstract

REFOS is an innovative project, aiming at the development, design and life-cycle assessment of a multi-purpose floating TLP steel platform, suitable for combined offshore wind/wave energy resources exploitation. It involves a multi-discipline partnership, which covers all aspects of REFOS platform analysis and design, through a systematic, integrated and state-of-the-art approach, validated through structural and hydrodynamic testing.

The ultimate target is the final design of REFOS platform and its components, in form of a detailed design report and specific drawings, suitable for two typical locations (one in the Mediterranean and one in the North Sea) and adjustable to the environmental conditions and design requirements of a specific offshore site. The final design is accompanied by a techno-economic analysis, demonstrating the feasibility of the proposed solution. Towards this target, detailed structural analysis is performed, together with hydro-elastic dynamic analysis of the floating system, accounting for the W/T and OWC devices.

The work in REFOS continues and extends the results of a national project, where a multi-purpose floating platform, suitable for the Aegean Sea, has been studied at a preliminary stage, but without structural design considerations.

The project has three phases:

- Definition of design parameters and environmental conditions at selected locations; hydro-aero-elastic analyses; air turbine design for wave energy;
- Structural design of the steel tower, platform, and tendons; mechanical testing and numerical simulations; testing of a scaled-down physical model in the Wave Tank;
- Final design & techno-economic life-cycle analysis; dissemination of results.

The proposed floating solution will constitute a breakthrough in renewable energy technology, allowing for cost-efficient exploitation of combined offshore wind/wave energy in Europe, towards new market opportunities for the steel- and the renewable-energy-industry.

Coordinator	Country	Scientific person in charge
<b>NATIONAL TECHNICAL UNIVERSITY OF ATHENS - NTUA</b>	EL	Prof. Spyridon MAVRAKOS
Partners		
<b>EUROPIPE GMBH</b>	DE	Dr. Oskar REEPMAYER
<b>ELLINIKI TECHNODOMIKI ANEMOS ANONIMI ETAIRIA PARAGOGIS ENERGIAS</b>	EL	Dr. Apostolos FRAGOULIS
<b>PANEPISTIMIO THESSALIAS</b>	EL	Prof. Spyros KARAMANOS
<b>INGENIERIA Y DISEÑO EUROPEO S.A.</b>	ES	Mr. Santiago LAVANDERA
<b>CENTRO SVILUPPO MATERIALI SPA</b>	IT	Ms Elisabetta MECOZZI



**TGS8 : Steel products and applications for building, construction and industry**

<b>709600 (2016)</b>	<b>PUREST</b>			
	<i>Promotion of new Eurocode rules for structural stainless steels</i>			
Info	Type of Project	Accompanying Measure	Duration (months)	18
	Total Budget	613.619 €	Start Date	01/07/2016
	EU Contribution	368.171 €	End date	31/12/2017
Abstract	<p>This project will disseminate new design guidance for structural stainless steel which has been developed over the last 10 years, primarily arising from RFCS-funded research.</p> <p>Activities are mostly targeted at design practitioners and include:</p> <ul style="list-style-type: none"> <li>• Updating and extending the Design Manual for Structural Stainless Steel (Third Edition);</li> <li>• Translating the Design Manual from English into 9 languages;</li> <li>• Developing online design software and design apps in accordance with the new stainless Eurocode rules;</li> <li>• National seminars;</li> <li>• Recording webinars for distance learning;</li> <li>• Publishing articles in national engineering journals.</li> </ul> <p>Teaching resources aimed at engineering students will also be prepared.</p> <p>Teaching resources aimed at engineering students will also be prepared.</p>			
Coordinator	<b>THE STEEL CONSTRUCTION INSTITUTE LBG</b>	<i>Country</i>	<i>Scientific person in charge</i>	
		UK	Mrs Nancy BADDOO	
Partners	<b>KATHOLIEKE UNIVERSITEIT LEUVEN</b>	BE	Prof. Barbara ROSSI	
	<b>CESKE VYSOKE UCENI TECHNICKE V PRAZE</b>	CZ	Dr. Michal JANDERA	
	<b>UNIVERSITAET DUISBURG-ESSEN</b>	DE	Prof. Natalie STRANGHÖNER	
	<b>UNIVERSITAT POLITECNICA DE CATALUNYA</b>	ES	Prof. Esther REAL	
	<b>TERASRAKENNEYHDISTYS RY</b>	FI	Mr. Pekka YRJÖLÄ	
	<b>CENTRO SVILUPPO MATERIALI SPA</b>	IT	Dr. Elisabetta MECOZZI	
	<b>POLITECNICA RZESZOWSKA IM IGNACEGO LUKASIEWICZA PRZ</b>	PL	Prof. Aleksander KOZLOWSKI	
	<b>ONE SOURCE CONSULTORIA INFORMATICA LDA</b>	PT	Mr. Luis CODEIRO	
	<b>UNIVERSIDADE DE COIMBRA</b>	PT	Prof. Luis SIMOES DA SILVA	
	<b>STIFTELSEN SVENSK STALBYGGNADSFORSKNING</b>	SE	Mr. Björn ÅSTEDT	
	<b>IMPERIAL COLLEGE OF SCIENCE TECHNOLOGY AND MEDICINE</b>	UK	Prof. Leroy GARDNER	



**TGS8 : Steel products and applications for building, construction and industry**

<b>709782 (2016)</b>	<b>OUTBURST</b>			
	<i>OpTimization of Steel Plated BRidges in Shape and STrength</i>			
Info	Type of Project	Research	Duration (months)	36
	Total Budget	1.608.411 €	Start Date	01/07/2016
	EU Contribution	965.046 €	End date	30/06/2019

Abstract

Curved steel panels are increasingly used in the design of new bridges due to architectural and/or structural demands. This is a recent trend which has resulted from technological advances that allow the economical use of curved shapes. However, design rules and design recommendations for curved plated members are still scarce and fundamental knowledge needs to be developed at various levels. The main objective of this research project is to develop solid knowledge on the structural behaviour of curved and nonrectangular steel panels (stiffened and unstiffened) made of mild steel and/or high strength steel for an integrated design approach taking into account also the aesthetic impact of bridges in the LCA assessment. The Structural Eurocodes do not cover the design of curved and nonrectangular panel segments. In fact, the scope of EN 1993-1-5 is limited to flat panels and EN 1993-1-6 is also not applicable to this type of elements since its scope is limited to shells of revolution. Design rules for curved and nonrectangular steel panels with and without stiffeners used in box-girder bridges and bridges with I-profile beams will be developed based on laboratory tests and extensive numerical parametric studies, and the following objectives will be targeted:

- Development of integrated design guidelines for the efficient, economic design of curved plated structures taking into account all relevant loading situations and design checks as well as the impact on the environment;
- To establish relevant interactions (dual flange/web role of curved cross-sections);
- To develop design rules for transverse stiffeners taking account of a possible dual flange/web role in curved panels;
- To optimize the number, shape and distribution of longitudinal stiffeners;
- To extend the plate buckling rules to plates with variable width, which are not yet in EN 1993-1-5, though they exist in bridges with curved shapes in transverse as well as in longitudinal direction.

Coordinator	Country	Scientific person in charge
<b>UNIVERSIDADE DE COIMBRA</b>	PT	Prof. Luis SILVA
Partners		
<b>ABES WAGNER &amp; PARTNER ZT-GMBH</b>	AT	Dr. Martin PIRCHER
<b>BILFINGER MCE GMBH</b>	AT	Mr. Guenther DORRER
<b>UNIVERSITAET STUTTGART</b>	DE	Prof. Ulrike KUHLMANN
<b>GRID INTERNATIONAL CONSULTING ENGINEERS SA</b>	PT	Prof. António REIS
<b>UNIVERZA V LJUBLJANI</b>	SI	Dr. Franc SINUR



**TGS8 : Steel products and applications for building, construction and industry**

<b>709807 (2016)</b>	<b>LASTEICON</b>			
	<i>LASER TECHNOLOGY FOR INNOVATIVE CONNECTIONS IN STEEL CONSTRUCTION</i>			
Info	Type of Project	Research	Duration (months)	42
	Total Budget	1.927.669 €	Start Date	01/07/2016
	EU Contribution	1.156.602 €	End date	31/12/2019

Abstract

LASTEICON aims to eliminate the use of excessive amount of stiffener plates and welding in steel joints, using laser cutting technology (LCT). The project will notably enhance the economy and sustainability of the fabrication as well as the aesthetic of any type of steel joints. Major focus is given to I-beam-to-CHS-column connections to promote hollow sections, since their excellent structural properties combined with their aesthetic appeal will lead decision makers (architects, building owners) to use more steel products in the building construction sector. Extendibility of the solution to other construction applications will be investigated with reference to steel truss girders.

Coordinator

**FINCON CONSULTING ITALIA SRL**

*Country*

IT

*Scientific person in charge*

Mr. carlo CASTIGLIONI

Partners

**UNIVERSITEIT HASSELT**

BE

Prof. Herve DEGEE

**VALLOUREC DEUTSCHLAND GMBH**

DE

Mr. Ralf HOJDA

**RHEINISCH-WESTFAELISCHE TECHNISCHE HOCHSCHULE AACHEN**

DE

Prof. Benno HOFFMEISTER

**INSTITUT NATIONAL DES SCIENCES APPLIQUEES DE RENNES**

FR

Prof. Mohammed HIJAJ

**OCAM S.R.L.**

IT

Mr. Andrea GALAZZI

**ADIGE-SYS SPA**

IT

Mr. Sergio RASO

**UNIVERSITA DI PISA**

IT

Prof. Walter SALVATORE

**INSTITUTO SUPERIOR TECNICO**

PT

Prof. Luis CALADO



**TGS8 : Steel products and applications for building, construction and industry**

<b>709892 (2016)</b>	<b>HOLLOSSTAB</b>			
	<i>Overall-Slenderness Based Direct Design for Strength and Stability of Innovative Hollow Sections</i>			
Info	Type of Project	Research	Duration (months)	36
	Total Budget	1.740.184 €	Start Date	01/07/2016
	EU Contribution	944.211 €	End date	30/06/2019

Abstract

In order to meet the increasing demands for sustainable & economic constructions, the European steel industry sees the increased use of more thin-walled sections and/or higher-strength steel grades as a main industrial goal. However, this leads to a number of scientific and engineering challenges, which stem from greatly increased relevance instability phenomena, as well as from the lack of appropriate design rules for slender, high-strength hollow sections. This project intends to address these points:

- "Direct" design rules for the cross-sectional strength of hollow sections will be developed, on the basis of the "Overall Interaction Concept". The method will lead to a continuous strength function for the class 1 to 4 range and take advantage of beneficial effects (mutual restraint, real stress state, strain hardening, ...). For CHS and EHS in particular, the new method will fill the current gap in design rules for class 3 and 4 sections;
- The method will be expanded for the applications in beam-columns and interactive L-G buckling;
- The elastic buckling behaviour of hollow sections will be studied in a systematic, (semi-)analytical way using the Generalized Beam Theory;
- The safety level of the new design rules will be ascertained on the basis of the methodology of EN 1990, making use of the test data provided in the project (physical and numerical tests) as well as production data regarding material properties and geometric tolerances provided by the industrial partners;
- The fields of application and of product improvement will be studied by R&D and engineering representatives of major steel industry stakeholders. Case-studies of structures built using traditional design rules will be re-assessed to determine the economic and technical advantages of the new design rules and developments in steel grades, shapes, and wall thicknesses;
- Specific design guidelines and tools (software) will be developed and made available to the industry.

Coordinator

**UNIVERSITAET DER BUNDESWEHR MUENCHEN**

Country

DE

Scientific person in charge

Prof. Ingbert MANGERIG

Partners

**CONDUCCIONES Y DERIVADOS SLU**

ES

Dr. Gorka Iglesias TOQUERO

**CENTRE TECHNIQUE INDUSTRIEL DE LA CONSTRUCTION METALLIQUE**

FR

Dr. Alain BUREAU

**INSTITUTO SUPERIOR TECNICO**

PT

Prof. Dinar CAMOTIM

**IMPERIAL COLLEGE OF SCIENCE TECHNOLOGY AND MEDICINE**

UK

Prof. Leroy GARDNER

**CONVENTION EUROPEENNE DE LA CONSTRUCTION METALLIQUE ASBL**

BE

Mrs Véronique DEHAN

**UNIVERSITE LAVAL**

CA



**TGS8 : Steel products and applications for building, construction and industry**

<b>709936 (2016)</b>	<b>OPTOSTEEL</b>			
	<i>Optimizing the toughness of high strength steel weld metal</i>			
Info	Type of Project	Research	Duration (months)	42
	Total Budget	1.556.567 €	Start Date	01/07/2016
	EU Contribution	933.940 €	End date	31/12/2019

## Abstract

For many steel constructions, high toughness of welds is a critical parameter to meet with current safety standards. For some high strength steel grades, HSS, the required weld metal toughness can be hard to reach due to non-uniform metallurgy achieved by means of standard welding techniques. Heterogeneous distribution of alloy elements of the wire filler metal into the weld seam, together high dilution levels, can lead to poor toughness in conventional welded HSS. For conventional laser arc hybrid welding, LAHW, of thick HSS plates, in addition, the narrow laser welding gaps associated to narrow-and-deep penetration hybrid welds limit the penetration of the elements added by the filler wire and, thus, the attainment of homogenous element distribution along the hybrid weld. As a consequence, scattering of the toughness data is obtained when testing at low temperature, down to -60° C. In the OptoSteel proposal, a novel experimental and simulation-based approach, combined with extensive toughness testing and a detailed metallurgical characterization of welds, will allow defining the new welding strategies and procedures, including filler metal development, aimed at ensuring homogeneous filler material distribution across the weld metal. This will lead to optimized weld metal toughness, enabled by using advanced laser welding techniques and methods, which are non-conventional LAHW and narrow gap multi-layer laser welding with wire addition, NGMLW.

## Coordinator

**LULEA TEKNISKA UNIVERSITET**

## Country

SE

## Scientific person in charge

Prof. Alexander KAPLAN

## Partners

**SALZGITTER MANNESMANN FORSCHUNG GMBH**

DE

Dr. Matthias HÖFEMANN

**THYSSENKRUPP STEEL EUROPE AG**

DE

Dr. Peter OHSE

**EQUIPOS NUCLEARES SA SME**

ES

Dr. Pedro VERON

**ASOCIACION DE INVESTIGACION METALURGICA DEL NOROESTE**

ES

Ms Gala PEREZ

**LINCOLN ELECTRIC EUROPE BV**

NL

Mr. Vincent VEN DER MEE

**TGS8 : Steel products and applications for building, construction and industry**

<b>709962 (2016)</b>	<b>DURAMECH</b>			
	<i>Towards Best Practice for Bolted Connections in High Strength Steels</i>			
Info	Type of Project	Research	Duration (months)	36
	Total Budget	1.693.185 €	Start Date	01/09/2016
	EU Contribution	1.015.911 €	End date	31/08/2019

## Abstract

The main goal of the proposed DURAMECH research project is to understand, predict and ultimately increase the fatigue resistance of bolted connections in moderately thick high strength steel materials, used in applications for heavy machinery. By combining a substantial experimental effort with advanced numerical methods, the fatigue properties of these joints will be assessed and compared with welded solutions that typically have a much lower fatigue resistance. At the same time, design guidelines and best practice modelling techniques for these types of connections will be derived. During the project the results are applied to relevant cases supplied by the end users.

## Coordinator

**KATHOLIEKE UNIVERSITEIT LEUVEN***Country Scientific person in charge*

BE Prof. Dimitri DEBRUYNE

## Partners

**ONDERZOEKSCENTRUM VOOR AANWENDING VAN STAAL NV**

BE Dr. Filip VAN DEN ABEELE

**CNH INDUSTRIAL BELGIUM**

BE Mr. Jean VANDENDRIESSCHE

**FRAUNHOFER GESELLSCHAFT ZUR FOERDERUNG DER ANGEWANDTEN FORSCHUNG E.V.**

DE Dr. Michael LUKE

**DAF TRUCKS NV**

NL Dr. Roel KERSTEN

**SSAB EMEA AB**

SE Dr. Eva PETURSSON



**TGS8 : Steel products and applications for building, construction and industry**

<b>710040 (2016)</b>	<b>REDUCE</b>		
	<i>Reuse and demountability using steel structures and the circular economy</i>		
Info	Type of Project	Research	Duration (months) 42
	Total Budget	2.143.810 €	Start Date 01/07/2016
	EU Contribution	1.286.286 €	End date 31/12/2019

Abstract

The project will provide methodologies, tools and guidance to assist in design for deconstruction, particularly of composite steel structures for multi-storey buildings. This will lead to new shear connection systems for demountable composite construction, based on push tests and beam tests to verify composite action and to develop design rules.

The whole life benefits of reusable structures will be quantified using LCA and circular economy indicators. Opportunities for greater standardisation and the use of BIM will be explored to facilitate deconstruction. A demonstration of demountability of the developed system is planned. Guidance on design for deconstruction and reuse will be prepared.

Coordinator

**THE STEEL CONSTRUCTION INSTITUTE LBG**

Country

UK

Scientific person in charge

Dr. Michael SANSOM

Partners

**LINDAB S.A.**

LU

Mr. Ernest HENDRICKX

**UNIVERSITE DU LUXEMBOURG**

LU

Prof. Christoph ODENBREIT

**TATA STEEL IJMUIDEN BV**

NL

Dr. Bauke HOEKSTRA BONNEMA

**STICHTING BOUWEN MET STAAL**

NL

Mr. Jan-Pieter DEN HOLLANDER

**TECHNISCHE UNIVERSITEIT DELFT**

NL

Prof. Milan VELJKOVIC

**AEC3 LTD**

UK

Mr. Nicholas NISBET

**UNIVERSITY OF BRADFORD**

UK

Prof. Dennis LAM



**TGS8 : Steel products and applications for building, construction and industry**

<b>710068 (2016)</b>	<b>SBRIPPLUS</b>			
	<i>Valorisation of Knowledge for Sustainable Steel-Composite Bridges in Built Environment</i>			
Info	Type of Project	Accompanying Measure	Duration (months)	24
	Total Budget	1.125.080 €	Start Date	01/07/2016
	EU Contribution	651.810 €	End date	30/06/2018

Abstract

Within the previous RFCS research project SBRI “Sustainable Steel-Composite Bridges in Built Environment”, a holistic approach was applied to steel-composite bridges by combining analyses of environmental, economic and functional qualities along the entire life-cycle of bridges. This proposal aims at the valorisation, the dissemination and the extension of the developed method for Advanced applications. A wide audience including bridge engineers and authorities should be reached, in order to assure the application of the project outcome.

Main tasks:

- Explanation of methodology and background by elaboration of worked examples and improvement of the SBRI-tool;
- Extension of bridge types by advanced application to innovative bridges across Europe demonstrating the flexibility and applicability of the methods developed;
- Dissemination activities (11 European languages, addition of national regulations and practices, organization of 13 workshops);
- Providing of recommendations for advanced applications and guidelines for bridge authorities.

Two design manuals will be prepared, drafted and translated in 11 European languages (CZ, EN, ES, FR, HR, DE, IT, NL, PT, PL, RO, SW) and distributed within the planned dissemination activities. Design Manual I includes background information on the methodology and worked examples for easy application in daily design work with the help of the improved software tool. By analyses of built examples across Europe the SBRI method is applied to innovative bridge solutions, results and conclusions are shown in Design Manual II. Another important task is providing of recommendations summing up and concluding the analyses and being the bases for guidelines to be elaborated for bridge authorities. The seminars around Europe offer the opportunity to present not only the results of the SBRI project, but also the advanced application to innovative solutions in addition to national regulations and practice.

Coordinator	Country	Scientific person in charge
<b>ARCELORMITTAL BELVAL &amp; DIFFERDANGE SA</b>	LU	Dr. Michael SANSOM
Partners		
<b>CESKE VYSOKE UCENI TECHNICKE V PRAZE</b>	CZ	Prof. František WALD
<b>FORSCHUNGSVEREINIGUNG STAHLANWENDUNG EV</b>	DE	Dr. Gregor NÜSSE
<b>AKTIEN-GESELLSCHAFT DER DILLINGER HÜTTENWERKE</b>	DE	Dr. Tobias LEHNERT
<b>UNIVERSITAET STUTTGART</b>	DE	Prof. Ulrike KUHLMANN
<b>S. STATHOPOULOS - K. FARROS CONSULTING ENGINEERS</b>	EL	Dr. Stamatis STATHOPOULOS
<b>FUNDACION TECNALIA RESEARCH &amp; INNOVATION</b>	ES	Mrs Amaia ARAMBURU
<b>INSTITUT FRANCAIS DES SCIENCES ET TECHNOLOGIES DES TRANSPORTS, DE L'AMENAGEMENT ET DES RESEAUX</b>	FR	Mr. André ORCESI
<b>SVEUCILISTE U ZAGREBU GRADEVINSKI FAKULTET</b>	HR	Prof. Darko DUJMOVIĆ
<b>UNIVERSITA DEGLI STUDI DI NAPOLI FEDERICO II.</b>	IT	Prof. Raffaele LANDOLFO

**STICHTING BOUWEN MET STAAL**

**BKE SPOLKA Z OGRANICZONA ODPOWIEDZIALNOSCIA**

**UNIVERSIDADE DE COIMBRA**

**BRISA ENGENHARIA E GESTAO SA**

**UNIVERSITATEA POLITEHNICA TIMISOARA**

**RAMBOLL SVERIGE AB**

**ATKINS LIMITED**

NL Dr. Ralph HAMERLINCK

PL Dr. Maciej KLÓSAK

PT Dr. Helena GERVÁSIO

PT Mr. Paulo BARROS

RO Prof. Viorel UNGUREANU

SE Prof. Peter COLLIN

UK Mr Chris HENDY



## Technical Group Steel 9

# Factory-wide control, social and environmental issues

### The scope TGS9 includes:

- Instrumentation, control and automation including artificial intelligence and information technologies
- Analytical techniques
- Working conditions and quality of life at the work place
- Energy, water and material flow management
- Ergonomic methods
- Occupational health and safety
- Reduction of exposure to occupational emissions
- Standardisation of testing and evaluation methods
- New processes for sustainable steel production
- Recovery and valorisation by-products
- Techniques for classification and preparation of steel scrap
- Control and protection of the environment in and around the workplace
- Restoration of steelwork sites
- Recovery of spent liquors
- Water treatment
- Life cycle assessment and sustainable products







**TGS9 : Factory-wide control, social and environmental issues**

<b>RFSP-CT-2015-00026</b>	<b>PLANTTEMP</b>			
	<i>Plant wide control of steel bath temperature</i>			
Info	Type of Project	Pilot&Demonstration	Duration (months)	36
	Total Budget	804.981 €	Start Date	01/07/2015
	EU Contribution	402.491 €	End date	30/06/2018
Abstract	<p>The objective of the Pilot &amp; Demonstration project is to develop an operator advisory system for through-process monitoring and control of the liquid steel temperature in order to improve the accuracy in meeting the target casting temperature with minimisation of energy and material consumptions.</p> <p>The through-process control system covers the complete process chain of electric steelmaking from the superheating phase in the EAF up to the end of the casting process in the tundish. The operator advisory system will evaluate the reliability of the information and give operational advice regarding appropriate measurement procedures and optimised set-points for the practices of the remaining treatment steps. For that purpose optimised measurement guidelines, model and sensor based monitoring systems and predictive control strategies are combined and applied. Thus the advisory system will help the operator to react in the optimal way on unscheduled variations in the temperature evolution. The following benefits shall be achieved by the application of the advisory system:</p> <ul style="list-style-type: none"> <li>• Support of the operator in judging the accuracy and reliability of the temperature information and recommendations for optimized operational practice;</li> <li>• Improved accuracy in meeting the target casting temperature;</li> <li>• Optimised resource efficiency with reduced electrical energy consumption;</li> <li>• Less interference with the casting speed, thus improved steel quality with higher reproducibility and productivity.</li> </ul> <p>The operator advisory system will be implemented, tested and validated at a well-equipped and instrumented electric steelmaking plant with a 140 t DC electric arc furnace, 2 ladle furnaces, a vacuum degasser, a final stirring station and a six strand continuous billet caster.</p>			
Coordinator	<b>VDEH-BETRIEBSFORSCHUNGSINSTITUT GMBH</b>		Country	<i>Scientific person in charge</i>
			DE	Dr. Tobias KORDEL
Partners	<b>GEORGSMARIENHÜTTE GMBH</b>		DE	Mr Bernd DETTMER

**TGS9 : Factory-wide control, social and environmental issues**

<b>RFSR-CT-2015-00027</b>	<b>PREVENTSECDUST</b>			
	<i>Prevention of secondary dust emissions in ironmaking plants using dust suppressants</i>			
Info	Type of Project	Research	Duration (months)	42
	Total Budget	2.002.593 €	Start Date	01/07/2015
	EU Contribution	1.201.556 €	End date	31/12/2018
Abstract	<p>The awareness of the importance of fine dust for human health increased strongly within the last years and with it the legislative regulations with regard to both emissions and occupational health. The project Prevention of secondary dust emissions in iron making plants using dust suppressants (PreventSecDust) will provide a major step to decrease the secondary dust emissions in iron making plants. It will cover all sources of secondary dust upstream to the blast furnace: Transport, storage and mechanical processing of raw materials and products. Tests with locally atomized aqueous dust suppressants showed good results with respect to dust suppression. However, almost no basic knowledge exists about the mechanisms of dust generation, the limits of the techniques or the influences on the processes involved. Finally, no technical devices exist, suitable for continuous, reliable operation in the hostile environment. Monitoring and control concepts are missing. The project starts with the investigation of the mechanisms of dust generation and propagation to derive the governing conditions. Local dust concentrations and relevant conditions will be measured at different locations and plants. This provides the knowledge necessary to develop tailor-made techniques and measures. Pilot spraying devices will be installed and extensive trials will be performed to derive guidelines for selection, concentration and dosing of dust suppressants. The design of the spraying devices will be optimised for continuous operational use with regard to effectiveness, maintenance and costs. Measuring and monitoring concepts will be developed. As well, new concepts for conventional dust suppression methods will be developed by DEM/CFD calculations. The new techniques will be completely assessed and will be integrated in existing dust prevention concepts to provide a new basis for the Best-Available-Techniques.</p>			
Coordinator	<b>VDEH-BETRIEBSFORSCHUNGSINSTITUT GMBH</b>	Country	DE	<i>Scientific person in charge</i> Dipl.-Ing. Kersten MARX
Partners	<b>ARCELORMITTAL INNOVACION, INVESTIGACION E INVERSION</b>	ES		Ms Beatriz GONZALEZ FERNANDES
	<b>MONTANUNIVERSITÄT LEOBEN</b>	AT		Dr. Michael PRENNER
	<b>TATA STEEL UK LIMITED</b>	UK		Dr. Neil HAINES
	<b>THYSSENKRUPP STEEL EUROPE AG</b>	DE		Mr Schwalbe Ralf
	<b>VOESTALPINE STAHL DONAWITZ GMBH</b>	AT		Mrs Sonja SCHADLER



**TGS9 : Factory-wide control, social and environmental issues**

<b>RFSR-CT-2015-00028</b>	<b>POWGETEG</b>			
	<i>Power generation from hot waste gases using thermoelectrics</i>			
Info	Type of Project	Research	Duration (months)	42
	Total Budget	2.381.665 €	Start Date	01/07/2015
	EU Contribution	1.428.999 €	End date	31/12/2018

Abstract

The possibilities of thermoelectric (TE) power generation using industrial gaseous waste heat at temperatures well above 550 °C will be determined in the PowGETEG project. Since the TE generators will be installed in the waste gas of an iron and steel manufacturing process, advanced components, materials and solutions need to be integrated in the TE generators and the electrical power subsystem. These requirements are determined by the high temperature level at which TE power generation will now be applied and the nature of such waste gases, that are produced when combusting iron and steel process gases like blast furnace gas or coke oven gas. Not only are such waste gases often fluctuating in temperature, composition and flow, they also contain particle matter that could lead to accretions on the surface of the heat exchanger of the TE generator, thus decreasing heat transfer, electrical power production and efficiency. Several waste heat sources of a German integrated steel mill will be studied, supported by both tests and data evaluation, in order to be able to detailly describe these waste gases. By testing both a bench scale unit and a demonstrator, which will able to produce about 1000 W, conclusions can be drawn about the requirements to process control, power conversion, heat exchanger design and the construction that supports the TE generator in the waste heat stream. These will then be used to study the techno-economic feasibility of implementing TE generators in high temperature waste gases and the effect it will have on energy efficiency of the integrated steel plant. This includes a comparison with other steam based power producing technologies and an extrapolation of the research results to other industries.

Coordinator

**VDEH-BETRIEBSFORSCHUNGSINSTITUT GMBH**

*Country Scientific person in charge*

DE Dr.-Ing. Frank MINTUS

Partners

**FUNDACION CETENA**

ES Mr. Jesús ESARTE

**GENTHERM EUROPE GMBH**

DE Mr. Rüdiger SPILLNER

**THYSSENKRUPP STEEL EUROPE AG**

DE Mr. Hans-Peter DOMELS

**THE UNIVERSITY OF GLASGOW**

UK Prof. Andrew KNOX



**TGS9 : Factory-wide control, social and environmental issues**

<b>RFSR-CT-2015-00029</b>	<b>GASNET</b>			
	<i>Optimization of the management of the process gases network within the integrated steelworks</i>			
Info	Type of Project	Research	Duration (months)	42
	Total Budget	1.849.502 €	Start Date	01/07/2015
	EU Contribution	1.109.701 €	End date	31/12/2018

Abstract

The project aims at improving the off-gases management within steelworks by minimizing gas amount that is burned in torch, air emissions, environmental impact and costs related to the waste of a resource and of CO2 allowances. A decision support tool for process operators and process support team is also developed simulating gas networks and optimizing gases distribution, by considering all the operating constraints. System dynamics and correlations between energy demands and gases production are fundamental for this analysis, as considerable savings can be achieved through transients proper management. Multi-period and multi-objective optimization techniques are applied to face this challenging objective.

Coordinator

**SCUOLA SUPERIORE DI STUDI UNIVERSITARI E DI PERFEZIONAMENTO SANT'ANNA**

Country

IT

Scientific person in charge

Dr. Valentina COLLA

Partners

**ARCELORMITTAL MAIZIERES RESEARCH S.A.**

FR

Dr. Valentine WEBER

**ARCELORMITTAL BREMEN GMBH**

DE

Mr. Santiago BASTIDA

**TATA STEEL NEDERLAND TECHNOLOGY B.V.**

NL

Dr. Pepijn PRONK

**VDEH-BETRIEBSFORSCHUNGSINSTITUT GMBH**

DE

Dipl.-Ing. Andreas WOLFF

**TGS9 : Factory-wide control, social and environmental issues**

<b>RFSR-CT-2015-00030</b>	<b>AUTOADAPT</b>
	<i>Novel automatic model identification and online parameter adaption for supporting the industrial deployment of model-based material property process control</i>
Info	Type of Project      Research      Duration (months)      42
	Total Budget      1.976.527 €      Start Date      01/07/2015
	EU Contribution      1.185.916 €      End date      31/12/2018

## Abstract

In the process route from hot-rolling to hot-dip galvanization, the homogeneity of the material properties often fails to meet increasing customer demands and there is an urgent need to improve processing systems here. Model-based automation is capable to solve this problem, but its value for the EU steel community is currently not fully exploited. Due to a cumbersome process of model generation, this technology is not widely deployed yet. The proposed expandable system aims to apply self-learning methods for adapting such automations to new products and plants. It will be implemented and tested in industrial scope. Easier commissioning will stimulate the industrial acceptance and distribution of model-based control, resulting in increased product quality for the EU steel industry.

## Coordinator

**VDEH-BETRIEBSFORSCHUNGSINSTITUT GMBH***Country      Scientific person in charge*

DE      Dr.-Ing. Jan POLZER

## Partners

**CENTRO SVILUPPO MATERIALI SPA**

IT      Mr Luigi LANGELLOTTO

**SCUOLA SUPERIORE DI STUDI UNIVERSITARI E DI PERFEZIONAMENTO SANT'ANNA**

IT      Dr. Valentina COLLA

**THYSSENKRUPP STEEL EUROPE AG**

DE      Dr. Thomas KEBE

**TGS9 : Factory-wide control, social and environmental issues**

<b>709553 (2016)</b>	<b>ROBOHARSH</b>			
	<i>Robotic workstation in harsh environmental conditions to improve safety in the steel industry</i>			
Info	Type of Project	Pilot&Demonstration	Duration (months)	36
	Total Budget	1.924.678 €	Start Date	01/07/2016
	EU Contribution	962.339 €	End date	30/06/2019
Abstract	<p>This project will disseminate new design guidance for structural stainless steel which has been developed over the last 10 years, primarily arising from RFCS-funded research.</p> <p>Activities are mostly targeted at design practitioners and include:</p> <ul style="list-style-type: none"><li>• Updating and extending the Design Manual for Structural Stainless Steel (Third Edition);</li><li>• Translating the Design Manual from English into 9 languages;</li><li>• Developing online design software and design apps in accordance with the new stainless Eurocode rules;</li><li>• National seminars;</li><li>• Recording webinars for distance learning;</li><li>• Publishing articles in national engineering journals.</li></ul> <p>Teaching resources aimed at engineering students will also be prepared.</p>			
Coordinator		Country	Scientific person in charge	
<b>SCUOLA SUPERIORE DI STUDI UNIVERSITARI E DI PERFEZIONAMENTO SANT'ANNA</b>		IT	Dr. Valentina COLLA	
Partners				
<b>POLYTEC SRL</b>		IT	Mr. Dario ABBÀ	
<b>PSC AUTOMATIZARI SI INSTALATII SRL</b>		RO	Mr. Raul PAL	



**TGS9 : Factory-wide control, social and environmental issues**

<b>709669 (2016)</b>	<b>CYBER-POS</b>			
	<i>Virtual Design of Cyber-Physical Production Optimization Systems for Long Production Factories</i>			
Info	Type of Project	Research	Duration (months)	42
	Total Budget	1.783.604 €	Start Date	01/07/2016
	EU Contribution	1.070.163 €	End date	31/12/2019

Abstract

Production technology in steel industry has reached a level that significant improvements can only be reached by through-process optimisation strategies instead of improving each process step separately. Therefore the connection of suitable technological models to describe process and product behavior, methods to find solutions for typical multi-criterial decisions and a strong communication between involved plants becomes mandatory.

Cyber-POS will develop a virtual simulation platform for the design of cyber-physical production optimization systems (CPPS) for long production facilities with special emphasis to thermal evolution and related material quality, leading to reduced energy consumption, shortened production time and improved product quality. Simulation and verification tools as well as a new IT framework for establishing the feasibility, safety and benefits of CPPS in the framework of “Steel Industry 4.0 Automation” will be introduced. Process (thermal, rolling, transport) models, material-quality models, logistics/scheduling models and communication (computers, software, networks) models are merged and used for production optimization, enabling fast dynamic and flexible reaction on changes in set-points, production routes, process disturbances or interruptions.

In this project the CPPS will be implemented at two long production facilities with the focus of reducing energy consumption plus reaching shortened production times at Mannstaedt (complex profiles) and at ArcelorMittal (rails) for increasing product quality.

Coordinator	Country	Scientific person in charge
<b>VDEH-BETRIEBSFORSCHUNGSINSTITUT GMBH</b>	DE	Dr. Jan POLZER
Partners		
<b>ASINCO GMBH</b>	DE	Dr. Dirk ZANDER
<b>MANNSTAEDT GMBH</b>	DE	Mr. Hermann WOLF
<b>FUNDACION ITMA</b>	ES	Dr. Armino GUERRERO
<b>ARCELORMITTAL ESPANA SA</b>	ES	Mr. Diego CARRASCAL
<b>SCUOLA SUPERIORE DI STUDI UNIVERSITARI E DI PERFEZIONAMENTO SANT'ANNA</b>	IT	Dr. Valentina COLLA

**TGS9 : Factory-wide control, social and environmental issues**

<b>710066 (2016)</b>	<b>DROMOSPLAN</b>			
	<i>Drones for autonomous monitoring of steel plants</i>			
Info	Type of Project	Research	Duration (months)	42
	Total Budget	1.857.589 €	Start Date	01/07/2016
	EU Contribution	1.114.553 €	End date	31/12/2019

## Abstract

Aim of this proposal is to evaluate the benefits arising from the application of Unmanned Aerial Vehicles (UAVs) in steelworks. So far UAVs have been deployed for military applications or used in small but growing number of civil applications, but never systematically in the steel industry. The goal is to substitute men in complex and expensive operations as those related to the monitoring, maintenance and safety of steel plant infrastructures. The implementation of real use cases with autonomous flight in two steel plant (TKSE, ILVA) and the experimental feasibility for indoor applications will prove the benefits deriving from UAV technology.

## Coordinator

**CENTRO SVILUPPO MATERIALI SPA**

## Country

IT

## Scientific person in charge

Dr. Roberto PIANCALDINI

## Partners

**VDEH-BETRIEBSFORSCHUNGSINSTITUT GMBH**

DE

Dr. Jan POLZER

**CLEES CHRISTIAN-ALEXANDER**

DE

Mr. Christian CLEES

**THYSSENKRUPP STEEL EUROPE AG**

DE

Mr. Tim KÖLSCHIED

**MBDA ITALIA SPA**

IT

Dr. Luca BANCALLARI

**CARDIFF UNIVERSITY**

UK

Dr. Dean STROUD