



Live Webinar

How can CEF help you set-up your eDelivery infrastructure?

28 October 2016



14 ⁰⁰	Introduction	Thomas Fillis
14 ²⁰	Introduction to message exchange infrastructures	Joao Rodrigues Frade
14 ³⁵	Message Exchange Models	Joao Rodrigues Frade
	Topologies	
	Protocols	
	Integration approach	
14 ⁵⁵	Discovery Models	Adrien Ferial
15 ¹⁰	Security Models	Maarten Daniels
	Trust circles	
	Security controls	
15 ²⁰	Technical Specifications	Adrien Ferial
	Sample Implementations	
	Q&A	All
15 ³⁰	End	

Introduction

by Thomas Fillis

Introduction to message exchange infrastructures Message Exchange Models **Topologies** Protocols Integration approach **Discovery Models** Security Models Trust circles Security controls **Technical Specifications** Sample Implementations **O&A** End

What happened before

26/07/16 CEF eDelivery - What's In It For You

26/05/16 Information session on AS4 Profile


25/05/16 eDelivery Extended Expert Group

19/05/16 CEF Digital Presents at the AMA

12/09/2016 Webinar - Electronic Registered Delivery Service (ERDS) and the eIDAS Regulation

More information on CEF Digital

Event Calendar







Today's speakers



Joao Rodrigues Frade

Head of the CEF Building Blocks sector in DIGIT



Adrien Ferial

Technical office leader of CEF eDelivery



Maarten Daniels Lead tester of CEF eDelivery




Moderated by

Thomas Fillis

Stakeholder Management Office in DIGIT

Highlights of the webinar





Benefits with an impact

10 TOP PRIORITIES OF THE EC

Jobs, growth and investments

Digital Single Market

Energy Union and Climate

Internal market

A deeper and fairer economic and monetary union

A balanced EU-US free trade agreement

Justice and fundamental rights

Migration

A stronger global actor

Democratic change

PROBLEM

- Europeans often face barriers when using online tools and services
- At present, markets are largely domestic in terms of online services
- Only 7% of EU small- and medium-sized businesses sell cross-border

SOLUTION

- This includes common EU data protection, copyright rules, boosting digital skills, accessible online content
- …and Cross-border
 Digital Public
 services (CEF Digital)

CONSEQUENCE

 Maximise economic potential, growth/jobs – anticipated to be 415€ billion to EU economy



Political support in the eGovernment Action Plan 2016 - 2020


DIGITAL PUBLIC SERVICES

Online • Transformative • Lean • Open



ACTION 6: The Commission will use the common building blocks such as CEF DSIs





HOW IS IT REGULATED?

CEF Regulation

The Connecting Europe Facility (CEF) is a regulation that defines how the Commission can finance support for the establishment of trans-European networks to reinforce an interconnected Europe.

CEF Telecom Guidelines

The CEF Telecom guidelines cover the specific objectives and priorities as well as eligibility criteria for funding of broadband networks and Digital Service Infrastructures (DSIs).

CEF Work Programme

Translates the CEF Telecom Guidelines in general objectives and actions planned on a yearly basis.



CEF Telecom – what does it finance











CEF Work Programmes






CEF DSIs have two key implementation instruments

A. CORE SERVICE PLATFORM

All information about the services offered by the European Commission focus on the building blocks.


https://ec.europa.eu/cefdigital/



B. GRANTS


All information about the grants: requirements, deadlines, how to apply, documentation

https://ec.europa.eu/inea/connecting-europefacility/cef-telecom







2016 GRANTS: Connecting Europe calls for proposals



* Includes eDelivery








eDelivery enables you to securely exchange data and documents



Deploying CEF eDelivery – today's focus





We invite you to be part of the CEF eDelivery & elnvoicing DSIs Stakeholder Days 2016 29 November - 1 December, Brussels

REGISTER TODAY

Introduction

Introduction to message exchange infrastructures


by Joao Rodrigues Frade

Message Exchange Models

Topologies Protocols Integration approach **Discovery Models** Security Models Trust circles Security controls **Technical Specifications** Sample Implementations **O&A** End

A message exchange infrastructure is

A combination of a message exchange model, discovery model and security model on top of the internet, or of a private network, to exchange structured or unstructured information wrapped in a messaging envelope.



The example of OpenPEPPOL

The Pan-European Public Procurement Online, the LSP of eProcurement, now transferred to the non-profit international association OpenPEPPOL.

The purpose of OpenPEPPOL is to enable European businesses to easily deal electronically with any European public sector buyers in their procurement processes, thereby increasing opportunities for greater competition for government contracts and providing better value for tax payers' money.

PARTY

PARTY

eDelivery

СЩ

of

Scope

PARTY



Data Exchange Agreements PEPPOL Transport Infrastructure Agreements (legal framework)

Payload PEPPOL Business Interoperability Specifications (document specifications)

> Message Exchange model 4-corner model (>100 APs) PEPPOL AS2 profile Service Providers

(Participant) Discovery model Dynamic discovery with a central SML and over 50 SMPs

> Security Model PKI-based security

> > Network Internet

> > > PARTY

п






The example of e-CODEX

The e-Justice Communication via Online Data Exchange, the LSP of eJustice, running until May 2016.

The e-CODEX project improves the cross-border access of citizens and businesses to legal means in Europe and furthermore creates the interoperability between legal authorities within the EU.



CEF eDelivery is not a one-size fits all solution


			e=codex	Your CEF eDelivery implementation
EXCHANGE MODEL	TOPOLOGY	4-corner model	4-corner model	Your choice
	PROTOCOL	PEPPOL AS2 profile	e-SENS AS4 profile	e-SENS AS4 profile recommended
	INTEGRATION APPROACH	ON Service Providers (Market) Specific Connector		Your choice
DISCOVERY MODEL		Dynamic	Static	Your choice
SECURITY	TRUST CIRCLE	PKI	Mutual trust	Your choice
MODEL	SECURITY CONTROL	Liberal inner security	Inner security with connector	Your choice
	MODEL DISCOVERY MODEL SECURITY	EXCHANGE PROTOCOL INTEGRATION APPROACH DISCOVERY MODEL TRUST CIRCLE	TOPOLOGY 4-corner model EXCHANGE PROTOCOL PROTOCOL PEPPOL AS2 profile INTEGRATION APPROACH Service Providers (Market) DISCOVERY MODEL TRUST CIRCLE FRUST CIRCLE PKI	EXCHANGE MODELTOPOLOGY4-corner model4-corner modelFROTOCOLPEPPOL AS2 profilee-SENS AS4 profileINTEGRATION APPROACHService Providers (Market)Specific ConnectorDISCOVERY MODELTRUST CIRCLEPKIMutual trustSECURITY CONTROLLiberal inner securityInner security with

Introduction Introduction to message exchange infrastructures

Message Exchange Models

Topologies	by Joao Rodrigues Frade
Protocols Integration approach	
Discovery Models	
Security Models Trust circles Security controls	
Technical Specifications	
Sample Implementations	
Q&A	
End	

Message exchange topologies: Overview






2 Corner model in detail

In the 2 corner model, backend systems communicate directly with each other through a point-to-point connection.

As a result, there is a need to set-up bilateral channels between every participant (when there is no common messaging protocol) or change backend systems to support the common protocol and impact the backends.

This is also known as the **Fully connected network**.



Furonean


3 Corner model in detail

In the 3 corner model, backend systems communicate with each other through a central hub.

Thanks to the fully centralised approach, parties exchange messages with each other via the central hub in 2 steps:

- Party A exchanges information with the Central Hub
- Central Hub exchanges information with Party B

This is also known as the Star network.




PROS

- No need to set up bilateral channels between participants.
- Central management and control of all processes



CONS

Central Access Point may become a bottleneck/single point of failure in the network.








4 Corner model in detail

In the 4 corner model, the backend systems of the users don't exchange data directly with each other but do this through Access Points. These Access Points are conformant to the same technical specifications and therefore capable of communicating with each other.

As a result, users can easily and safely exchange data even if their IT systems were developed independently from each other.

This is also known as the **Mesh network**





Introduction	
Introduction to message exchange infrastructures	
Message Exchange Models	
Topologies	
Protocols	by Joao Rodrigues Frade
Integration approach	
Discovery Models	
Security Models	
Trust circles	
Security controls	
Technical Specifications	
Sample Implementations	
Q&A	
End	

Message exchange protocols

PREDECESSORS

Many protocols were developed around the concepts in Electronic Data Interchange (EDI) but over the internet, some of which address the needs of specific industries or regions.

Scope of CEF eDelivery

AS4 based on WS*

WS* refers to a large set of specifications developed for standardizing aspects exchanging information using SOAP-based web services.

ebMS3/AS4 is a profile based on WS* standards developed by OASIS.

RESTFUL

REST refers to REpresentational State Transfer. It is a software architecture style, as well as a lightweight messaging protocol, for machine-to-machine information exchange directly using the network layer (HTTP).

NETWORK		SMTP	HTTP	FTP
MESSAGING	•••••••••••••••••	AS1	AS2	AS3
DATA			TEXT/MIME	



HTTP

XML/JSON



Message exchange protocols: Pros and Cons

CEF eDelivery

	PREDECESSORS	AS4 based on WS*	RESTFUL
PROS	Automated data validation and confirmation of message sent	Additional WS* specifications to enhance security and reliability Payload agnostic with clear separation of "Content" and data needed for secure, reliable delivery	Stateful Performant, scalable and easy to deploy
CONS	Supports "One-way Push" only Many standards and regular revisions causing limited cross-interoperability and lock-in partnerships High set-up cost (direct integration into the business application)	Heavy-weight XML standard	Reliability and security are not standardised Only supports basic messaging patterns: "One-Way Push" and "Two- way Synch"




Introduction	
Introduction to message exchange infrastructures	
Message Exchange Models Topologies Protocols	
Integration approach	by Joao Rodrigues Frade
Discovery Models	
Security Models Trust circles Security controls	
Technical Specifications	
Sample Implementations	
Q&A	
End	

Integration approach

It is key to determine how Backends will be integrated with the Access Points. Connectors may be built, bought or reused.

Some Access Point products offer advanced integration possibilities whereas others are purely for messaging purposes.

Services Providers may provide integration added-value services and at the same time operate the Access Point.



Interactive quiz

1. What is the recommended topology for eDelivery Infrastructures with thousands of participants (4-corner)

2. Does AS4 have features that support secure and reliable delivery of any type of content (yes)



Introduction Introduction to message exchange infrastructures Message Exchange Models Topologies Protocols Integration approach **Discovery Models** Security Models Trust circles Security controls **Technical Specifications** Sample Implementations **O&A** End

by Adrien Ferial

Discovery models

CEF eDelivery


Static

In a Static Service Location model the IP address and related attributes are static. The IP address of all the Access Points in the network are stored on a central location for the other Access Points to reference. To send a message, the sending Access Point looks a the static list of IP addresses on the networks' Domain Name System (DNS) to locate the Access Point of the receiver.

Dynamic

Dynamic Service Location enables the sending AP to dynamically discover the IP address and capabilities of the receiver. Instead of looking at a static list of IP addresses, the sender consults a **Service Metadata Publisher (SMP)** where information about every participant in the data exchange network is kept up to date. As at any point in time there can be several SMPs, every participant must be given a unique ID that must be published by **the Service Metadata Locator (SML)** on the network's Domain Name System (DNS). By knowing this URL, the sender is able to dynamically locate the right SMP and therefore the right receiver.

PROS & CONS



Less flexible, change of irrelevant references

More automated and flexible

Slower speed, as some overhead processing is required but

Dynamic discovery in detail


SML

The role of the SML (Service Metadata Locator) is to manage the resource records of the participants and SMPs (Service Metadata Publisher) in the DNS (Domain Name System). The SML is usually a centralised component in an eDelivery Messaging Infrastructure.

SMP

Once the sender discovers the address of the receiver's SMP, it is able to retrieve the needed information (i.e. metadata) about the receiver. With such information, the message can be sent. The SMP is usually a distributed component in an eDelivery Messaging Infrastructure.

Phase 1: Registration





Dynamic discovery in detail


SML

The role of the SML (Service Metadata Locator) is to manage the resource records of the participants and SMPs (Service Metadata Publisher) in the DNS (Domain Name System). The SML is usually a centralised component in an eDelivery Messaging Infrastructure.

SMP

Once the sender discovers the address of the receiver's SMP, it is able to retrieve the needed information (i.e. metadata) about the receiver. With such information, the message can be sent. The SMP is usually a distributed component in an eDelivery Messaging Infrastructure.

Phase 2: Operations



Interactive quiz

Quiz

- 1. If the SML is unavailable can Access Points still exchange messages? (yes)
- 2. If you have a limited and stable number of participants do you need dynamic discovery? (no)



Introduction Introduction to message exchange infrastructures Message Exchange Models **Topologies** Protocols Integration approach **Discovery Models** Security Models Trust circles Security controls **Technical Specifications** Sample Implementations **O&A** End

Trust circles: overview

Dedicated PKI

This trust architecture assumes that there is a dedicated PKI per policy domain that enables the eDelivery components (APs, SMPs and SML) to trust each other by sharing the common root CA (Certification Authority) certificate as a trust anchor.

To facilitate building of such a trust model, DIGIT provides support for the PKI services by establishing so-called eDelivery CA. The next section explains the architecture of the eDelivery CA.

Mutual exchange of certificates

Local trust store model assumes that each relying party, e.g. AP, SML, SMP, maintains its own repository of PKI certificates it trusts. Creation of a local trust store is the simplest way for relying parties to trust each other's certificates.

Using local trust stores does not require cross-certification between the PKIs that issued different certificates, nor does it require implementing mechanisms for processing complex certification paths, as all CAs in a path can be included in the local trust store.

Domain trusted list

The idea behind domain trusted lists is to enable service providers to use certificates issued by multiple CAs without the need to build complex cross-certification paths. For instance, a service provider who intends to operate APs and SMPs inside a policy domain will be able to use the certificates for these infrastructure components issued by a CA of its choice, as long as they comply with the domain policy.



Trust circles: Pros and cons

		Dedicated PKI	Mutual exchange of certificates	Domain trusted list
DIGIT	SETUP	Simple configuration as all components share the same CA	Integration of the SML containing all the SMP certificates in the network	Integration of the SML + Not supported by TLS protocol
	MAINTENANCE	Low maintenance as all components share the same CA	Maintain SML trust store and keep it up-to-date	Maintain the certificates of multiple domain trusted list issuers
POLICY DOMAIN	SCALABILITY	Easy to add/remove APs/SMPs as the have the same trust root.	All local trust stores need to be updated when a AP/SMP is changed	Adding/removing of AP/SMP can be done in a central place.
	FLEXIBILITY	Full reliance on the root CA certificate	Flexibility in choice of the CA provider + No single point of failure	Flexibility in choice of CAs but full reliance on the domain trusted list
	OPERATIONAL EFFORT	CA provided and managed by DIGIT	Significant effort to maintain the local trust stores	Maintenance of the domain trusted list + distribution of the certificate used to sign the trusted list
	соѕт	PKI architecture provided by DIGIT	No additional expenses on certificate infrastructure	Additional cost to establish and operate a domain trusted list
	SECURITY	Transparent certificate policy and accurate certificate status info	No direct control over certificate policies and trust store content	Accurate trust info in a domain trusted list

High score Medium score


Low score




Introduction Introduction to message exchange infrastructures Message Exchange Models Topologies Protocols Integration approach **Discovery Models** Security Models Trust circles Security controls **Technical Specifications** Sample Implementations **O&A** End

by Maarten Daniels

Approach to link eDelivery and eIDAS regulation




eDelivery Messaging Infrastructure based on the 4-Corner Model



Summary of security requirements from the eIDAS regulation

Requirement	Description	eIDAS reference Article 3 (36) Article 19 Article 24 Article 44, (d) the sending and receiving of data is secured by an advanced electronic signature or an advanced electronic seal of a qualified trust service provider in such a manner as to preclude the possibility of the data being changed undetectably;	
REQ1 Message Integrity	Messages should be secured against any modification during transmission.		
REQ2 Message Confidentiality	Messages should be encrypted during transmission.	Article 5 Article 19 Article 24	
REQ3 Sender Identification	The identity of the sender should be verified.	Article 24 Article 44 (b) they ensure with a high level of confidence the identification of the sender;	
REQ4 Recipient / Addressee Identification	Recipient / addressee Identity should be verified before the delivery of the message.	Article 24 Article 44 (c) they ensure the identification of the addressee before the delivery of the data;	
REQ5 Time-Reference	The date and time of sending and receiving a message should be indicated via a qualified electronic timestamp.	Article 44 (f) the date and time of sending, receiving and any change of data are indicated by a qualified electronic time stamp.	
REQ6 Proof of Send/Receive	Sender and receiver of the message should be provided with evidence of message sending and receiving.	Article 3 (36) " provides evidence relating to the handling of the transmitted data, including proof of sending and receiving the data"	

Mapping of security requirements to the 4-Corner Model



Summary of security controls

(*) Not exhaustive and it is by no means a guarantee that the system will be granted qualified status under the eIDAS regulation. For the process of granting the qualified status, please refer to the national supervisory body in the respective country.

Security control

Legal implications

CTR1 **Transport Layer Security (TLS) + Authentication** TLS protocols ensure authenticity and integrity of the message, by applying host to host cryptographic mechanisms

CTR2 Message Encryption

Message encryption ensures confidentiality of the message payload so that only the correct recipient can access it

CTR3: Electronic Seal of message

From technical perspective, electronic seal ensures integrity of the message header and payload and authenticity of origin

CTR4: Electronic Seal of evidence

Provides evidence to the sender C1 that the message was sent, delivered to the final recipient C4 and authenticity of destination

CTR5: Electronic Timestamp

Data in electronic form which binds other data in electronic form to a particular time establishing evidence that the latter data existed at that time

European General Data Protection Regulation (GDPR), in case of applicability.

European General Data Protection Regulation (GDPR), in case of applicability.

Non-qualified: Ensures integrity and origin of the data, in other words its authentication **Qualified**: eIDAS Regulation, Article 35. "A qualified electronic seal shall enjoy the presumption of integrity of the data and of correctness of the origin of that data" **Both**: Non-discrimination in legal proceedings


Non-qualified: Ensures date and time of the data.

Qualified: eIDAS Regulation, Article 41. "A qualified electronic time stamp shall enjoy the presumption of the accuracy of the date and the time it indicates and the integrity of the data to which the date and time are bound."

Both: Non-discrimination in legal proceedings




Mapping of security controls to the 4-Corner Model





Mapping of security controls to the 4-Corner Model



List of security controls applied to the e-SENS AS4 message protocol

Security control	Description			
CTR1 Transport Layer Security (TLS)	 Transport Layer Security (TLS 1.2 [9]) protocol is used, following ENISA security [7] and BSI [8] guidelines. For the sender identification is provided as follows: Basic authentication: C2 uses username/password to authenticate to C3. In this case, proper password management, including secure storage, sufficient complexity and regular updates need to be ensured by C2; Mutual authentication: This is done using the digital certificate of C2, allowing C3 to identify C3. 			
CTR2 Message Encryption	C2 encrypts the payload of the message using AES-GCM with a random secret key, and the random key with the public key of C3 using RSA-OAEP. Message encryption follows WS-Security using W3C XML Encryption The used cipher suite for symmetric encryption is: AES GCM-mode, and for asymmetric: RSA-OAEP. This should follow the ENISA security [7] and BSI [8] guidelines.			
CTR3: Electronic Seal of message	C2 applies an electronic seal to the message header and payload using its own private key which guarantees integrity protection. The seal is verified by C3 using C2 public key for authenticity and non-repudiation of the message payload and headers. Electronic sealing follows WS-Security with W3C XML Signing. The cipher suite is RSA-SHA256.			
CTR4: Electronic Seal of evidence	Electronic seal is applied to the receipt. Upon reception and verification of a message from C2, C3 generates an evidence receipt based on message identification information (e.g., message identifier, timestamp, and sender metadata) with a new timestamp and a reference to the received message, applies an electronic seal and returns the sealed evidence to C2. The receipt is sent automatically to C2 as a "signal" message response to the initial message. Electronic sealing follows WS-Security with W3C XML Signing. The used cipher suite is: RSA-SHA256.			
CTR5: Electronic Timestamp	Timestamp is placed at the WS-Security header, and it is electronically sealed for integrity protection. At this moment, by default, it is not a qualified time stamp and it relies on the system clock.			

Interactive quiz

Quiz

- 1. Do I receive, by default, the status of Qualified provider of Electronic Registered Delivery Services if I reuse CEF eDelivery? (no this status is given be the Supervisory Authorities)
- 2. Is the exchanged information encrypted when exchanged between Access Points? (yes)



Introduction Introduction to message exchange infrastructures Message Exchange Models **Topologies** Protocols Integration approach **Discovery Models** Security Models Trust circles Security controls **Technical Specifications** Sample Implementations **O&A** End

by Adrien Ferial

CEF eDelivery specifications

The approach employed by eDelivery is to promote the use of existing technical specifications and standards rather than to define new ones.

The profiling work of e-SENS and PEPPOL on these standards, i.e. constraining configuration choices, is equally taken on board. Even though eDelivery makes software available implementing these specifications, the use of commercial software or other Open Source software projects is also possible.

COMPONENT **KEY SPECIFICATIONS** e-SENS AS4 profile of the ebMS3/AS4 OASIS Standards Access \geq Point PEPPOL AS2 profile of AS2 and SBDH (for the eProcurement only) Digital ETSI - Electronic Signatures and Infrastructures profile \geq Certificates Service Metadata e-SENS Profile based on the OASIS BDXL Specification \geq Locator (SML) e-SENS ebCore Party ID Profile \geq Service Metadata e-SENS Profile based on the OASIS BDX-SMP Specification \geq Publisher (SMP) Connector **FTSI REM for evidences**



Introduction Introduction to message exchange infrastructures Message Exchange Models **Topologies** Protocols Integration approach **Discovery Models** Security Models Trust circles Security controls **Technical Specifications** Sample Implementations

by Adrien Ferial

Q&A End

e-SENS AS4 conformant solutions

European Commission > CEF Digital Home > CEF building blocks > eDelivery > eDelivery Services > eDelivery Software > Access Point software				More information on CEF Digita Conformant Solutions >	
eDelivery					
Home Discover How it works	Services Collaboration				
TECHNICAL SPECIFICATIONS	e-SENS AS4 confo	mant solutions		DOMIBUS	_
Access Point specifications Connector specifications	This page lists the solutions that have pas according to the e-SENS AS4 profile:	sed or are in the process of passing the conformanc	>e testing	Demibes	
PKI specifications SML specifications SMP soecifications	Domibus (EC sample implementation Flame	1)		FLAME	
SOFTWARE	Holodeak IBM Laurentius s Mendelson RSSBus A full list of other vendors supporting AS4 can be accessed at the bottom of this page.			HOLODECK	
 Access Point software e-SENS AS4 conformant solutions SML software 				IBM	
 SMP software Security Controls Connector software 				LAURENTIUS	
MANAGED SERVICES		Latest release Download Domibus v3.1.1			
PKI Service SML service TESTING SERVICES	Domibus *	Latest release Download Domibus v3.1.1 Test report Download (zip) Contact CEF-EDELIVERY-SUPPORT@	jeo.europa.eu	MENDELSON	
eDelivery Conformance testing eDelivery Connectivity testing	_	*(EC <u>sample implementation</u>)		RSSBus	
SUPPORTING SERVICES eDelivery Training and Deployment eDelivery Service desk	Flame	Latest release Download FMS Server and Lig	pht Client v5.3		
	CONFORMANT	Test report Download (zip) Contact info@flamems.com		Conformant Ongoing	
	Holodeck HOLO B2B	Latest release Download Holodeck B2B v2.0 Test report Download (zip) Contact info@holodeck-b2b.org			



Sample software maintained by the EC

DOMIBUS

Domibus is the European Commission's sample implementation of an AS4 conformant Access Point, based on the e-SENS AS4 profile.

Through the "Operational Management Board", CEF eDelivery stakeholders define the evolution of these solutions, by suggesting features that are then developed by the CEF's team.

BENEFITS

- Released under an open source license
- Viable solutions for use in production environment
- Fully supported by the European Commission
- Based on market-driven technical specifications

Software Providers Service Providers Policy Domains STATUS Service Documentation

USERS





Contact us

>

Introduction Introduction to message exchange infrastructures Message Exchange Models Topologies Protocols Integration approach **Discovery Models** Security Models Trust circles Security controls **Technical Specifications** Sample Implementations Q&A

End





We invite you to be part of the CEF eDelivery & elnvoicing DSIs Stakeholder Days 2016 29 November - 1 December, Brussels

REGISTER TODAY

Find out more on CEF Digital



The CEF Building Blocks

Supported by the Connecting Europe Facility (CEF), the CEF Building Blocks offer basic capabilities that can be used in any European project to facilitate the delivery of digital public services across borders.

elnvoicing	
eSignature	
eTranslation	





Learn More >

DIGIT

Directorate-General for Informatics

DG CONNECT

Directorate-General for Communications Networks, Content and Technology

Contact us

 (\mathbf{X})

CEF-BUILDING-BLOCKS@ec.europa.eu

© European Union, 2016. All rights reserved. Certain parts are licensed under conditions to the EU. Reproduction is authorized provided the source is acknowledged.